

Clark Forklift Model	V	BATTERY	CAPACITY		DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT
	T				(L)	(W)	(H)	(Lbs.)
Class 1 Trucks								
EC500-020(36/25") 33.50 25.00 23.00	36 V	18-85-15	595	20.9	31.8	23.6	22.9	1926
N/Cov. SB350Gry Connector 1620 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-020(36/26") 33.50 26.75 23.00	36 V	18-85-17	680	23.9	33.1	25.6	22.9	2142
N/Cov. SB350Gry Connector 1620 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-020(36/28") 33.50 28.75 23.00	36 V	18-85-17	680	23.9	33.1	26.5	22.9	2142
N/Cov. SB350Gry Connector 1620 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-020(48/25") 33.50 25.00 23.00	48 V	24-85-11	425	19.9	Call for more Info(630)851-5800			
N/Cov. SB350Gry Connector 1620 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-020(48/26") EC500-025(48/26") 33.50 26.75 23.00	48 V	24-85-13	510	23.9	30.6	25.4	22.9	2256
N/Cov. SB350Gry Connector 1620 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-020(48/28") 33.50 28.75 23.00	48 V	24-85-13	510	23.9	30.6	25.4	22.9	2256
N/Cov. SB350Gry Connector 1620 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-022 (36v) EC500-027 (36v) EC500-033 (36v) 39.50 40.00 23.75	36 V	18-85-33	1360	47.7	38.3	38.2	22.9	4032
N/Cov. SB350Gry Connector 3600 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-022 (48v) EC500-027(48v) EC500-060(48/40") EC500-033(48v) 39.50 40.00 23.75	48 V	24-85-25	1020	47.7	38.8	38.1	22.9	3984
N/Cov. SB350Gry Connector 3600 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-025 (36/26") 33.50 26.75 23.00	36 V	18-85-17	680	23.9	33.1	25.6	22.9	2142
N/Cov. SB350Gry Connector 1700 Min. Weight Term A18 4 wheel - Sit down Trk dims								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY
Compartment Size	L		Rate		in.	in.	in.	WEIGHT
	T		Ah	kWh	(L)	(W)	(H)	(Lbs.)
EC500-025 (36/28") 33.50 28.75 23.00	36 V	18-85-17	680	23.9	33.1	26.5	22.9	2142
N/Cov. SB350Gry Connector 1700 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-025(36/30") EC500-S030(36/30") 33.50 30.75 23.00	36 V	18-85-19	765	26.9	31.9	29.6	22.9	2340
N/Cov. SB350Gry Connector 1700 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-025(48/28") EC500-S030(48/28") 33.50 28.75 23.00	48 V	24-85-13	510	23.9	30.6	25.4	22.9	2256
N/Cov. SB350Gry Connector 1700 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-025(48/30") EC500-S30(48/30") 33.50 30.75 23.00	48 V	24-85P-15	595	27.8	32	29.5	22.9	2568
N/Cov. SB350Gry Connector 1700 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-060 (36/32") 39.50 32.00 23.75	36 V	18-85-27	1105	38.8	38.1	31.4	22.9	3240
N/Cov. SB350Gry Connector 3060 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-060(36/37") 39.50 37.00 23.75	36 V	18-85-31	1275	44.8	38.2	36.2	22.9	3780
N/Cov. SB350Gry Connector 3060 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-060(36/40") EC500-070(36/40") EC500-080(36/40") 39.50 40.00 23.50	36 V	18-85-33	1360	47.7	38.3	38.2	22.9	4032
N/Cov. SB350Gry Connector 3491 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-060(48/32") 39.50 32.00 23.75	48 V	85-19	765	35.8	Call for more Info(630)851-5800			
N/Cov. SB350Gry Connector 3060 Min. Weight Term A18 4 wheel - Sit down Trk dims								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT
	T				(L)	(W)	(H)	(Lbs.)
EC500-060(48/37")	48 V	24-85-23	935	43.8	38.2	35.6	22.9	3648
EC500-070(48/37")								
39.50 37.00 23.75								
N/Cov. SB350Gry Connector 3060 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-070(36/37")	36 V	18-85-31	1275	44.8	38.2	36.2	22.9	
39.50 37.00 23.50								3780
N/Cov. SB350Gry Connector 3491 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-070(48/40")	48 V	24-85-25	1020	47.7	38.8	38.1	22.9	3984
EC500-080 (48/40")								
39.50 40.00 23.50								
N/Cov. SB350Gry Connector 3491 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-100 (36v)	36 V	6-85-19	1530	107.4	Call for more Info(630)851-5800			
46.25 39.62 24.00								
(2) 18 Cell								
W/Cover SB350Gry Connector 3450 Min. Weight Term A18 4 wheel - Sit down								
EC500-100 (48v)	48 V	24-85-29	1190	55.7	44.8	38.2	23.3	4656
46.25 39.62 24.00								
W/Cover SB350Gry Connector 3450 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-120 (36v)	36 V	6-85-19	1530	107.4	Call for more Info(630)851-5800			
46.25 39.62 24.00								
(2) 18 Cell								
W/Cover SB350Gry Connector 4250 Min. Weight Term A18 4 wheel - Sit down								
EC500-120 (48v)	48 V	24-85-29	1190	55.7	44.8	38.2	23.3	4656
46.25 39.62 24.00								
W/Cover SB350Gry Connector 4250 Min. Weight Term A18 4 wheel - Sit down Trk dims								
EC500-S30 (36/26")	36 V	18-85-17	680	23.9	33.1	25.6	22.9	2142
33.50 26.75 23.00								
N/Cov. SB350Gry Connector 1700 Min. Weight Term A18 4 wheel - Sit down Trk dims								
ECG20 (36/30")	36 V	18-85-25	1020	35.8	38.1	29.1	22.9	2988
ECG25 (36/30")								
ECG30 (36/30")								
39.25 30.50 23.50								
N/Cov. SB350Gry Connector 2600 Min. Weight Term A18 Rider-Sit down Trk dims								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY	DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY	
Compartment Size	L		Rate		in.	in.	in.	WEIGHT	
	T		Ah	kWh	(L)	(W)	(H)	(Lbs.)	
ECG20 (36/34") ECG32(36/34") ECG25(36/34") ECG30(36/34") 39.25 34.50 23.50	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	3492	
N/Cov. SB350Gry Connector 3000 Min. Weight Term A18 4 wheel - Sit down									
ECG20 (48/34") ECG32(48/34") ECG25(48/34") ECG30(48/34") 39.25 34.50 23.50	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408	
N/Cov. SB350Gry Connector 3000 Min. Weight Term A18 4 wheel - Sit down									
ECG20(48/30") ECG25(48/30") ECG30(48/30") 39.25 30.50 23.50	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120	
N/Cov. SB350Gry Connector 2600 Min. Weight Term A18 Rider-Sit down Trk dims									
ECS 10 (36/34") ETL 10 38.90 34.40 23.15	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	3492	
N/Cov. SB350Gry Connector 3300 Min. Weight Term A18 Rider-Sit down Trk dims									
ECS 10 (48/34") 38.90 34.40 23.15	48 V	85-21	Call for more Info(630)851-5800						
N/Cov. SB350Gry Connector 3300 Min. Weight Term A18 Rider-Sit down Trk dims									
ECS 25(36/34") 38.90 34.40 23.15	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	3492	
N/Cov. SB350Gry Connector 3000 Min. Weight Term A18 Rider-Sit down Trk dims									
ECS 25(48/30") 38.90 30.40 23.15	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120	
N/Cov. SB350Gry Connector 2850 Min. Weight Term A18 Rider-Sit down Trk dims									
ECS17 (36/27") 38.90 27.50 23.15	36 V	18-85-23	935	32.8	38.1	26.9	22.9	2736	
N/Cov. SB350Gry Connector 1900 Min. Weight Term A18 Rider-Sit down Trk dims									

Clark Forklift Model	V	BATTERY	CAPACITY		DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR	RATE	X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT
	T				(L)	(W)	(H)	(Lbs.)
ECS17(36/30") 38.90 30.40 23.15	36 V	18-85-25	1020	35.8	38.1	29.1	22.9	2988
N/Cov. SB350Gry Connector 2400 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS17(36/34") 38.90 34.40 23.15	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	3492
N/Cov. SB350Gry Connector 2600 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS17(48/27") 38.90 27.50 23.15	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
N/Cov. SB350Gry Connector 1900 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS17(48/30") 38.90 30.40 23.15	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120
N/Cov. SB350Gry Connector 2400 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS17(48/34") 38.90 34.40 23.15	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
N/Cov. SB350Gry Connector 2600 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS20 (36/27") 38.90 27.50 23.15	36 V	18-85-23	935	32.8	38.1	26.9	22.9	2736
N/Cov. SB350Gry Connector 2200 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS20(36/30") 38.90 30.40 23.15	36 V	18-85-25	1020	35.8	38.1	29.1	22.9	2988
N/Cov. SB350Gry Connector 2400 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS20(36/34") 38.90 34.40 23.15	36 V	18-85-29	1190	38.41	38.2	33.6	22.9	3492
N/Cov. SB350Gry Connector 2600 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS20(48/27") 38.90 27.50 23.15	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
N/Cov. SB350Gry Connector 2200 Min. Weight Term A18 Rider-Sit down Trk dims								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY
Compartment Size	L		Rate		in.	in.	in.	WEIGHT
	T		Ah	kWh	(L)	(W)	(H)	(Lbs.)
ECS20(48/30") 38.90 30.40 23.15	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120
N/Cov. SB350Gry Connector 2400 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS20(48/34") 38.90 34.40 23.15	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
N/Cov. SB350Gry Connector 2600 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS25 (36/27") 38.90 27.50 23.15	36 V	18-85-23	935	32.8	38.1	26.9	22.9	2736
N/Cov. SB350Gry Connector 2700 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS25(36/30") 38.90 30.40 23.15	36 V	18-85-25	1020	35.8	38.1	29.1	22.9	2988
N/Cov. SB350Gry Connector 2850 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS25(48/27") 38.90 27.50 23.15	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
N/Cov. SB350Gry Connector 2700 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS25(48/34") 38.90 34.40 23.15	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
N/Cov. SB350Gry Connector 3000 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS27 (36/30") ETL 5 (36v) 38.90 30.40 23.15	36 V	18-85-25	1020	35.8	38.1	29.1	22.9	2988
N/Cov. SB350Gry Connector 2950 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS27(36/34") 38.90 34.40 23.15	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	3492
N/Cov. SB350Gry Connector 2950 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS27(48/30") 38.90 30.40 23.15	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120
N/Cov. SB350Gry Connector 3000 Min. Weight Term A18 Rider-Sit down Trk dims								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT
	T				(L)	(W)	(H)	(Lbs.)
ECS27(48/34") 38.90 34.40 23.15	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
N/Cov. SB350Gry Connector 3000 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS30 (36/30") 38.90 30.40 23.15	36 V	18-85-25	1020	35.8	38.1	29.1	22.9	2988
N/Cov. SB350Gry Connector 2950 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS30(36/34") 38.90 34.40 23.15	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	3492
N/Cov. SB350Gry Connector 2950 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS30(48/30") 38.90 30.40 23.15	48 V	85-19	Call for more Info(630)851-5800					
N/Cov. SB350Gry Connector 3000 Min. Weight Term A18 Rider-Sit down Trk dims								
ECS30(48/34") 38.90 34.40 23.15	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
N/Cov. SB350Gry Connector 3000 Min. Weight Term A18 Rider-Sit down Trk dims								
ECX20 (36/30") ECX25 (36/30") ECX30 (36/30") 39.25 30.50 23.50	36 V	18-85-25	1020	35.8	38.1	29.1	22.9	2988
N/Cov. SB350Gry Connector 2600 Min. Weight Term A18 Rider-Sit down Trk dims								
ECX20 (36/34") ECX32 (36/34") ECX25 (36/34") ECX30 (36/34") 39.25 34.50 23.50	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	3492
N/Cov. SB350Gry Connector 3000 Min. Weight Term A18 4 wheel - Sit down								
ECX20 (48/34") ECX32(48/34") ECX25(48/34") ECX30(48/34") 39.25 34.50 23.50	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
N/Cov. SB350Gry Connector 3000 Min. Weight Term A18 4 wheel - Sit down								
ECX20(48/30") ECX25(48/30") ECX30(48/30") 39.25 30.50 23.50	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120
N/Cov. SB350Gry Connector 2600 Min. Weight Term A18 Rider-Sit down Trk dims								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR	RATE	X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT
	T				(L)	(W)	(H)	(Lbs.)
ETL 5(48v) 38.90 30.40 23.15	48 V	85-19			Call for more Info(630)851-5800			
N/Cov. SB350Gry Connector 3000 Min. Weight Term A18 Rider-Sit down Trk dims								
ETL15 (36v) ETL17 (36v) ETL20 (36v) 39.50 40.00 23.75	36 V	18-85-33	1360	47.7	38.3	38.2	22.9	4032
N/Cov. SB350Gry Connector 3600 Min. Weight Term A18 Rider-Sit down Trk dims								
ETL15 (48v) ETL17 (48v) ETL20(48v) 39.50 40.00 23.75	48 V	24-85-25	1020	47.7	38.8	38.1	22.9	3984
N/Cov. SB350Gry Connector 3600 Min. Weight Term A18 Rider-Sit down Trk dims								
TM 12(24v) TM 15S(24v) 38.80 13.75 31.00	24 V	12-125-17	1000	23.4	38	13	30.3	1896
N/Cov. SB350Gry Connector 1650 Min. Weight Term A18 3 wheel-Sit down								
TM15 TM17 TM20 38.80 20.50 31.00	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down Trk dims								
TM22 TMG15(36/20") TM25 TMG17(36/20") 38.80 20.50 31.00	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down Trk dims								
TMG 12 (48v) TMG 15S (48v) 38.80 13.75 31.00	48 V	125-7			Call for more Info(630)851-5800			
N/Cov. SB350Gry Connector 1650 Min. Weight Term A18 3 wheel-Sit down								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT
	T				(L)	(W)	(H)	(Lbs.)
TMG 12(36v)	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
TM 15S(36v)								
TMG 15S(36v)								
38.80 13.75 31.00								
N/Cov. SB350Gry Connector 1650 Min. Weight Term A18 3 wheel-Sit down Trk dims								
TMG15(36/25")	36 V	18-125-21	1250	43.9	38.2	24.6	30.3	3618
TMG17(36/25")								
38.80 25.22 31.00								
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down Trk dims								
TMG15(48/20")	48 V	125-11			Call for more Info(630)851-5800			
TMG17(48/20")								
38.80 20.50 31.00								
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down								
TMG15(48/25")	48 V	24-125-15	875	41	38.2	23.6	30.3	3384
TMG17(48/25")								
38.80 25.22 31.00								
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down Trk dims								
TMG20 (36/20")	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
TMG22 (36/20")								
TMG25 (36/20")								
38.80 20.50 31.00								
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down Trk dims								
TMG20 (36/25")	36 V	18-125-21	1250	43.9	38.2	24.6	30.3	3618
TMG22 (36/25")								
TMG25 (36/25")								
38.80 25.22 31.00								
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down Trk dims								
TMG20 (48/20")	48 V	125-11			Call for more Info(630)851-5800			
TMG22 (48/20")								
TMG25 (48/20")								
38.80 20.50 31.00								
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down								
TMG20 (48/25")	48 V	24-125-15	875	41	38.2	23.6	30.3	3384
TMG22(48/25")								
TMG25(48/25")								
38.80 25.22 31.00								
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down Trk dims								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT
	T				(L)	(W)	(H)	(Lbs.)
TMX12 (36v)	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
TMX15S (36v)								
38.80 13.75 31.00								
N/Cov. SB350Gry Connector 1650 Min. Weight Term A18 3 wheel-Sit down Trk dims								
TMX12 (48v)	48 V	125-7			Call for more Info(630)851-5800			
TMX15S (48v)								
38.80 13.75 31.00								
N/Cov. SB350Gry Connector 1650 Min. Weight Term A18 3 wheel-Sit down								
TMX15 (36/25")	36 V	18-125-21	1250	43.9	38.2	24.6	30.3	3618
TMX17 (36/25")								
38.80 25.22 31.00								
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down Trk dims								
TMX15 (48/20")	48 V	125-11			Call for more Info(630)851-5800			
TMX17 (48/20")								
38.80 20.50 31.00								
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down								
TMX15 (48/25")	48 V	24-125-15	875	41	38.2	23.6	30.3	3384
TMX17(48/25")								
38.80 25.22 31.00								
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down Trk dims								
TMX20 (36/20")	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
TMX22(36/20")								
TMX25(36/20")								
38.80 20.50 31.00								
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down Trk dims								
TMX20 (36/25")	36 V	18-125-21	1250	43.9	38.2	24.6	30.3	3618
TMX22(36/25")								
TMX25(36/25")								
38.80 25.22 31.00								
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down Trk dims								
TMX20 (48/20")	48 V	125-11			Call for more Info(630)851-5800			
TMX22(48/20")								
TMX25(48/20")								
38.80 20.50 31.00								
N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY
Compartment Size	L		RA	TE	in.	in.	in.	WEIGHT
	T		Ah	kWh	(L)	(W)	(H)	(Lbs.)

TMX20 (48/25")	48 V	24-125-15	875	41	38.2	23.6	30.3	3384
TMX22(48/25")								
TMX25(48/25")								
38.80 25.22 31.00								

N/Cov. SB350Gry Connector 2590 Min. Weight Term A18 3 wheel-Sit down Trk dims

Class 2 Trucks

ESM-12	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
ESM II 12								
38.80 13.88 31.50								

N/Cov. SB350Gry Connector 1280 Min. Weight Term D12 Rider-Stand up Trk dims

ESM-15	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
ESM II 15								
38.80 16.13 31.50								

N/Cov. SB350Gry Connector 1885 Min. Weight Term D12 Rider-Stand up Trk dims

ESM-15S	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
ESM II 15S								
38.80 13.88 31.50								

N/Cov. SB350Gry Connector 1590 Min. Weight Term D12 Rider-Stand up Trk dims

ESM-17	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
ESM II 17								
38.80 18.38 31.50								

N/Cov. SB350Gry Connector 2175 Min. Weight Term D12 Rider-Stand up Trk dims

ESM-20/25	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
ESM II 20								
ESM II 25								
38.80 20.75 31.50								

N/Cov. SB350Gry Connector 2460 Min. Weight Term D12 Rider-Stand up Trk dims

ESM-22	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
ESM II 22								
38.80 20.75 31.50								

N/Cov. SB350Gry Connector 1845 Min. Weight Term D12 Rider-Stand up Trk dims

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR	RATE	X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT
	T				(L)	(W)	(H)	(Lbs.)
ETA 12	72 V	6-100-11	500	35.1	Call for more Info(630)851-5800			
ETD 10(30")								
ETD 15S(30")								
ETD 15(30")								
41.00 30.00 27.50								
N/Cov. SB350Gry Connector 2700 Min. Weight Term B20 Order Picker								
ETA 15	72 V	6-75S-17			Call for more Info(630)851-5800			
40.00 40.00 24.70								
N/Cov. SB350Gry Connector 4130 Min. Weight Term B20 Order Picker Trk dims								
ETD 10(40")	72 V	6-85-17	680	47.7	Call for more Info(630)851-5800			
ETD 15S(40")								
40.00 40.00 24.70								
N/Cov. SB350Gry Connector 2700 Min. Weight Term B20 Order Picker Trk dims								
ETD 15(40")	72 V	85-17			Call for more Info(630)851-5800			
40.00 40.00 24.70								
N/Cov. SB350Gry Connector 3932 Min. Weight Term B20 Order Picker Trk dims								
ETR 10	24 V	85-23			Call for more Info(630)851-5800			
33.00 25.10 25.40								
W/Cover SB350Gry Connector 1925 Min. Weight Term B20 Order Picker								
ETR 13	72 V	6-85-11	425	29.8	Call for more Info(630)851-5800			
41.00 30.00 27.50								
W/Cover SB350Gry Connector 1936 Min. Weight Term B20 Order Picker Trk dims								
NOS 15	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896
38.75 14.50 31.50								
N/Cov. SB350Gry Connector 1200 Min. Weight Term 00 Order picker Trk dims								
NP 15(14")	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
NP 20(14")								
38.75 14.50 32.00								
W/Cover SB175Red Connector 1600 Min. Weight Term A20 Reach-Narrow aisle								
NP 15(16")	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
NP 20(16")								
38.75 16.50 32.00								
W/Cover SB175Red Connector 1600 Min. Weight Term A20 Reach-Narrow aisle								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR	RATE	X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT
	T				(L)	(W)	(H)	(Lbs.)
NP 15(21") NP 20(21") 38.75 21.50 32.00	36 V	18-125-17	1000	35.1	38.1	20.1	31	2844
W/Cover SB175Red Connector 1600 Min. Weight Term A20 Reach-Narrow aisle								
NP 15D(16") NP 22(16") 38.75 16.50 32.00	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov. SB350Gry Connector 2100 Min. Weight Term B20 Reach-Narrow aisle Trk dims								
NP 15D(21") NP 22(21") 38.75 21.50 32.00	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350Gry Connector 2100 Min. Weight Term B20 Reach-Narrow aisle Trk dims								
NP300-30 (12") NP300-40 (12") NP300-50 (12") 36.75 12.25 31.25	24 V	12-125-13	750	17.6	35.8	11.8	30.3	1500
N/Cov. SB175Red Connector 1150 Min. Weight Term A20 Reach-Narrow aisle Trk dims								
NP300-30 (14") NP300-40 (14") NP300-50 (14") 36.75 14.50 31.25	24 V	12-125-15	875	20.5	36	14	30.3	1692
N/Cov. SB175Red Connector 1400 Min. Weight Term A20 Reach-Narrow aisle Trk dims								
NP300-30(16") NP300-50(16") NP300-40(16") 36.75 16.50 31.25	24 V	12-125-15	875	20.5	36	14	30.3	1692
N/Cov. SB175Red Connector 1400 Min. Weight Term A20 Reach-Narrow aisle Trk dims								
NPR 15D (18") NPR 22 (18") 38.75 18.50 32.00	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov. SB350Gry Connector 2175 Min. Weight Term B14 Reach-Double Trk dims								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT
	T				(L)	(W)	(H)	(Lbs.)
NPR 15D (21")	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
NPR 22 (21")								
38.75 21.00 32.00								
N/Cov. SB350Gry Connector 2460 Min. Weight Term B14 Reach Trk dims								
NPR 15D(16")	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
NPR								
20(36/16")								
NPR 17(36/16")								
38.75 16.13 32.00								
N/Cov. SB350Gry Connector 1900 Min. Weight Term B14 Reach Trk dims								
NPR 17 (24/13")	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896
NPR 20 (24/13")								
38.75 13.88 32.00								
N/Cov. SB350Gry Connector 1600 Min. Weight Term B14 Reach-Narrow aisle								
NPR 17 (24/16")	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136
NPR 20 (24/16")								
38.75 16.13 32.00								
N/Cov. SB350Gry Connector 1900 Min. Weight Term B14 Reach-Narrow aisle Trk dims								
NPR 17 (36/13")	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
NPR 20 (36/13")								
38.75 13.88 32.00								
N/Cov. SB350Gry Connector 1600 Min. Weight Term B14 Reach-Narrow aisle								
NS300-30 (12")	24 V	12-125-13	750	17.6	35.8	11.8	30.3	1500
NS300-40 (12")								
NS300-50 (12")								
36.75 12.25 31.25								
N/Cov. SB175Red Connector 1150 Min. Weight Term A20 Reach-Narrow aisle Trk dims								
NS300-30(16")	24 V	12-125-15	875	20.5	36	14	30.3	1692
NS300-40(16")								
NS300-50(16")								
36.75 16.50 31.50								
N/Cov. SB175Red Connector 1400 Min. Weight Term A20 Turret-Narrow aisle Trk dims								
NSR 22 (24,13")	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896
38.75 13.88 32.00								
N/Cov. SB350Gry Connector 1600 Min. Weight Term B14 Saddle truck								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR	RATE	X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT
	T				(L)	(W)	(H)	(Lbs.)
NSR 22 (24,16") 38.75 16.13 32.00	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136
N/Cov. SB350Gry Connector 1900 Min. Weight Term B14 Saddle truck Trk dims								
NSR 22 (36,13") 38.75 13.88 32.00	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
N/Cov. SB350Gry Connector 1600 Min. Weight Term B14 Saddle truck								
NSR 25 (36,18") 38.75 18.50 32.00	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov. SB350Gry Connector 2175 Min. Weight Term B14 Saddle truck Trk dims								
NSR 25 (36,21") 38.75 21.00 32.00	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350Gry Connector 2460 Min. Weight Term B14 Straddle truck Trk dims								
NSR 25 (36/16") NSR 22 (36/16") 38.75 16.13 32.00	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov. SB350Gry Connector 1900 Min. Weight Term B14 Saddle truck Trk dims								
NST 20(32L"/12") NST 30(32L"/12") NST 25(32L"/12") NST 40(32L"/12") 32.75 12.13 31.50	24 V	12-125-11	625	14.6	31.8	11	30.3	1260
N/Cov. SB175Red Connector 1200 Min. Weight Term A20 Rider-Stand up Trk dims								
NST 20(32L"/16") NST 30(32L"/16") NST 25(32L"/16") NST 40(32L"/16") 32.75 16.63 31.50	24 V	12-125-13	750	17.6	30.6	12.9	30.3	1500
N/Cov. SB175Red Connector 1200 Min. Weight Term A20 Rider-Stand up Trk dims								
NST20(37L"/16") NST30(37L"/16") NST25(37L"/16") NST40(37L"/16") 37.00 16.63 31.50	24 V	12-125-15	875	20.5	36	14	30.3	1692
N/Cov. SB175Red Connector 1200 Min. Weight Term A20 Rider-Stand up Trk dims								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY	DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY	
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT	
	T				(L)	(W)	(H)	(Lbs.)	
NST30(37L"/12") NST20(37L"/12") NST40(37L"/12") NST25(37L"/12") 37.00 12.13 31.50	24 V	12-125-13	750	17.6	35.8	11.8	30.3	1500	
N/Cov. SB175Red Connector 1200 Min. Weight Term A20 Rider-Stand up Trk dims									
OP 15 (24v/36L") 36.25 13.88 31.50	24 V	12-125-15	875	20.5	35.2	12.9	30.3	1692	
N/Cov. SB350Red Connector 1600 Min. Weight Term B24 Order Picker									
OP 15 (36V/39L") 39.50 13.88 31.50	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350Gry Connector 1600 Min. Weight Term B24 Order Picker									
OP 15X 38.25 13.88 31.50	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896	
N/Cov. SB350Red Connector 1500 Min. Weight Term B24 Order Picker									
OP 7 (12/8") 32.00 8.00 24.50	12 V	6-85-13	510	6	30.6	7.8	22.9	564	
W/Cover SB175Ylw Connector 500 Min. Weight Term B15 Order Picker Trk dims									
OP 7 (24/13") 32.00 13.50 25.50	24 V	12-85-13	510	11.9	30.6	12.8	22.9	1128	
W/Cover SB175Ylw Connector 500 Min. Weight Term B15 Order Picker Trk dims									
OP 7(12/13") 32.00 13.50 25.50	12 V	6-85-25	1020	11.9	29.2	12.9	22.9	996	
W/Cover SB175Ylw Connector 500 Min. Weight Term B15 Order Picker									
Class 3 Trucks									
CSM 7 CSM 10 CSM 15 28.60 9.00 24.60	24 V	12-85-7	255	6	25.5	8.7	22.9	708	
N/Cov. SB175Red Connector 0 Min. Weight Term B28 Pallet-Straddle Trk dims									

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY	DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY	
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT	
	T				(L)	(W)	(H)	(Lbs.)	
CSP 15	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
CS 15									
CS 20									
32.00 13.25 40.00									
W/Cover SB175Red Connector 900 Min. Weight Term B28 Walkie-Reach Trk dims									
CST 10	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
CST 15									
CST 20									
32.00 13.25 40.00									
W/Cover SB175Red Connector 900 Min. Weight Term B28 Pallet-Counterbalance Trk dims									
CTR	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
32.00 13.13 40.00									
W/Cover SB175Red Connector 0 Min. Weight Term B28 Tugger Trk dims									
CTT 3	24 V	12-100-13	600	14	Call for more Info(630)851-5800				
34.25 14.00 26.50									
N/Cov. SB175Red Connector 900 Min. Weight Term B28 Tow Tractor Trk dims									
CTT 7 (36v/16")	36 V	85-9	Call for more Info(630)851-5800						
34.25 16.00 23.00									
N/Cov. SB350Gry Connector 900 Min. Weight Term B36 Tugger Trk dims									
CTT 7 (36v/21")	36 V	18-85-13	510	17.9	31.6	20.4	22.9	1692	
34.25 21.50 23.00									
N/Cov. SB350Gry Connector 1375 Min. Weight Term B36 Tugger Trk dims									
CTT 7 (48v/16")	48 V	24-85-7	255	11.9	33.3	14.2	22.9	708	
34.25 16.00 23.00									
N/Cov. SB350Gry Connector 900 Min. Weight Term B36 Tugger Trk dims									
CTT 7 (48v/21")	48 V	24-85-9	340	15.9	32	18.3	22.9	1680	
34.25 21.50 23.00									
N/Cov. SB350Gry Connector 1375 Min. Weight Term B36 Tugger Trk dims									
CTW	12 V	6-85-13	510	6	30.6	7.8	23.3	564	
32.00 8.13 40.00									
W/Cover SB175Gry Connector 0 Min. Weight Term B28 Tugger Trk dims									
HWD25 (7")	24 V	12-85-7	255	6	33.6	6.5	23.3	708	
HWD30 (7")									
HWD36 (7")									
HWD40 (7")									
35.50 7.00 40.00									
W/Cover SB175Gry Connector 456 Min. Weight Term B20 Pallet-Walk									
HWD25(13")	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
HWD30(13")									
HWD36(13")									
HWD40(13")									
31.40 13.60 40.00									
W/Cover SB175Gry Connector 821 Min. Weight Term B20 Pallet-Walk Trk dims									

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY
Compartment Size	L		Rate		in.	in.	in.	WEIGHT
	T		Ah	kWh	(L)	(W)	(H)	(Lbs.)
HWP 40 (8") 31.63 8.13 40.00	12 V	6-85-13	510	6	30.6	7.8	23.3	564
W/Cover SB175Ylw Connector 430 Min. Weight Term B15 Pallet-Walk Trk dims								
HWP 40(13") 31.25 13.38 40.00	12 V	6-85-25	1020	11.9	29.2	12.9	23.3	996
W/Cover SB175Ylw Connector 860 Min. Weight Term B15 Pallet-Walk								
HWP25 (7") HWP30 (7") 35.50 7.00 40.00	24 V	12-85-7	255	6	33.6	6.5	23.3	708
W/Cover SB175Red Connector 456 Min. Weight Term B20 Pallet-Walk								
HWP25(13") HWP30(13") 31.40 13.60 40.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cover SB175Gry Connector 821 Min. Weight Term B20 Pallet-Walk Trk dims								
P25 (13") P30 (13") 31.40 13.60 40.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cover SB175Red Connector 821 Min. Weight Term B15 Pallet-Walk Trk dims								
P25 (7") P30 (7") 35.50 7.00 40.00	24 V	12-85-7	255	6	33.6	6.5	23.3	708
W/Cover SB175Red Connector 456 Min. Weight Term B20 Pallet-Walk								
P40 (13") P60 (13") 31.60 13.40 40.00	12 V	6-85-25	1020	11.9	29.2	12.9	23.3	996
W/Cover SB175Ylw Connector 365 Min. Weight Term B15 Pallet-Walk								
P40 (8") P60 (8") 31.60 8.10 40.00	12 V	6-85-13	510	6	30.6	7.8	23.3	564
W/Cover SB175Ylw Connector 365 Min. Weight Term B15 Pallet-Walk Trk dims								
PWC 30 PWC 40 32.00 13.50 31.00	24 V	12-125-13	750		30.6	12.9	31	1500
W/Cover SB175Gry Connector 800 Min. Weight Term B15 Pallet Trk dims								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT
	T				(L)	(W)	(H)	(Lbs.)
PWD25 (13")	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
PWD30 (13")								
PWD36 (13")								
PWD40 (13")								
31.40 13.60 40.00								
W/Cover SB175Gry Connector 821 Min. Weight Term B15 Pallet-Walk Trk dims								
PWD25 (7")	24 V	12-85-7	255	6	33.6	6.5	23.3	708
PWD30 (7")								
PWD36 (7")								
PWD40 (7")								
35.50 7.00 40.00								
W/Cover SB175Gry Connector 456 Min. Weight Term B20 Pallet-Walk								
PWT	24 V	12-125-13	750	17.6	30.6	12.9	31	1500
32.00 13.50 31.00								
W/Cover SB175Gry Connector 800 Min. Weight Term B15 Tug Trk dims								
S20(13")	12 V	6-85-25	1020	11.9	29.2	12.9	23.3	996
S30(13")								
S40(13")								
31.25 13.40 40.00								
W/Cover SB175Red Connector 570 Min. Weight Term B15 Pallet-High lift								
S20(8")	12 V	6-85-13	510	6	30.6	7.8	23.3	564
S30(8")								
S40(8")								
31.25 8.00 40.00								
W/Cover SB175Red Connector 430 Min. Weight Term B15 Pallet-High lift Trk dims								
SP20 (13")	12 V	6-85-25	1020	11.9	29.2	12.9	23.3	996
SP30(13")								
31.25 13.40 40.00								
W/Cover SB175Red Connector 570 Min. Weight Term B15 Pallet-High lift								
SP20 (8")	12 V	6-85-13	510	6	30.6	7.8	23.3	564
SP30 (8")								
31.25 8.00 40.00								
W/Cover SB175Red Connector 430 Min. Weight Term B15 Pallet-High lift Trk dims								

Clark Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT
	T				(L)	(W)	(H)	(Lbs.)
ST20	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
ST30								
ST40								
31.63 13.88 40.00								
W/Cover SB175Red Connector 810 Min. Weight Term B15 Pallet-High lift Trk dims								
WP 45	24 V	12-85-7	255	6	25.3	8.6	23.3	708
28.50 9.00 24.00								
W/Cover SB175Red Connector 200 Min. Weight Term 00 Pallet-Walk								
WP40 (12v/28"L)	12 V	6-85-11	425	5	26	7.8	23.3	486
28.25 9.00 40.00								
W/Cover SB175Ylw Connector 300 Min. Weight Term B15 Pallet-Walk Trk dims								
WP40 (12v/31"L)	12 V	6-85-13	510	6	30.6	7.8	23.3	564
31.25 9.00 40.00								
W/Cover SB175Ylw Connector 300 Min. Weight Term B15 Pallet-Walk Trk dims								
WP40 (24v/28"L)	24 V	12-85-7	255	6	25.3	8.6	23.3	708
28.25 9.00 40.00								
W/Cover SB175Red Connector 300 Min. Weight Term B15 Pallet-Walk Trk dims								
WP40 (24v/31"L)	24 V	12-85-7	255	6	25.3	8.6	23.3	708
31.25 9.00 40.00								
W/Cover SB175Red Connector 300 Min. Weight Term B15 Pallet-Walk Trk dims								