

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
CLASS 1									
30SC(18") 38.62 18.38 23.12	36 Volt	18-85-15	595	20.9	38.1	17.7	22.9	1926	
N/Cov.-SB350Gry Connector: 1650 Min. Weight: Term: A9 3 Wheel-Sit down									
30SC(20") 38.62 20.62 23.12	36 Volt	18-85-17	680	23.9	38.1	20.1	22.9	2142	
N/Cov.-SB350Gry Connector: 1850 Min. Weight: Term: A9 3 Wheel-Sit down									
35 SC 38.62 22.81 23.12	36 Volt	18-85-19	765	26.9	38.1	22.3	22.9	2340	
N/Cov.-SB350Gry Connector: 2050 Min. Weight: Term: A9 3 Wheel-Sit down									
40FC (36/27") 50FC (36/27") 38.69 27.25 22.75	36 Volt	18-85-23	935	32.8	38.1	26.9	22.9	2736	
N/Cov.-SB350Gry Connector: 2400 Min. Weight: Term: A15 4 Wheel-Sit down									
40FC (48/27") 50FC (48/27") 38.69 27.25 22.75	48 Volt	24-85-17	680	31.8	38.1	26.9	22.9	2856	
N/Cov.-SB350Blu Connector: 2400 Min. Weight: Term: A15 4 Wheel-Sit down									
40FC (48/32") 50FC (48/32") 38.69 32.94 22.75	48 Volt	24-85-21	850	39.8	38.1	32.6	22.9	3408	
N/Cov.-SB350Blu Connector: 2800 Min. Weight: Term: A15 4 Wheel-Sit down									
40FP(36/32") 50FP(36/32") 38.69 32.94 22.75	36 Volt	18-85-27	1105	38.8	38.1	31.4	22.9	3240	
N/Cov.-SB350Gry Connector: 2800 Min. Weight: Term: A15 4 Wheel-Sit down									
40FP(36v) 50FP(36v) 55FP(36v) 60FP(36v) 38.69 36.38 22.75	36 Volt	18-85-31	1275	44.8	38.2	36.2	22.9	3780	
N/Cov.-SB350Gry Connector: 3100 Min. Weight: Term: A15 4 Wheel-Sit down									

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
			Ah	kWh				
50FC (48/36") 38.69 36.38 22.75	48 Volt	24-85-23	935	43.8	38.2	35.6	22.9	3780
N/Cov.-SB350Blu Connector: 2800 Min. Weight: Term: A15 4 Wheel-Sit down								
50FC(36/36") 55FC(36/36") 60FC(36/36") 38.69 36.38 22.75	36 Volt	18-85-31	1275	44.8	38.2	36.2	22.9	3780
N/Cov.-SB350Gry Connector: 3100 Min. Weight: Term: A15 4 Wheel-Sit down								
55 FC(48/36") 60 FC(48/36") 38.69 36.38 22.75	48 Volt	24-85-23	935	43.8	38.2	35.6	22.9	3780
N/Cov.-SB350Blu Connector: 3100 Min. Weight: Term: A15 4 Wheel-Sit down								
55FC(36/32") 50FC(36/32") 40FC(36/32") 60FC(36/32") 38.69 32.94 22.75	36 Volt	18-85-27	1105	38.8	38.1	31.4	22.9	3240
N/Cov.-SB350Gry Connector: 2800 Min. Weight: Term: A15 4 Wheel-Sit down								
55FC(48/32") 40FP(48/32") 60FC(48/32") 50FP(48/32") 38.69 32.94 22.75	48 Volt	24-85-21	850	39.8	38.1	32.6	22.9	3408
N/Cov.-SB350Blu Connector: 2800 Min. Weight: Term: A15 4 Wheel-Sit down								
60FP(48v) 40FP(48/36") 55FP(48v) 50FP(48/36") 38.69 36.38 22.75	48 Volt	24-85-23	935	43.8	38.2	35.6	22.9	3780
N/Cov.-SB350Blu Connector: 3100 Min. Weight: Term: A15 4 Wheel-Sit down								
FC4010-40(36V) FC4010-50(36V) 38.69 27.25 22.75	36 Volt	18-85-23	935	32.8	38.1	26.9	22.9	2736
N/Cov.-SB350Gry Connector: 2630 Min. Weight: Term: A15 4 Wheel-Sit down								

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
FC4010-40(48V) FC4010-50(48V) 38.69 27.25 22.75	48 Volt	24-85-17	680	31.8	38.1	26.9	22.9	2856
N/Cov.-SB350Blu Connector: 2630 Min. Weight: Term: A15 4 Wheel-Sit down								
FC4020-40(36V) FC4020-50(36V) FC4020-55(36V) FC4020-60(36V) 38.69 32.94 22.75	36 Volt	18-85-27	1105	38.8	38.1	31.4	22.9	3240
N/Cov.-SB350Gry Connector: 2800 Min. Weight: Term: A15 4 Wheel-Sit down								
FC4020-40(48V) FC4020-50(48V) FC4020-55(48V) FC4020-60(48V) 38.69 32.94 22.75	48 Volt	24-85-21	850	39.8	38.1	32.6	22.9	3408
N/Cov.-SB350Blu Connector: 2800 Min. Weight: Term: A15 4 Wheel-Sit down								
FC4040-50(36V) FC4040-55(36V) FC4040-60(36V) 38.69 36.38 22.75	36 Volt	18-85-31	1275	44.8	38.2	36.2	22.9	3780
N/Cov.-SB350Gry Connector: 3100 Min. Weight: Term: A15 4 Wheel-Sit down								
FC4040-50(48V) FC4040-55(48V) FC4040-60(48V) 38.69 36.38 22.75	48 Volt	24-85-23	935	43.8	38.2	35.6	22.9	3780
N/Cov.-SB350Blu Connector: 3100 Min. Weight: Term: A15 4 Wheel-Sit down								
SC 4010-30 38.81 16.01 22.80	36 Volt	18-85-13	510	17.9	38.1	15.4	22.9	1692
N/Cov.-SB350Gry Connector: 1475 Min. Weight: Term: A9 3 Wheel-Sit down								
SC 4020-30 SC 4020-35 38.81 20.50 22.80	36 Volt	18-85-17	680	23.9	38.1	20.1	22.9	2142
N/Cov.-SB350Gry Connector: 1850 Min. Weight: Term: A9 3 Wheel-Sit down								
SC 4040-35 SC 4040-40 38.81 24.88 22.80	36 Volt	18-85-21	850	29.8	38.1	24.6	22.9	2556
N/Cov.-SB350Gry Connector: 2250 Min. Weight: Term: A9 3 Wheel-Sit down								

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
CLASS 2									
15SP48 30SP48 30SP42 36.25 14.25 31.00	24 Volt	12-125-15	875	20.5	36	14	30.3	1692	
N/Cov.-SB350Red Connector: 1520 Min. Weight: Term: A20 Order Picker									
30 TSP (48/27") 38.75 27.00 31.00	48 Volt	24-125-17	1000	46.8	38.1	26.6	30.3	3792	
N/Cov.-SB350Blu Connector: 3140 Min. Weight: Term: A9 Turret-Narrow aisle									
30 TSP (48/33") 38.75 33.00 31.00	48 Volt	24-125-21	1250	58.5	38.2	32.6	30.3	4824	
N/Cov.-SB350Blu Connector: 3880 Min. Weight: Term: A9 Turret-Narrow aisle									
30 TSP (72/13") 38.44 13.50 31.00	72 Volt	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov.-SB350Gry Connector: 1610 Min. Weight: Term: A9 Turret-Narrow aisle									
30 TSP (72/15") 38.38 15.88 31.00	72 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov.-SB350Gry Connector: 1770 Min. Weight: Term: A9 Turret-Narrow aisle									
30 TSP (72/18") 38.69 18.00 31.00	72 Volt	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov.-SB350Gry Connector: 2085 Min. Weight: Term: A9 Turret-Narrow aisle									
30RD(36/14) 35RR(36/14) 40RS(36/14) 38.38 14.25 31.00	36 Volt	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov.-SB350Gry Connector: 1595 Min. Weight: Term: A9 Reach-Narrow aisle									
30SP36 31.75 13.12 23.25	24 Volt	12-85-13	510	11.9	30.6	12.8	22.9	1128	
N/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A17 Order Picker									

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
35RR(24/14") RR3010-40(24/14") RR3010-35(14") 38.38 14.25 31.00	24 Volt	12-125-17	1000	23.4	38.1	13.5	30.3	1896	
N/Cov.-SB350Red Connector: 1410 Min. Weight: Term: A9 Reach-Narrow aisle									
35RR(24/16") RR3010-40(16") RR3010-35(16") RR5010-35(16") 38.38 16.25 31.00	24 Volt	12-125-19	1125	26.3	38.2	14.7	30.3	2148	
N/Cov.-SB350Red Connector: 1800 Min. Weight: Term: A9 Reach-Narrow aisle									
35RR(36/12") RR 3520-35(12") 38.38 12.19 31.00	36 Volt	18-125-9	500	17.6	37.8	11.2	30.3	1602	
N/Cov.-SB350Gry Connector: 1305 Min. Weight: Term: A22 Reach-Narrow aisle									
35RR(36/16") 40RS(36/16") 45RR(36/16") 30RD(36/16") 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov.-SB350Red Connector: 1880 Min. Weight: Term: A9 Reach-Narrow aisle									
40 RCTL 38.56 20.75 31.00	36 Volt	18-125-17	1000	35.1	38.1	20.1	30.3	3330	
N/Cov.-SB350Gry Connector: 2400 Min. Weight: Term: A12 Rider-Stand up									
40 TS (15") 38.38 15.88 31.00	72 Volt	*18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov.-SB350Gry Connector: 1770 Min. Weight: Term: A9 Turret-Narrow aisle									
40 TS (18") 38.69 18.00 31.00	72 Volt	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov.-SB350Gry Connector: 2085 Min. Weight: Term: A9 Turret-Narrow aisle									
40RS (24/14") RS 3010-40(24/14") RS 3020-40(24/14") 38.38 14.25 31.00	24 Volt	12-125-17	1000	23.4	38.1	13.5	30.3	1896	
N/Cov.-SB350Red Connector: 1410 Min. Weight: Term: A9 Reach-Narrow aisle									
40RS (24/16") RS 3010-40(16") RS 3020-40(24/16") 38.38 16.25 31.00	24 Volt	12-125-19	1125		38.2	14.8	30.3	2136	
N/Cov.-SB350Red Connector: 1800 Min. Weight: Term: A9 Reach-Narrow aisle									

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
40RS (36/12") RS 3020-40(36/12") RS 3010-40(36/12") 38.38 12.19 31.00	36 Volt	18-125-9	500	17.6	37.8	11.2	30.3	1602
N/Cov.-SB350Gry Connector: 1305 Min. Weight: Term: A22 Reach-Narrow aisle								
PR3020-60 PR3020-80 PR3040-60 PR3040-80 31.12 13.19 31.62	24 Volt	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Pallet-Walkie								
RC 3020-40 38.56 20.75 31.00	36 Volt	18-125-17	1000	35.1	38.1	20.1	30.3	3330
N/Cov.-SB350Gry Connector: 2400 Min. Weight: Term: A12 Rider-Stand up								
RC3020-30 (13") 30RC (13") 38.56 13.68 31.00	36 Volt	18-125-11	625	21.9	38.1	13.1	30.3	1890
N/Cov.-SB350Gry Connector: 1710 Min. Weight: Term: A12 Rider-Stand up								
RC3020-30 (15") 30RC (15") 38.56 15.68 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov.-SB350Gry Connector: 1925 Min. Weight: Term: A12 Rider-Stand up								
RC3020-30(18") 30RC(18") RC3020-35 35RC(18") 38.56 18.38 31.00	36 Volt	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov.-SB350Gry Connector: 2085 Min. Weight: Term: A12 Rider-Stand up								
RD 3020-35(14") 38.38 14.25 31.00	36 Volt	18-125-11	625	21.9	38.1	13.1	30.3	1890
N/Cov.-SB350Gry Connector: 1595 Min. Weight: Term: A9 Reach-Narrow aisle								
RD 5020-30 (14") RD 5220-30(14") 38.38 14.25 31.00	36 Volt	18-125-11	625	21.9	38.1	13.1	30.3	1890
N/Cov.-SB350Gry Connector: 1600 Min. Weight: Term: A9 Reach-Narrow aisle								

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY X in. (L)	DIMENSIONS Y in. (W)    Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
RD 5020-30 (18") 38.38 18.00 31.00	36 Volt	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov.-SB350Gry Connector: 2280 Min. Weight: Term: A9 Reach-Narrow aisle									
RD 5020-30 (20") 38.38 20.75 31.00	36 Volt	18-125-17	1000	35.1	38.1	20.1	30.3	3330	
N/Cov.-SB350Gry Connector: 2600 Min. Weight: Term: A9 Reach-Narrow aisle									
RD 5080S-30 (20") 38.69 20.75 31.00	36 Volt	18-125-17	1000	35.1	38.1	20.1	30.3	3330	
N/Cov.-SB350Gry Connector: 2600 Min. Weight: Term: A9 Reach-Narrow aisle									
RD 5220-30 (18") 38.69 18.00 31.00	36 Volt	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov.-SB350Gry Connector: 2280 Min. Weight: Term: A9 Reach-Narrow aisle									
RD3040-30(16") RD3020(16") RD3540-30(16") RD3520(16") 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov.-SB350Red Connector: 1880 Min. Weight: Term: A9 Reach-Narrow aisle									
RD3040-30(18") RD3540-30(18") 30RD(18") 38.69 18.00 31.00	36 Volt	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov.-SB350Gry Connector: 2120 Min. Weight: Term: A9 Reach-Narrow aisle									
RD3040-30(20") RD3540-30(20") 30RD(20") 38.69 20.75 31.00	36 Volt	18-125-17	1000	35.1	38.1	20.1	30.3	3330	
N/Cov.-SB350Gry Connector: 2400 Min. Weight: Term: A9 Reach-Narrow aisle									
RD-5020-30(16") RD-5020-45(16") 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov.-SB350Gry Connector: 2000 Min. Weight: Term: A9 Reach-Narrow aisle									
RD5060S-30(16") RD5060S-45(16") 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov.-SB350Gry Connector: 2000 Min. Weight: Term: A9 Reach-Narrow aisle									

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
RD5060S-30(20") RD5080S-30(20") 38.69 20.75 31.00	36 Volt	18-125-17	1000	35.1	38.1	20.1	30.3	3330	
N/Cov.-SB350Gry Connector: 2600 Min. Weight: Term: A9 Reach-Narrow aisle									
RD5220-30(16") 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov.-SB350Gry Connector: 2000 Min. Weight: Term: A9 Reach-Narrow aisle									
RD5220-30(21") 38.69 20.75 31.00	36 Volt	18-125-17	1000	35.1	38.1	20.1	30.3	3330	
N/Cov.-SB350Gry Connector: 2600 Min. Weight: Term: A9 Reach-Narrow aisle									
RD5260S-30(16") RD5280S-30(16") 38.69 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov.-SB350Gry Connector: 2000 Min. Weight: Term: A9 Reach-Narrow aisle									
RD5260S-30(20") RD5280S-30(20") 38.69 20.75 31.00	36 Volt	18-125-17	1000	35.1	38.1	20.1	30.3	3330	
N/Cov.-SB350Gry Connector: 2600 Min. Weight: Term: A9 Reach-Narrow aisle									
RD5265S-30(16") RD5285S-30(16") 38.69 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov.-SB350Gry Connector: 2000 Min. Weight: Term: A9 Reach-Narrow aisle									
RD5265S-30(20") RD5285S-30(20") 38.69 20.75 31.00	36 Volt	18-125-17	1000	35.1	38.1	20.1	30.3	3330	
N/Cov.-SB350Gry Connector: 2600 Min. Weight: Term: A9 Reach-Narrow aisle									
RR 3010-35 (12") RR 5010-35 (12") 38.38 12.19 31.00	24 Volt	12-125-15	875	20.5	38	12	30.3	1692	
N/Cov.-SB350Red Connector: 1240 Min. Weight: Term: A9 Reach-Narrow aisle									
RR 3010-40 (14") 38.38 14.25 31.00	24 Volt	12-125-17	1000	23.4	38.1	13.5	30.3	1896	
N/Cov.-SB350Red Connector: 1410 Min. Weight: Term: A9 Reach-Narrow aisle									



CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
RR 3520-35(14") 38.38 14.25 31.00	36 Volt	18-125-11	625	21.9	38.1	13.1	30.3	1890
N/Cov.-SB350Gry Connector: 1595 Min. Weight: Term: A9 Reach-Narrow aisle								
RR 3540-45 (16") 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov.-SB350Gry Connector: 1880 Min. Weight: Term: A9 Reach-Narrow aisle								
RR 5010-35 (14") RR 5010-40(14") RR 5210-35(14") RR 5210-40(14") 38.38 14.25 31.00	24 Volt	12-125-17	1000	23.4	38.1	13.5	30.3	1896
N/Cov.-SB350Red Connector: 1600 Min. Weight: Term: A9 Reach-Narrow aisle								
RR 5010-40 (16") RR 5210-35(16") RR 5210-40(16") 38.38 16.25 31.00	24 Volt	12-125-19	1125	26.3	38.2	14.8	30.3	2136
N/Cov.-SB350Red Connector: 1880 Min. Weight: Term: A9 Reach-Narrow aisle								
RR 5020-35 (12") RR 3020-35(12") RR 5220-35(12") RR5225-35(12") 38.38 12.19 31.00	36 Volt	18-125-9	500	17.6	37.8	11.2	30.3	1602
N/Cov.-SB350Gry Connector: 1300 Min. Weight: Term: A9 Reach-Narrow aisle								
RR 5020-35 (14") RR 5220-35(14") RR 5225-35(14") 38.38 14.25 31.00	36 Volt	18-125-11	625	21.9	38.1	13.1	30.3	1890
N/Cov.-SB350Gry Connector: 1600 Min. Weight: Term: A9 Reach-Narrow aisle								
RR 5020-45 (18") RR 5220-45(18") 38.69 18.00 31.00	36 Volt	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov.-SB350Gry Connector: 2280 Min. Weight: Term: A9 Reach-Narrow aisle								
RR 5020-45 (20") RR5060S-45(20") RR5080S-45(20") 38.69 20.75 31.00	36 Volt	18-125-17	1000	35.1	38.1	20.1	30.3	3330
N/Cov.-SB350Gry Connector: 2600 Min. Weight: Term: A9 Reach-Narrow aisle								

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
RR 5210-35 (12") 38.38 12.19 31.00	24 Volt	12-125-15	875	20.5	38	12	30.3	1692
N/Cov.-SB350Red Connector: 1300 Min. Weight: Term: A9 Reach-Narrow aisle								
RR3040-45(16") RR3020-35(16") RR3540-45(16") RR5020-35(16") RR5220-35(16") 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov.-SB350Gry Connector: 1880 Min. Weight: Term: A9 Reach-Narrow aisle								
RR3040-45(18") RR3540-45(18") 45RR(18") 38.69 18.00 31.00	36 Volt	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov.-SB350Gry Connector: 2120 Min. Weight: Term: A9 Reach-Narrow aisle								
RR3040-45(20") RR3540-45(20") 45RR(20") 38.69 20.75 31.00	36 Volt	18-125-17	1000	35.1	38.1	20.1	30.3	3330
N/Cov.-SB350Gry Connector: 2400 Min. Weight: Term: A9 Reach-Narrow aisle								
RR5020-30(16") RR5020-45(16") 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov.-SB350Gry Connector: 2000 Min. Weight: Term: A9 Reach-Narrow aisle								
RR5060S-30(16") RR5060S-45(16") 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov.-SB350Gry Connector: 2000 Min. Weight: Term: A9 Reach-Narrow aisle								
RR5080S-30(16") RR5080S-45(16") 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov.-SB350Gry Connector: 2000 Min. Weight: Term: A9 Reach-Narrow aisle								
RR5220-45(16") RR5260S-45(16") RR5280S-45(16") 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov.-SB350Gry Connector: 2000 Min. Weight: Term: A9 Reach-Narrow aisle								

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
RR5220-45(21") RR5260S-45(21") RR5280S-45(21") 38.69 20.75 31.00	36 Volt	18-125-17	1000	35.1	38.1	20.1	30.3	3330
N/Cov.-SB350Gry Connector: 2600 Min. Weight: Term: A9 Reach-Narrow aisle								
RR5225-35(16") RR5225-45(16") 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov.-SB350Gry Connector: 1880 Min. Weight: Term: A9 Reach-Narrow aisle								
RR5225-45 (18") 38.69 18.00 31.00	36 Volt	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov.-SB350Gry Connector: 2280 Min. Weight: Term: A9 Reach-Narrow aisle								
RR5225-45(21") 38.69 20.75 31.00	36 Volt	18-125-17	1000	35.1	38.1	20.1	30.3	3330
N/Cov.-SB350Gry Connector: 2600 Min. Weight: Term: A9 Reach-Narrow aisle								
RR5260(16") RR5265S-45(16") RR5280(16") RR5285S-45(16") 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov.-SB350Gry Connector: 2000 Min. Weight: Term: A9 Reach-Narrow aisle								
RR5260(18") RR5265S-45(18") RR5280(18") RR5285S-45(18") 38.69 18.00 31.00	36 Volt	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov.-SB350Gry Connector: 2280 Min. Weight: Term: A9 Reach-Narrow aisle								
RR5260(21") RR5265S-45(21") RR5280(21") RR5285S-45(21") 38.69 20.75 31.00	36 Volt	18-125-17	1000		38.1	20.1	30.3	3330
N/Cov.-SB350Gry Connector: 2600 Min. Weight: Term: A9 Reach-Narrow aisle								
RS3010-40(24/12") RS3020-40(24/12") 35RR(24/12") 40RS(24/12") 38.38 12.19 31.00	24 Volt	12-125-15	875	20.5	38	12	30.3	1692
N/Cov.-SB350Red Connector: 1240 Min. Weight: Term: A22 Reach-Narrow aisle								

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
RS3010-40(36/14") RS3020-40(36/14") 38.38 14.25 31.00	36 Volt	18-125-11	625	21.9	38.1	13.1	30.3	1890
N/Cov.-SB350Gry Connector: 1595 Min. Weight: Term: A9 Reach-Narrow aisle								
RS3010-40(36/16") RR 3020-45 RS3020- 40(36/16") RR3520-45 38.38 16.25 31.00	36 Volt	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov.-SB350Red Connector: 1880 Min. Weight: Term: A9 Reach-Narrow aisle								
SP3010 SP3015 SP3020 SP3040 36.25 14.25 31.00	24 Volt	12-125-15	875	20.5	36	14	30.3	1692
N/Cov.-SB350Red Connector: 1520 Min. Weight: Term: A20 Order Picker								
SP3205-30 31.75 13.12 23.25	24 Volt	12-85-13	510	11.9	30.6	12.8	22.9	1128
N/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Order Picker								
SP3210-30 SP3220-30 SP3250H-30 36.25 14.25 31.00	24 Volt	12-125-15	875	20.5	36	14	30.3	1692
N/Cov.-SB350Red Connector: 1520 Min. Weight: Term: A20 Order Picker								
SP3405-30 31.75 13.12 23.25	24 Volt	12-85-13	510	11.9	30.6	12.8	22.9	1128
N/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Order Picker								
SP3410-30 SP3420-30 SP3450H-30 36.25 14.25 31.00	24 Volt	12-125-15	875	20.5	36	14	30.3	1692
N/Cov.-SB350Red Connector: 1520 Min. Weight: Term: A20 Order Picker								
SR 5285H (46") 46.97 19.64 30.56	48 Volt	24-125-13	750	35.1	Call for more Info:(630-851-5800			
N/Cov.-SB350Blu Connector: 2736 Min. Weight: Term: 00 Reach-Narrow aisle								
SR 5285H (48") 48.15 19.64 30.56	48 Volt	Call for more info...(630) 851-5800						
N/Cov.-SB350Blu Connector: 2736 Min. Weight: Term: 00 Reach-Narrow aisle								

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
SSR30 36.38 11.75 40.00	24 Volt	12-125-13	750	17.6	35.8	11.8	30.3	1500	
W/Cov.-SB350Red Connector: 1300 Min. Weight: Term: A12 Order Picker									
TSP 6000 (48/25") 44.62 24.88 31.25	48 Volt	24-125-15	875	41	38.2	23.6	30.3	1692	
N/Cov.-SB350Blu Connector: 2900 Min. Weight: Term: A15 Turret-Narrow aisle									
TSP 6000 (48/28") 44.62 28.31 31.25	48 Volt	24-125-17	1000	46.8	39.6	25.6	30.3	3792	
N/Cov.-SB350Blu Connector: 3140 Min. Weight: Term: A15 Turret-Narrow aisle									
TSP 6000 (48/34") 44.62 33.94 31.25	48 Volt	24-125-21	1250	58.5	38.2	32.6	30.3	4824	
N/Cov.-SB350Blu Connector: 3880 Min. Weight: Term: A15 Turret-Narrow aisle									
CLASS 3									
20WB 30WB 40WB 31.75 13.12 23.25	24 Volt	12-85-13	510	11.9	30.6	12.8	22.9	1128	
N/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A17 Pallet-High lift									
20WR(13") 30W(13") 30WR(13") 40W(13") 31.75 13.12 23.25	24 Volt	12-85-13	510	11.9	30.6	12.8	22.9	1128	
N/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A17 Pallet-High lift									
20WR(6") 30W(6") 40W(6") 35.06 6.62 23.25	24 Volt	12-85-7	255	6	33.6	6.5	22.9	708	
N/Cov.-SB175Gry Connector: 510 Min. Weight: Term: A17 Pallet-High lift									
60 PW(13") 80 PW(13") 31.75 13.12 23.25	24 Volt	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Pallet-Low lift									

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
60PC 60PR 80PC 80PR 31.75 13.12 23.25	24 Volt	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Walkie-Pallet								
60PE(13") 80PE(13") 31.75 13.12 23.25	24 Volt	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Pallet-Walk								
60PE(6") 60PW(6") 80PE(6") 80PW(6") 35.06 6.62 23.25	24 Volt	12-85-7	255	6	33.6	6.5	23.3	708
W/Cov.-SB175Gry Connector: 510 Min. Weight: Term: A22 Pallet-Walk								
GPW 28.25 8.82 24.00	24 Volt	12-85-7	255	6	33.6	6.5	23.3	708
W/Cov.-SB175Gry Connector: 510 Min. Weight: Term: A22 Pallet-Low lift								
PC3520-60 PC3520-80 PC3540-60 PC3540-80 31.12 13.19 31.62	24 Volt	12-125-13	750	17.6	30.6	12.8	23.3	1500
W/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Pallet-Walkie								
PC3600-60 PC3600-80 31.12 13.19 31.62	24 Volt	12-125-13	750	17.6	30.6	12.8	23.3	1500
W/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Pallet-Walkie								
PE 3520(13") PE 3540(13") 34.44 13.19 31.62	24 Volt	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Pallet-Walk								
PE 3520(6") PE 3540(6") 34.44 6.69 31.62	24 Volt	12-85-7	255	6	33.6	6.5	23.3	708
W/Cov.-SB175Gry Connector: 360 Min. Weight: Term: A22 Pallet-Walk								

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
PE 4000-60(13") PE 4000-80(13") 31.12 13.19 31.62	24 Volt	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Pallet-Walk								
PE 4000-60(6") PE 4000-80(6") 34.44 6.69 31.62	24 Volt	12-85-7	255	6	33.6	6.5	23.3	708
W/Cov.-SB175Gry Connector: 360 Min. Weight: Term: A22 Pallet-Walk								
PE3560-60 31.12 13.19 31.62	24 Volt	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Pallet truck								
PW3510-60 31.12 7.94 23.38	12 Volt	6-85-13	510	6	16.9	6.5	23.3	564
W/Cov.-SB175Gry Connector: 400 Min. Weight: Term: A22 Pallet-Low lift								
PW3520-60 (13") PW3520-80 (13") 31.12 13.19 23.38	24 Volt	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cov.-SB175Gry Connector: 815 Min. Weight: Term: A22 Pallet-Low lift								
PW3520-60 (6") PW3520-80 (6") 34.44 6.69 23.38	24 Volt	12-85-7	255	6	33.6	6.5	23.3	708
W/Cov.-SB175Gry Connector: 360 Min. Weight: Term: A22 Pallet-Low lift								
ST3000-20 ST3000N-20 25.55 7.28 24.13	24 Volt	12-85-5	170	4	24.9	6.5	22.9	576
N/Cov.-SB175Gry Connector: 267 Min. Weight: Term: 00 Pallet-Stacker								
SX3000-30 26.40 9.10 23.62	24 Volt	12-85-7	255	6	25.3	8.6	22.9	708
N/Cov.-SB175Gry Connector: 360 Min. Weight: Term: B18 Pallet-Stacker								
TR3520(23"H) TR3540(23"H) TR3560(23"H) TR3600(23"H) 31.12 13.19 23.38	24 Volt	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Tow Tractor								

CROWN FORKLIFT MODEL# BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
TR3520(31"H) TR3540(31"H) TR3560(31"H) TR3600(31"H) 31.12 13.19 31.62 W/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Tow Tractor	24 Volt	12-125-13	750	17.6	30.6	12.9	31	1500
TWR3520(23"H) TWR3540(23"H) TWR3560(23"H) 31.12 13.19 23.38 W/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Tow Tractor	24 Volt	12-85-13	510	11.9	30.6	12.8	23.3	1128
TWR3520(31"H) TWR3540(31"H) TWR3560(31"H) 31.12 13.19 31.62 W/Cov.-SB175Gry Connector: 975 Min. Weight: Term: A22 Tow Tractor	24 Volt	12-125-13	750	17.6	30.6	12.9	31	1500
WE2000-25 WE2000-30 WE2000-40 32.50 8.63 24.70 N/Cov.-SB175Gry Connector: 644 Min. Weight: Term: B18 Pallet-Walkie	24 Volt	12-85-7	255	6	25.3	8.6	22.9	708
WE2300-25 WE2300-30 32.50 8.63 24.70 N/Cov.-SB175Gry Connector: 644 Min. Weight: Term: B18 Pallet-Walkie	24 Volt	12-85-7	255	6	25.3	8.6	22.9	708
WP2030-45 WP2035-45 WP2330-45 WP2335-45 25.80 7.90 40.00 W/Cov.-SB175Gry Connector: 0 Min. Weight: Term: A20 Pallet-Walkie	24 Volt	12-85-5	170	4	24.9	7.8	23.3	576
WP2040-45 WP2045-45 WP2340-45 WP2345-45 25.80 9.10 40.00 W/Cov.-SB175Gry Connector: 0 Min. Weight: Term: A20 Pallet-Walkie	24 Volt	12-85-7	255	6	25.3	8.6	22.9	708
WS2000-30 WS2300-30 WS2000-40 WS2300-40 32.50 8.63 24.70 N/Cov.-SB175Gry Connector: 644 Min. Weight: Term: B18 Pallet-Walkie	24 Volt	12-85-7	255	6	25.3	8.6	22.9	708