

HYSTER Forklift Model	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY
Compartment Size	L		Ah	kWh	in.	in.	in.	Weight
	T				(L)	(W)	(H)	(Lbs.)
Class 1 Trucks								
A20XL A25XL A30XL 32.85 19.72 26.69	24 V	12-85-21	850	19.9	32.6	19.2	22.9	1704
N/Cov. SB350Red Connector 1370 Min. Weight Pos. A25 Rider-Sit down								
E100 XLS (36v) 44.10 39.20 23.15	36 V	18-85-33	1360	47.7	38.4	38.2	22.9	4032
N/Cov. SB350ry Connector 3600 Min. Weight Pos. B30 4 wheel sit down								
E100 XLS (48v) 44.10 39.20 23.15	48 V	24-85-27	1105	51.7	42	38.5	22.9	4320
N/Cov. SB350Blu Connector 3600 Min. Weight Pos. B30 4 wheel sit down								
E100XL(36v) E120XL(36v) 44.10 45.70 23.15	72 V	36-85-21			Call for more info (630) 851-5800			
N/Cov. SB350ry Connector 3600 Min. Weight Pos. B30 4 wheel sit down								
E100XL(48v) E120XL(48v) 44.10 45.70 23.15	48 V	24-85-31	1275	59.7	Call for more info (630) 851-5800			
N/Cov. SB350Blu Connector 4000 Min. Weight Pos. B30 4 wheel sit down								
E100XL2(36v) E120XL2(36v) E100XL3(36v) E120XL3(36v) 44.10 45.70 23.15	36 V	36-85-21	1700	59.7	Call for more info (630) 851-5800			
N/Cov. SB350ry Connector 4230 Min. Weight Pos. B30 4 wheel sit down								
E100XL2(48v) E120XL2(48v) E100XL3(48v) E120XL3(48v) 44.10 45.70 23.15	48 V	24-85-31	1275	59.7	Call for more info (630) 851-5800			
N/Cov. SB350Blu Connector 4230 Min. Weight Pos. B30 4 wheel sit down								

HYSTER Forklift Model Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY		BATTERY DIMENSIONS			TOTAL BATTERY Weight (Lbs.)
			6 HOUR RATE Ah	kWh	X in. (L)	Y in. (W)	Z in. (H)	
E100Z (36v) 44.10 45.70 23.15	36 V	36-85-21	1700		Call for more info (630) 851-5800			
N/Cov. SB350ry Connector 4000 Min. Weight Pos. B30 4 wheel sit down								
E100Z (48v) 44.10 45.70 23.15	48 V	24-85-31	1275		Call for more info (630) 851-5800			
N/Cov. SB350Blu Connector 4000 Min. Weight Pos. B30 4 wheel sit down								
E100ZS (36v) 44.10 39.20 23.15	36 V	18-85-33	1360	47.7	38.4	38.2	22.9	4032
N/Cov. SB350ry Connector 3600 Min. Weight Pos. B30 4 wheel sit down								
E100ZS (48v) 44.10 39.20 23.15	48 V	24-85-27	1105	51.7	42	38.5	22.9	4320
N/Cov. SB350Blu Connector 3600 Min. Weight Pos. B30 4 wheel sit down								
E120Z (36v) 44.10 45.70 23.15	36 V	36-85-21	1700	59.7	Call for more info (630) 851-5800			
N/Cov. SB350ry Connector 4200 Min. Weight Pos. B30 4 wheel sit down								
E120Z (48v) 44.10 45.70 23.15	48 V	24-85-31	1275	59.7	Call for more info (630) 851-5800			
N/Cov. SB350Blu Connector 4200 Min. Weight Pos. B30 4 wheel sit down								
E20AR E25AR 27.00 19.75 31.25	36 V	18-125-9	500	17.6	25.8	17.8	22.9	1602
N/Cov. 325-SB175ry Connector 1250 Min. Weight Pos. B18 Rider-Sit down								
E25 XL (36v) 35.81 27.36 24.61	36 V	18-85-19	765	26.9	34.9	25.5	22.9	2340
N/Cov. SB350ry Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25 XL (48v) 35.81 27.36 24.61	48 V	24-85-15	595	27.8	35.2	25.8	22.9	2568
N/Cov. SB350ry Connector 1750 Min. Weight Pos. A30 4 wheel sit down								

HYSTER Forklift Model Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY		BATTERY DIMENSIONS			TOTAL BATTERY Weight (Lbs.)
			6 HOUR RATE Ah	kWh	X in. (L)	Y in. (W)	Z in. (H)	
E25 XL2 (36v) 35.16 27.32 23.15	36 V	18-85-17	680	23.9	33.1	25.6	22.9	2142
N/Cov. SB350ry Connector 1750 Min. Weight Pos. A30 Rider-Sit down								
E25 XL2 (48v) 35.16 27.32 23.15	48 V	24-85-13	510	23.9	30.6	25.4	22.9	2256
N/Cov. SB350ry Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25XM (36/34L") E30XM (36/34L") E35XM (36/34L") E40XM2S (36/34L") 34.57 27.36 24.13	36 V	18-85-17	680	23.9	33.1	25.6	22.9	2142
N/Cov. SB350ry Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25XM (36/35L") E30XM (36/35L") E35XM (36/35L") E40XM2S (36/35L") 35.79 27.36 24.13	36 V	18-85-19	765	26.9	34.9	25.5	22.9	2340
N/Cov. SB350ry Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25XM (48/34L") E30XM (48/34L") E35XM (48/34L") E40XM2S (48/34L") 34.57 27.36 24.13	48 V	24-85-13	510	23.9	30.6	25.4	22.9	2256
N/Cov. SB350Blu Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25XM (48/35L") E30XM (48/35L") E35XM (48/35L") E40XM2S (48/35L") 35.79 27.36 24.13	48 V	24-85-15	595	27.8	35.2	25.8	22.9	2568
N/Cov. SB350Blu Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25XM2 (36/34L") E30XM2 (36/34L") E35XM2 (36/34L") 34.57 27.36 24.13	36 V	18-85-17	680		33.1	25.6	22.9	2142
N/Cov. SB350ry Connector 1750 Min. Weight Pos. A30 4 wheel sit down								

HYSTER Forklift Model Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY		BATTERY DIMENSIONS			TOTAL BATTERY Weight (Lbs.)
			6 HOUR RATE Ah	kWh	X in. (L)	Y in. (W)	Z in. (H)	
E25XM2 (36/35L") E30XM2 (36/35L") E35XM2 (36/35L") 35.79 27.36 24.13	36 V	18-85-19	765	26.9	34.9	25.5	22.9	2340
N/Cov. SB350ry Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25XM2 (48/34L") E30XM2 (48/34L") E35XM2 (48/34L") 34.57 27.36 24.13	48 V	24-85-13	510	23.9	30.6	25.4	22.9	2256
N/Cov. SB350Blu Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25XM2 (48/35L") E30XM2 (48/35L") E35XM2 (48/35L") 35.79 27.36 24.13	48 V	24-85-15	595	27.8	35.2	25.8	22.9	2568
N/Cov. SB350Blu Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25XM3 (36/34L") E30XM3 (36/34L") E35XM3 (36/34L") E40XM3S (36/34L") 34.57 27.36 24.13	36 V	18-85-17	680	23.9	33.1	25.6	22.9	2142
N/Cov. SB350ry Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25XM3 (36/35L") E30XM3 (36/35L") E35XM3 (36/35L") E40XM3S(36/35L") 35.79 27.36 24.13	36 V	18-85-19	765	26.9	34.9	25.5	22.9	2340
N/Cov. SB350ry Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25XM3 (48/34L") E30XM3 (48/34L") E35XM3 (48/34L") E40XM3S (48/34L") 34.57 27.36 24.13	48 V	24-85-13	510	23.9	30.6	25.4	22.9	2256
N/Cov. SB350Blu Connector 1750 Min. Weight Pos. A30 4 wheel sit down								

HYSTER Forklift Model Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY		BATTERY DIMENSIONS			TOTAL BATTERY Weight (Lbs.)
			6 HOUR RATE Ah	kWh	X in. (L)	Y in. (W)	Z in. (H)	
E25XM3 (48/35L") E30XM3 (48/35L") E35XM3 (48/35L") E40XM3S (48/35L") 35.79 27.36 24.13	48 V	24-85-15	595	27.8	35.2	25.8	22.9	2568
N/Cov. SB350Blu Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25Z (36/34L") E30Z (36/34L") E35Z (36/34L") E40ZS (36/34L") 34.57 27.36 24.13	36 V	18-85-17	680	23.9	33.1	25.6	22.9	2142
N/Cov. SB350ry Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25Z (36/35L") E30Z (36/35L") E35Z (36/35L") E40ZS(36/35L") 35.79 27.36 24.13	36 V	18-85-19	765	26.9	34.9	25.5	22.9	2340
N/Cov. SB350ry Connector 1750 Min. Weight Pos. A30 4 wheel sit down								
E25Z (48/34L") E30Z (48/34L") E35Z (48/34L") E40ZS (48/34L") 34.57 27.36 24.13	48 V	24-85-13	510	23.9	30.6	25.4	22.9	2256
N/Cov. SB350Blu Connector 1850 Min. Weight Pos. A30 4 wheel sit down								
E25Z (48/35L") E30Z (48/35L") E35Z (48/35L") E40ZS (48/35L") 35.79 27.36 24.13	48 V	24-85-15	595	27.8	35.2	25.8	22.9	2568
N/Cov. SB350Blu Connector 1850 Min. Weight Pos. A30 4 wheel sit down								
E30 AR 38.69 16.00 32.00	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov. SB350ry Connector 1925 Min. Weight Pos. C30 Rider-Sit down								

HYSTER Forklift Model Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY		BATTERY X in. (L)	DIMENSIONS			TOTAL BATTERY Weight (Lbs.)
			6 HOUR RATE Ah	kWh		Y in. (W)	Z in. (H)		
E30 XL (36v) 35.81 27.36 24.61	36 V	18-85-19	765	26.9	34.9	25.5	22.9	2340	
N/Cov. SB350ry Connector 1850 Min. Weight Pos. A30 4 wheel sit down									
E30 XL (48v) 35.81 27.36 24.61	48 V	24-85-15	595	27.8	35.2	25.8	22.9	2568	
N/Cov. SB350ry Connector 1850 Min. Weight Pos. A30 4 wheel sit down									
E30 XL2 (36v) 35.16 27.32 23.15	36 V	18-85-17	680	23.9	33.1	25.6	22.9	2142	
N/Cov. SB350ry Connector 1850 Min. Weight Pos. A30 Rider-Sit down									
E30 XL2 (48v) 35.16 27.32 23.15	48 V	24-85-15	595	27.8	35.2	25.8	22.9	2568	
N/Cov. SB350ry Connector 1850 Min. Weight Pos. A30 4 wheel sit down									
E30BC(36v) E40BC(36v) 39.00 28.38 25.75	36 V	18-85-23	935	32.8	38.1	26.9	22.9	2736	
N/Cov. SB350ry Connector 2500 Min. Weight Pos. B30 Rider-Sit down									
E30BC(48v) E40BC(48v) 39.00 28.38 25.75	48 V	*24-85-17	680	31.8	38.1	26.9	22.9	2856	
N/Cov. SB350Blu Connector 2500 Min. Weight Pos. B30 Rider-Sit down									
E35 XL (36v) 35.81 27.36 24.61	36 V	18-85-19	765	26.9	34.9	25.5	22.9	2340	
N/Cov. SB350ry Connector 2020 Min. Weight Pos. A30 4 wheel sit down									
E35 XL (48v) 35.81 27.36 24.61	48 V	24-85-15	595	27.8	35.2	25.8	22.9	2568	
N/Cov. SB350ry Connector 2020 Min. Weight Pos. A30 4 wheel sit down									
E35 XL2 (36v) 35.16 27.32 23.15	36 V	18-85-17	680	23.9	33.1	25.6	22.9	2142	
N/Cov. SB350ry Connector 2020 Min. Weight Pos. A30 4 wheel sit down									

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			TOTAL BATTERY Weight (Lbs.)
Battery Compartment Size			Ah	kWh	X in. (L)	Y in. (W)	Z in. (H)	
E35 XL2 (48v) 35.16 27.32 23.15	48 V	24-85-13	510	23.9	30.6	25.4	22.9	2256
N/Cov. SB350ry Connector 2020 Min. Weight Pos. A30 4 wheel sit down								
E40 AR 38.69 20.75 32.00	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350ry Connector 2700 Min. Weight Pos. C36 Rider-Sit down								
E40XL(36v/27") E40XL2(36v/27") E50XL(36v/27") E50XL2(36v/27") 38.86 27.32 24.57	36 V	18-85-23	935	32.8	38.1	26.9	22.9	2736
N/Cov. SB350ry Connector 2300 Min. Weight Pos. B30 4 wheel sit down								
E40XL(36v/33") E40XL2(36v/33") 38.86 33.11 24.57	36 V	18-85-27	1105	38.8	38.2	31.4	22.9	3492
N/Cov. SB350ry Connector 2300 Min. Weight Pos. B30 4 wheel sit down								
E40XL(48v/27") E40XL2(48v/27") E50XL(48v/27") E50XL2(48v/27") 38.86 27.32 24.57	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
N/Cov. SB350ry Connector 2300 Min. Weight Pos. B30 4 wheel sit down								
E40XL(48v/33") E40XL2(48v/33") 38.86 33.11 24.57	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
N/Cov. SB350ry Connector 2300 Min. Weight Pos. B30 4 wheel sit down								
E45XM (36/27") E50XM (36/27") E50XM2 (36/27") E45XM2 (36/27") 38.86 27.36 24.41	36 V	18-85-23	935	32.8	38.1	26.9	22.9	2736
N/Cov. SB350ry Connector 2300 Min. Weight Pos. B30 4 wheel sit down								

HYSTER Forklift Model Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY		BATTERY DIMENSIONS			TOTAL BATTERY Weight (Lbs.)
			6 HOUR RATE Ah	kWh	X in. (L)	Y in. (W)	Z in. (H)	
E45XM (36/33") E50XM (36/33") E45XM2 (36/33") E50XM2 (36/33") 38.86 33.15 24.41	36 V	18-85-27	1105	975	38.2	31.4	22.9	3492
N/Cov. SB350ry Connector 2900 Min. Weight Pos. B30 4 wheel sit down								
E45XM (48/27") E50XM (48/27") E50XM2 (48/27") E45XM2 (48/27") 38.86 27.36 24.41	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
N/Cov. SB350Blu Connector 2300 Min. Weight Pos. B30 4 wheel sit down								
E45XM (48/33") E50XM (48/33") E45XM2 (48/33") E50XM2 (48/33") 38.86 33.15 24.41	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
N/Cov. SB350Blu Connector 2900 Min. Weight Pos. B30 4 wheel sit down								
E45Z(36v/27") E50Z(36v/27") E55Z(36v/27") 38.90 27.40 24.40	36 V	18-85-23	935	32.8	38.1	26.9	22.9	2736
N/Cov. SB350ry Connector 2300 Min. Weight Pos. B30 4 wheel sit down								
E45Z(36v/33") E50Z(36v/33") E55Z(36v/33") E60Z(36v/33") 38.90 33.20 24.40	36 V	18-85-27	1105	975	38.2	31.4	22.9	3492
N/Cov. SB350ry Connector 2900 Min. Weight Pos. B30 4 wheel sit down								
E45Z(48v/27") E50Z(48v/27") E55Z(48v/27") 38.90 27.40 24.40	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
N/Cov. SB350Blu Connector 2300 Min. Weight Pos. B30 4 wheel sit down								

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
E45Z(48v/33") E50Z(48v/33") E55Z(48v/33") E60Z(48v/33") 38.90 33.20 24.40	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408	
N/Cov. SB350Blu Connector 2900 Min. Weight Pos. B30 4 wheel sit down									
E50BC(36v) E60BC(36v) 39.00 31.25 25.75	36 V	18-85-25	1020	35.8	38.1	29.9	22.9	2988	
N/Cov. SB350ry Connector 2700 Min. Weight Pos. B30 Rider-Sit down Trk dims									
E50BC(48v) E60BC(48v) 39.00 31.25 25.75	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120	
N/Cov. SB350Blu Connector 2700 Min. Weight Pos. B30 Rider-Sit down Trk dims									
E55XL(36v) E55XL2(36v) E60XL(36v) E60XL2(36v) 38.86 33.11 23.15	36 V	18-85-27	1105	38.8	38.2	31.4	22.9	3492	
N/Cov. SB350ry Connector 2900 Min. Weight Pos. B30 4 wheel sit down									
E55XL(48v) E55XL2(48v) E60XL(48v) E60XL2(48v) 38.86 33.11 23.15	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408	
N/Cov. SB350ry Connector 2900 Min. Weight Pos. B30 4 wheel sit down									
E55XM (36v) E60XM (36v) E55XM2 (36v) E60XM2 (36v) 38.86 33.15 24.41	36 V	18-85-27	1105	38.8	38.2	31.4	22.9	3492	
N/Cov. SB350ry Connector 2900 Min. Weight Pos. B30 4 wheel sit down									
E55XM (48v) E60XM (48v) E55XM2 (48v) E60XM2 (48v) 38.86 33.15 24.41	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408	
N/Cov. SB350Blu Connector 2900 Min. Weight Pos. B30 4 wheel sit down									

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
E65XM (36v) E65XM2 (36v) 38.86 39.76 24.41	36 V	18-85-33	1360	47.7	38.4	38.2	22.9	4032	
N/Cov. SB350ry Connector 3420 Min. Weight Pos. B30 4 wheel sit down									
E65XM (48v) E65XM2 (48v) 38.86 39.76 24.41	48 V	24-85-25	1020	47.7	38.8	38.1	22.9	3984	
N/Cov. SB350Blu Connector 3420 Min. Weight Pos. B30 4 wheel sit down									
E65Z(36v/39") 38.90 39.80 24.40	36 V	18-85-33	1360	47.7	38.4	38.2	22.9	4032	
N/Cov. SB350ry Connector 3420 Min. Weight Pos. B30 4 wheel sit down									
E65Z(48v/39") 38.90 39.80 24.40	48 V	24-85-25	1020	47.7	38.8	38.1	22.9	3984	
N/Cov. SB350Blu Connector 3420 Min. Weight Pos. B30 4 wheel sit down									
E70XL(36v) E70XL2(36v) E80XL(36v) E80XL2(36v) 44.10 39.20 23.15	36 V	18-85-33	1360	47.7	38.4	38.2	22.9	4032	
N/Cov. SB350ry Connector 3400 Min. Weight Pos. B30 4 wheel sit down									
E70XL(48v) E70XL2(48v) E80XL(48v) E80XL2(48v) 44.10 39.20 23.15	48 V	24-85-27	1105	51.7	42	38.5	22.9	4320	
N/Cov. SB350Blu Connector 3400 Min. Weight Pos. B30 4 wheel sit down									
E70XL3(36v) E80XL3(36v) E100XL3S(36V) 44.10 39.20 23.15	36 V	18-85-33	1360	47.7	38.4	38.2	22.9	4032	
N/Cov. SB350ry Connector 3600 Min. Weight Pos. B30 4 wheel sit down									

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
E70XL3(48v) E80XL3(48v) E100XL3S(48v) 44.10 39.20 23.15	48 V	24-85-27	1105	51.7	42	38.5	22.9	4320	
N/Cov. SB350Blu Connector 3600 Min. Weight Pos. B30 4 wheel sit down									
E70Z(36v) E80Z(36v) 44.10 39.20 23.15	36 V	18-85-33	1360	47.7	38.4	38.2	22.9	4032	
N/Cov. SB350ry Connector 3400 Min. Weight Pos. B30 4 wheel sit down									
E70Z(48v) E80Z(48v) 44.10 39.20 23.15	48 V	24-85-27	1105	51.7	42	38.5	22.9	4320	
N/Cov. SB350Blu Connector 3400 Min. Weight Pos. B30 4 wheel sit down									
J25B(24v) J30BS(24v) 39.38 16.75 26.00	24 V	12-100-21	1000	23.4	Call for more info (630) 851-5800				
N/Cov. SB350Red Connector 1720 Min. Weight Pos. B30 3 wheel sit down Trk dims									
J25B(36v) J30BS(36v) 39.38 16.75 26.00	36 V	18-100-13	600	15.8	Call for more info (630) 851-5800				
N/Cov. SB350Red Connector 1720 Min. Weight Pos. B30 3 wheel sit down Trk dims									
J30 XM 39.00 16.70 26.10	36 V	18-85-13	510	17.9	38.1	15.4	22.9	1692	
N/Cov. SB350ry Connector 1300 Min. Weight Pos. B30 Rider-Sit down									
J30B (24v) 39.38 23.50 26.00	24 V	12-85-29	1190	27.8	Call for more info (630) 851-5800				
N/Cov. SB350Red Connector 1820 Min. Weight Pos. B30 3 wheel sit down Trk dims									
J30B (36v) 39.38 23.50 26.00	36 V	18-85-19	765	26.9	38.1	22.3	22.9	2340	
N/Cov. SB350ry Connector 1820 Min. Weight Pos. B30 3 wheel sit down Trk dims									

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
J30XMT (36/16") 39.00 16.70 23.10	36 V	18-85-13	510	17.9	38.1	15.4	22.9	1692	
N/Cov. SB350ry Connector 1300 Min. Weight Pos. B30 3 wheel sit down									
J30XMT (48/16") 39.00 16.70 23.10	48 V	24-85-9	340	15.9	38.1	14.5	22.9	1680	
N/Cov. SB350Blu Connector 1300 Min. Weight Pos. B30 3 wheel sit down									
J30XMT2 (36/21") J30XMT (36/21") 39.00 21.50 23.10	36 V	18-85-17	680	23.9	38.1	20.1	22.9	2142	
N/Cov. SB350ry Connector 2000 Min. Weight Pos. B30 3 wheel sit down									
J30XMT2 (48/21") J30XMT (48/21") 39.00 21.50 23.10	48 V	24-85-13	510	23.9	38.1	20.6	22.9	2256	
N/Cov. SB350Blu Connector 2000 Min. Weight Pos. B30 3 wheel sit down									
J30ZT(36v) 39.00 21.50 23.10	36 V	18-85-17	680	23.9	38.1	20.1	22.9	2142	
N/Cov. SB350ry Connector 1900 Min. Weight Pos. A20 3 wheel sit down									
J30ZT(48v) 39.00 21.50 23.10	48 V	24-85-13	510	23.9	38.1	20.6	22.9	2256	
N/Cov. SB350Blu Connector 1900 Min. Weight Pos. A20 3 wheel sit down									
J35B (24v) 39.38 26.50 26.00	24 V	12-85-33	1360	31.8	Call for more info (630) 851-5800				
N/Cov. SB350Red Connector 2200 Min. Weight Pos. B30 3 wheel sit down Trk dims									
J35B (36v) 39.38 26.50 26.00	36 V	18-85-21	850	29.8	38.1	24.6	22.9	2556	
N/Cov. SB350ry Connector 2200 Min. Weight Pos. B30 3 wheel sit down Trk dims									
J35XM (old) J40XM (old) 39.00 25.20 26.10	36 V	18-85-21	850	29.8	38.1	24.6	22.9	2556	
N/Cov. SB350ry Connector 2100 Min. Weight Pos. B30 Rider-Sit down									

HYSTER Forklift Model Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY		BATTERY DIMENSIONS			TOTAL BATTERY Weight (Lbs.)
			6 HOUR RATE Ah	kWh	X in. (L)	Y in. (W)	Z in. (H)	
J35XMT2 (36v) J40XMT2 (36v) J35XMT (36v) J40XMT (36v) 39.00 25.20 23.10	36 V	18-85-21	850	29.8	38.1	24.6	22.9	2556
N/Cov. SB350ry Connector 2100 Min. Weight Pos. B30 3 wheel sit down								
J35XMT2 (48v) J40XMT2 (48v) J35XMT (48v) J40XMT (48v) 39.00 25.20 23.10	48 V	24-85-15	595	27.8	38.1	23.6	22.9	1926
N/Cov. SB350Blu Connector 2100 Min. Weight Pos. B30 3 wheel sit down								
J35ZT(36v) J40ZT(36v) 39.00 25.20 23.10	36 V	18-85-21	850	29.8	38.1	24.6	22.9	2556
N/Cov. SB350ry Connector 2100 Min. Weight Pos. A20 3 wheel sit down								
J35ZT(48v) J40ZT(48v) 39.00 25.20 23.10	48 V	24-85-15	595	27.8	38.1	23.6	22.9	1926
N/Cov. SB350Blu Connector 2100 Min. Weight Pos. A20 3 wheel sit down								
J40XL(36/33") J40XL2 (36v) J50XL(36/33") J50XL2(36v) 38.86 33.11 23.15	36 V	18-85-27	1105	38.8	38.2	31.4	22.9	3240
N/Cov. SB350ry Connector 2900 Min. Weight Pos. B30 4 wheel sit down								
J40XL(36/39") J50XL(36/39") 38.86 39.72 23.15	36 V	18-85-33	1360	47.7	38.4	38.4	22.9	4032
N/Cov. SB350ry Connector 2900 Min. Weight Pos. B30 4 wheel sit down								
J40XL(48/33") J40XL2 (48v) J50XL(48/33") J50XL2(48v) 38.86 33.11 23.15	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
N/Cov. SB350ry Connector 2900 Min. Weight Pos. B30 4 wheel sit down								

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	Y in. (W)	Z in. (H)	TOTAL BATTERY Weight (Lbs.)
J40XL(48/39") J50XL(48/39") 38.86 39.72 23.15	48 V	24-85-25	47.7	38.8	38.1	22.9	3984	3984
N/Cov. SB350Blu Connector 2900 Min. Weight Pos. B30 4 wheel sit down								
J40XM(36v) J40XM2(36v) J50XM(36v) J50XM2(36v/28") 38.80 28.30 30.80	36 V	18-125-23	1375	48.3	38.2	26.9	30.3	4032
N/Cov. SB350ry Connector 3720 Min. Weight Pos. B30 3 wheel sit down								
J40XM(48v) J40XM2(48v) J50XM(48v) J50XM2(48v/28") 38.80 28.30 30.80	48 V	24-125-17	1000	46.8	38.1	26.6	30.3	3792
N/Cov. SB350Blu Connector 3720 Min. Weight Pos. B30 3 wheel sit down								
J40Z(80v) J50Z(80v/28") 40.60 28.30 30.90	80 V	40-125-9	500	39	Call for more info (630) 851-5800			
N/Cov. SBE320Bk Connector 3720 Min. Weight Pos. A12 4 wheel sit down Trk dims								
J50XM2(36v/33") J60XM (36v) J60XM2(36v) 38.80 33.90 30.80	36 V	18-125-29	1750	61.4	38.1	33.6	30.3	
N/Cov. SB350ry Connector 4456 Min. Weight Pos. B30 3 wheel sit down								
J50XM2(48v/33") J60XM (48v) J60XM2(48v) 38.80 33.90 30.80	48 V	24-125-21	1250	58.5	38.2	32.6	30.3	4824
N/Cov. SB350ry Connector 4456 Min. Weight Pos. B30 3 wheel sit down								
J50Z(80v/34") J60Z(80v) J65Z(80v) 40.60 33.90 30.90	80 V	40-125-11	625	48.8	Call for more info (630) 851-5800			
N/Cov. SBE320Bk Connector 4456 Min. Weight Pos. A12 4 wheel sit down								

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
J60XL(36v) J60XL2(36v) 38.86 39.72 23.15	36 V	18-85-33	1360	47.7	38.4	38.2	22.9	4032	
N/Cov. SB350ry Connector 3420 Min. Weight Pos. B30 4 wheel sit down									
J60XL(48v) J60XL2(48v) 38.86 39.72 23.15	48 V	24-85-25	1020	47.7	38.8	38.1	22.9	3984	
N/Cov. SB350Blu Connector 3420 Min. Weight Pos. B30 4 wheel sit down									
R30CH 39.00 22.75 31.50	36 V	18-125-17	1000	35.1	38.1	20.1	31	2844	
Optional battery cover 320-SB350ry Connector 2500 Min. Weight Pos. B16 Turret									
V30ZMD(36v) 38.90 39.80 24.40	36 V	18-85-33	1360	47.7	38.4	38.2	22.9	4032	
N/Cov. SB350ry Connector 3420 Min. Weight Pos. B30 Turret									
V30ZMD(48v) 38.90 39.80 24.40	48 V	24-85-25	1020	47.7	38.8	38.1	22.9	3984	
N/Cov. SB350Blu Connector 3420 Min. Weight Pos. B30 Turret									
Class 2 Trucks									
E30 FR (24v) 38.75 15.50 31.62	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136	
N/Cov. SB350Red Connector 1925 Min. Weight Pos. D9 Rider-Stand up									
E30HSD 38.60 18.30 31.10	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov. SB350ry Connector 1885 Min. Weight Pos. B25 Rider-Stand up Trk dims									
E35FR E30FR (36v) 38.75 16.12 31.62	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov. SB350ry Connector 1925 Min. Weight Pos. D9 Rider-Stand up									

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
E35HSD (18") 38.60 18.30 31.10	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov. SB350ry Connector 2315 Min. Weight Pos. B25 Rider-Stand up Trk dims									
E35HSD (21") E40HSD 38.60 20.80 31.10	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844	
N/Cov. SB350ry Connector 2540 Min. Weight Pos. B25 Rider-Stand up Trk dims									
E50FR E40FR E55FR E45FR 38.88 20.60 31.62	36 V	18-125-17	1000		38.1	20.1	30.3	2844	
N/Cov. SB350ry Connector 2700 Min. Weight Pos. 00 Rider-Stand up									
N25XMDR2 (24/14") N25XMDR3(24/14") 38.88 14.62 31.18	24 V	12-125-17	1000	23.4	38.2	13.5	30.3	1896	
N/Cov. SB350Red Connector 1550 Min. Weight Pos. B16 Reach Trk dims									
N25XMDR2 (24/16") N25XMDR3 (24/16") 38.88 16.62 31.18	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136	
N/Cov. SB350Red Connector 1600 Min. Weight Pos. B16 Reach									
N25XMDR2 (36/14") N25XMDR3 (36/14") 38.88 14.62 31.18	36 V	18-125-11	625	21.9	38.2	13.2	30.3	1890	
N/Cov. SB350ry Connector 1550 Min. Weight Pos. B16 Reach Trk dims									
N25XMDR2 (36/16") N30XMDR2 (36/16") N25XMDR3 (36/16") N30XMDR3 (36/16") 38.88 16.62 31.18	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov. SB350ry Connector 1850 Min. Weight Pos. B16 Reach									

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
N30FR (24/12") 39.00 12.50 31.50	24 V	12-125-15	875	20.5	38.2	12	30.3	1692	
N/Cov. SB350Red Connector 1300 Min. Weight Pos. B16 Reach Trk dims									
N30FR (24/14") N40FR (24v) 38.38 14.50 31.62	24 V	12-125-17	1000	23.4	38.2	13.5	30.3	1896	
N/Cov. SB350Red Connector 1500 Min. Weight Pos. B16 Reach Trk dims									
N30FR (36/14") N40FR (36v) 38.38 14.50 31.62	36 V	18-125-11	625	21.9	38.2	13.2	30.3	1890	
N/Cov. SB350ry Connector 0 Min. Weight Pos. B16 Reach Trk dims									
N30XMDR2 (36/18") N30XMDR3 (36/18") 38.88 18.75 31.18	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov. SB350ry Connector 2200 Min. Weight Pos. B16 Reach Trk dims									
N30XMDR2 (36/21") N30XMDR3 (36/21") 38.88 21.12 31.18	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844	
N/Cov. SB350ry Connector 2500 Min. Weight Pos. B16 Reach Trk dims									
N30XMH (36v) N30XMH2 (36v) 38.86 39.76 24.41	36 V	18-85-33	1360	47.7	38.4	38.2	22.9	4032	
N/Cov. SB350ry Connector 3420 Min. Weight Pos. B30 Turret truck									
N30XMH (48v) N30XMH2 (48v) 38.86 39.76 24.41	48 V	24-85-25	1020	47.7	38.8	38.2	22.9	3984	
N/Cov. SB350Blu Connector 3420 Min. Weight Pos. B30 Turret truck									
N30XMR2 (12") 38.90 12.50 31.20	24 V	12-125-15	875	20.5	38.2	12	30.3	1692	
N/Cov. SB350Red Connector 1250 Min. Weight Pos. B16 Reach Trk dims									

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
N30XMR2(24/14") N40XMR2(24/14") 38.90 14.60 31.20	24 V	12-125-17	1000	23.4	38.2	13.5	30.3	1896	
N/Cov. SB350Red Connector 1500 Min. Weight Pos. B16 Reach Trk dims									
N30XMR3 (12") 38.88 12.50 31.20	24 V	12-125-15	875	20.5	38	12	30.3	1692	
N/Cov. SB350Red Connector 1400 Min. Weight Pos. B16 Reach Trk dims									
N30XMR3(24/14") N40XMR3(24/14") 38.88 14.60 31.20	24 V	12-125-17	1000	23.4	38.2	13.5	30.3	1896	
N/Cov. SB350Red Connector 1550 Min. Weight Pos. B16 Reach Trk dims									
N30MXDR (18") N30MXDR3 (18") 38.88 18.80 31.50	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov. SB350ry Connector 2200 Min. Weight Pos. B16 Reach Trk dims									
N30MXDR (21") N30MXDR3 (21") 38.88 21.10 31.50	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844	
N/Cov. SB350ry Connector 2600 Min. Weight Pos. B16 Reach Trk dims									
N30ZDR(36v/16") N35ZRS(36v/16") N40ZRS(36v/16") N30ZDRS(36v/16") 39.00 16.50 31.50	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov. SB350ry Connector 1700 Min. Weight Pos. B16 Reach Trk dims									
N35ZDR(36v/16") N35ZR(36v/16") N40ZR(36v/16") N45ZR(36v/16") 39.00 16.50 31.50	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov. SB350ry Connector 1700 Min. Weight Pos. B16 Reach Trk dims									

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
N35ZR(36v/14") N40ZR(36v/14") N30ZDR(36v/14") 39.00 14.50 31.50	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350ry Connector 1500 Min. Weight Pos. B16 Reach Trk dims									
N35ZRS(24v/12") N40ZRS(24v/12") 39.00 12.50 31.50	24 V	12-125-15	875	20.5	38	12	30.3	1692	
N/Cov. SB350Red Connector 1400 Min. Weight Pos. B16 Reach Trk dims									
N35ZRS(24v/14") N40ZRS(24v/14") N30ZDRS(24v/14") 39.00 14.50 31.50	24 V	12-125-17	1000	23.4	38.2	13.5	30.3	1896	
N/Cov. SB350Red Connector 1500 Min. Weight Pos. B16 Reach Trk dims									
N35ZRS(24v/16") N40ZRS(24v/16") N30ZDRS(24v/16") 39.00 16.50 31.50	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136	
N/Cov. SB350Red Connector 1700 Min. Weight Pos. B16 Reach Trk dims									
N35ZRS(36v/12") N40ZRS(36v/12") 39.00 12.50 31.50	36 V	125-9	Call for more info (630) 851-5800						
N/Cov. SB350ry Connector 1400 Min. Weight Pos. B16 Reach Trk dims									
N35ZRS(36v/14") N40ZRS(36v/14") N30ZDRS(36v/14") 39.00 14.50 31.50	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350ry Connector 1500 Min. Weight Pos. B16 Reach Trk dims									
N40EA (24/12") 38.38 12.12 31.62	24 V	12-125-15	875	20.5	38	12	30.3	1692	
N/Cov. SB350Red Connector 0 Min. Weight Pos. B30 Reach Trk dims									

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
N40EA (36/14") N50EA (36/14") 38.38 14.50 31.62	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350Red Connector 0 Min. Weight Pos. B30 Reach Trk dims									
N40ER (24/12") 38.38 12.12 31.62	24 V	12-125-15	875	20.5	38	12	30.3	1692	
N/Cov. SB350Red Connector 0 Min. Weight Pos. B16 Reach Trk dims									
N40ER (24/14") N50ER (24v) 38.38 14.50 31.62	24 V	12-125-17	1000	23.4	38.2	13.5	30.3	1896	
N/Cov. SB350Red Connector 1500 Min. Weight Pos. B16 Reach Trk dims									
N40ER (36/14") N50ER (36v) 38.38 14.50 31.62	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350ry Connector 0 Min. Weight Pos. B16 Reach Trk dims									
N40FR(24/16") N45FR(24/16") 39.00 16.60 31.62	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136	
N/Cov. SB350Red Connector 1800 Min. Weight Pos. B16 Reach Trk dims									
N40FR(36/16") N45FR(36/16") 39.00 16.60 31.62	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov. SB350ry Connector 1800 Min. Weight Pos. B16 Reach Trk dims									
N40XMR2 (24/16") 38.90 16.60 31.20	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136	
N/Cov. SB350Red Connector 1600 Min. Weight Pos. B16 Reach									
N40XMR2 (36/14") 38.90 14.60 31.20	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350ry Connector 1550 Min. Weight Pos. B16 Reach Trk dims									

HYSTER Forklift Model Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY		BATTERY DIMENSIONS			TOTAL BATTERY Weight (Lbs.)
			6 HOUR RATE Ah	kWh	X in. (L)	Y in. (W)	Z in. (H)	
N40XMR2 (36/16") N45XMR2 (16") 38.90 16.60 31.20	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov. SB350ry Connector 1550 Min. Weight Pos. B16 Reach Trk dims								
N40XMR3 (24/16") 38.88 16.60 31.20	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136
N/Cov. SB350Red Connector 1700 Min. Weight Pos. B16 Reach Trk dims								
N40XMR3 (36/14") 38.88 14.60 31.20	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
N/Cov. SB350ry Connector 1550 Min. Weight Pos. B16 Reach Trk dims								
N40XMR3 (36/16") N45XMR3 (16") 38.88 16.60 31.20	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov. SB350ry Connector 1700 Min. Weight Pos. B16 Reach Trk dims								
N45ER 38.38 16.50 31.62	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov. SB350ry Connector 0 Min. Weight Pos. B16 Reach Trk dims								
N45FR (36/18") 39.00 18.75 31.50	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov. SB350ry Connector 2200 Min. Weight Pos. B16 Reach Trk dims								
N45FR (36/21") 39.00 21.12 31.50	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350ry Connector 2500 Min. Weight Pos. B16 Reach Trk dims								
N45XMR2 (18") 38.90 18.80 31.20	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov. SB350ry Connector 2200 Min. Weight Pos. B16 Reach Trk dims								
N45XMR2 (21") 38.90 21.10 31.20	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350ry Connector 2500 Min. Weight Pos. B16 Reach Trk dims								

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
N45XMR3 (18") N45XMR (18") 38.88 18.80 31.20	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov. SB350ry Connector 2200 Min. Weight Pos. B16 Reach Trk dims									
N45XMR3 (21") N45XMR (21") 38.88 21.10 31.20	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844	
N/Cov. SB350ry Connector 2500 Min. Weight Pos. B16 Reach Trk dims									
N45XMR3 (18") 38.88 18.80 31.50	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov. SB350ry Connector 2200 Min. Weight Pos. B16 Reach Trk dims									
N45XMR3 (21") 38.88 21.10 31.50	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844	
N/Cov. SB350ry Connector 2600 Min. Weight Pos. B16 Reach Trk dims									
N45ZR(36v/18") N35ZDR(36v/18") 39.00 18.50 31.50	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov. SB350ry Connector 2200 Min. Weight Pos. B16 Reach Trk dims									
N45ZR(36v/21") N35ZDR(36v/21") 39.00 21.50 31.50	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844	
N/Cov. SB350ry Connector 2500 Min. Weight Pos. B16 Reach Trk dims									
N50EA (24/14") N40EA (24/14") 38.38 14.50 31.62	24 V	12-125-17	1000	23.4	38.2	13.5	30.3	1896	
N/Cov. SB350Red Connector 0 Min. Weight Pos. B30 Reach Trk dims									
N50EA (36/16") 38.38 16.50 31.62	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov. SB350Red Connector 0 Min. Weight Pos. B30 Reach Trk dims									

HYSTER Forklift Model Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY		BATTERY X in. (L)	DIMENSIONS			TOTAL BATTERY Weight (Lbs.)
			6 HOUR RATE Ah kWh	Y in. (W)		Z in. (H)			
N50FA (24/14") 39.00 14.60 31.62	24 V	12-125-17	1000	23.4	38.2	13.5	30.3	1896	
N/Cov. SB350Red Connector 1650 Min. Weight Pos. B16 Reach Trk dims									
N50FA (24/16") 39.00 16.60 31.62	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136	
N/Cov. SB350Red Connector 1650 Min. Weight Pos. B16 Reach Trk dims									
N50FA (36/14") 39.00 14.60 31.62	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350ry Connector 1650 Min. Weight Pos. B16 Reach Trk dims									
N50FA (36/16") 39.00 16.60 31.62	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov. SB350ry Connector 1650 Min. Weight Pos. B16 Reach Trk dims									
N50XMA2 (24/12") N50XMA3 (24/12") 38.88 12.50 31.18	24 V	12-125-15	875	20.5	38	12	30.3	1692	
N/Cov. SB350Red Connector 1250 Min. Weight Pos. B16 Straddle Trk dims									
N50XMA2 (24/14") N50XMA3 (24/14") 38.88 14.62 31.18	24 V	12-125-17	1000	23.4	38.2	13.5	30.3	1896	
N/Cov. SB350Red Connector 1500 Min. Weight Pos. B16 Straddle Trk dims									
N50XMA2 (24/16") N50XMA3 (24/16") 38.88 16.62 31.18	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136	
N/Cov. SB350Red Connector 1600 Min. Weight Pos. B16 Straddle									
N50XMA2 (36/14") N50XMA3 (36/14") 38.88 14.62 31.18	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350ry Connector 1500 Min. Weight Pos. B16 Straddle Trk dims									

HYSTER Forklift Model Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY		BATTERY DIMENSIONS			TOTAL BATTERY Weight (Lbs.)
			6 HOUR RATE Ah kWh	X in. (L)	Y in. (W)	Z in. (H)		
N50XMA2 (36/16") N50XMA3 (36/16") 38.88 16.62 31.18	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov. SB350ry Connector 1850 Min. Weight Pos. B16 Straddle Trk dims								
R25A 36.70 13.50 31.00	24 V	12-125-15	875	20.5	35.1	12.9	31	1692
W/Cover SB175ry Connector 1200 Min. Weight Pos. B20 Order Picker Trk dims								
R30E (24v) R30EA (24v) R30EF(24v) 38.90 14.60 31.20	24 V	12-125-17	1000	23.4	38.2	13.5	30.3	1896
N/Cov. SB350Red Connector 1500 Min. Weight Pos. B16 Order picker Trk dims								
R30E (36v) R30EA (36v) R30EF(36v) 38.90 14.60 31.20	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
N/Cov. SB350Red Connector 1500 Min. Weight Pos. B16 Order picker Trk dims								
R30ES 36.00 13.50 24.71	24 V	12-85-15	595	13.9	35.1	12.9	23.3	1284
W/Cover SB175Red Connector 1025 Min. Weight Pos. B16 Order picker Trk dims								
R30F(24v) R30FA(24v) R30FF(24v) 38.90 14.60 31.20	24 V	12-125-17	1000	23.4	38.2	13.5	30.3	1896
N/Cov. SB350Red Connector 1500 Min. Weight Pos. B16 Order picker Trk dims								
R30FA(36v) R30FF(36v) 39.00 14.60 31.50	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
N/Cov. SB350ry Connector 1800 Min. Weight Pos. B16 Order picker Trk dims								
R30XM (24v) R30XMA (24v) R30XMF (24v) R30XMA2 (24v) R30XMF2 (24v) 38.90 14.60 30.80	24 V	12-125-17	1000	23.4	38.2	13.5	30.3	1896
N/Cov. SB350Red Connector 1500 Min. Weight Pos. B16 Order picker Trk dims								

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
R30XM (36v) R30XMA (36v) R30XMF (36v) R30XMF2 (36v) 38.90 14.60 30.80	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350ry Connector 1800 Min. Weight Pos. B16 Order picker Trk dims									
R30XM2 (24v) 38.90 14.60 30.80	24 V	12-125-17	1000	23.4	38.2	13.5	30.3	1896	
N/Cov. SB350Red Connector 1600 Min. Weight Pos. B16 Order picker									
R30XM2 (36v) 38.90 14.60 30.80	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350ry Connector 1600 Min. Weight Pos. B16 Order picker									
R30XMA2 (36v) 38.90 14.60 30.80	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350ry Connector 1500 Min. Weight Pos. B16 Order picker Trk dims									
R30XMS 36.00 13.50 24.71	24 V	12-85-15	595	13.9	35.1	12.9	23.3	1284	
N/Cov. SB175Red Connector 1025 Min. Weight Pos. B16 Order picker Trk dims									
R30XMS2 36.00 13.50 24.70	24 V	12-85-15	595	13.9	35.1	12.9	23.3	1284	
N/Cov. SB175Red Connector 1025 Min. Weight Pos. B16 Order picker Trk dims									
R40EH 42.40 17.40 31.50	72 V				Call for more info (630) 851-5800				
N/Cov. 0 Connector 4000 Min. Weight Pos. D30 Order Picker Trk dims									
V30XMU 44.76 21.65 33.46	48 V	24-125-13	750	35.1	44	20.6	30.3	3000	
N/Cov. SB350Blu Connector 2640 Min. Weight Pos. B30 Turret truck Trk dims									

HYSTER Forklift Model Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY		BATTERY DIMENSIONS			TOTAL BATTERY Weight (Lbs.)
			6 HOUR RATE Ah	kWh	X in. (L)	Y in. (W)	Z in. (H)	
V30ZMU(LWB,23.6") 38.70 23.60 31.00	48 V	24-125-15	875	41	38.1	23.6	30.3	3384
N/Cov. SB350Blu Connector 3087 Min. Weight Pos. B30 Turret truck								
V30ZMU(LWB,26.8") 38.40 26.80 31.00	48 V	24-125-17	1000	46.8	38.1	26.6	30.3	3792
N/Cov. SB350Blu Connector 3087 Min. Weight Pos. B30 Turret truck								
V30ZMU(LWB,27") 38.70 27.00 31.00	48 V	24-125-17	1000	46.8	38.1	26.6	30.3	3792
N/Cov. SB350Blu Connector 3087 Min. Weight Pos. B30 Turret truck								
V30ZMU(MWB,20.8") 44.20 20.80 31.00	48 V	24-125-13	750	35.1	44	20.6	30.3	3000
N/Cov. SB350Blu Connector 2976 Min. Weight Pos. B30 Turret truck								
V30ZMU(MWB,23.8") 38.70 23.80 31.00	48 V	24-125-15	875	41	38.1	23.6	30.3	3384
N/Cov. SB350Blu Connector 2976 Min. Weight Pos. B30 Turret truck								
V35XMU 40.75 28.74 37.40	72 V	36-125-11	625		Call for more info (630) 851-5800			
N/Cov. SB350rn Connector 3520 Min. Weight Pos. B30 Turret truck								
V35ZMU(LWB,17.9") 38.30 17.90 31.00	72 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov. SB350rn Connector 4189 Min. Weight Pos. B30 Turret truck								
V35ZMU(LWB,20.1") 38.30 20.10 31.00	72 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350rn Connector 4189 Min. Weight Pos. B30 Turret truck								
V35ZMU(LWB,20.4") 38.70 20.40 31.00	72 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350rn Connector 4189 Min. Weight Pos. B30 Turret truck								

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
V35ZMU(MWB,15.5") 37.90 15.50 31.00	72 V	18-125-13	750	26.3	37.8	15.4	30.3	2250	
N/Cov. SB350rn Connector 4079 Min. Weight Pos. B30 Turret truck									
V35ZMU(MWB,15.8") 38.10 15.80 31.00	72 V	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov. SB350rn Connector 4079 Min. Weight Pos. B30 Turret truck									
V35ZMU(SWB,13.5") 38.30 13.50 31.00	72 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350rn Connector 3307 Min. Weight Pos. B30 Turret truck									
V35ZMU(SWB,14") 37.90 14.00 31.00	72 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350rn Connector 3307 Min. Weight Pos. B30 Turret truck									
V35ZMU(SWB,26.7") 38.30 26.70 31.00	72 V				Call for more info (630) 851-5800				
N/Cov. SB350rn Connector 3307 Min. Weight Pos. B30 Turret truck									
V40XMU 46.14 34.17 33.28	72 V	36-125-13	750		Call for more info (630) 851-5800				
N/Cov. SB350rn Connector 4180 Min. Weight Pos. B30 Turret truck									
Class 3 Trucks									
B40XL B60XL 31.90 13.60 40.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175Red Connector 0 Min. Weight Pos. B15 Pallet-Walk/ride									
B60XT (13") B80XT(13") 32.00 13.40 31.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175Red Connector 1450 Min. Weight Pos. B20 Pallet-Walk/ride									

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
B60XT (9") B80XT (9") 32.00 9.00 31.00	24 V	12-85-7	255	6	25.4	8.7	23.3	708	
W/Cover SB175Red Connector 0 Min. Weight Pos. B20 Pallet-Walk/ride									
B60Z B80Z 32.00 13.40 40.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175Red Connector 536 Min. Weight Pos. B20 Pallet-Walkie Trk dims									
C60XT C80XT 32.00 13.40 31.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175Red Connector 1450 Min. Weight Pos. B20 Pallet-Walk/ride									
C60XT2 C80XT2 31.60 13.40 31.00	24 V	12-125-13	750	17.6	30.6	12.9	31	1500	
W/Cover SB175Red Connector 1450 Min. Weight Pos. B20 Pallet-rider									
C60Z C80Z 31.20 13.40 40.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175Red Connector 1450 Min. Weight Pos. B20 Pallet-Walk/ride									
B60Z 31.60 13.40 31.00	24 V	12-125-13	750	17.6	30.6	12.9	31	1500	
W/Cover SB175Red Connector 1035 Min. Weight Pos. B20 Hybot-Auto Walkie Trk dims									
TP 40 D 19.75 11.95 40.00	24 V	12-85-5	170	4	Call for more info (630) 851-5800				
W/Cover SB175Red Connector 0 Min. Weight Pos. 00 Trk dims									
W40DL(13") W60DL(13") 32.00 13.38 40.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175Red Connector 0 Min. Weight Pos. B15 Trk dims									

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
W40DL(8") W60DL(8") 32.00 8.27 40.00	24 V	12-85-5	170	4	24.9	7.8	23.3	576	
W/Cover SB175Red Connector 0 Min. Weight Pos. B15 Trk dims									
T5XT 32.00 13.50 31.00	24 V	12-125-13	750	17.6	30.6	12.9	31	1500	
W/Cover SB175Red Connector 1450 Min. Weight Pos. B20 Tow tractor									
T5Z T7Z 31.30 13.40 40.00	24 V	12-125-13	750	17.6	30.6	12.9	31	1500	
W/Cover SB175Red Connector 1450 Min. Weight Pos. B16 Tow tractor									
W20XTA (12/13") W30XTA (12/13") W40XTA (12v) 35.40 13.50 40.00	12 V	6-85-21	850	9.9	24.6	12.9	23.3	852	
W/Cover SB175Red Connector 400 Min. Weight Pos. B20 Pallet-Stacker/Straddle									
W20XTA (12/8") W30XTA (12/8") 35.40 8.12 40.00	12 V	6-85-13	510	6	30.6	7.8	23.3	564	
W/Cover SB175Red Connector 400 Min. Weight Pos. B20 Pallet-Stacker/Straddle Trk dims									
W20XTA (24/13") W30XTA (24/13") W40XTA (24v) 35.40 13.50 40.00	24 V	12-85-15	595	13.9	35.1	12.9	23.3	1284	
W/Cover SB175Red Connector 400 Min. Weight Pos. B20 Pallet-Stacker/Straddle									
W20XTA (24/8") W30XTA (24/8") 35.40 8.12 40.00	24 V	12-85-7	255	6	33.6	6.5	23.3	708	
W/Cover SB175Red Connector 400 Min. Weight Pos. B20 Pallet-Stacker/Straddle Trk dims									
W20XTC (12v) W25XTC (12v) W30XTC (12v) 31.87 13.38 40.00	12 V	6-85-21	850	9.9	24.6	12.9	23.3	852	
W/Cover SB175ry Connector 400 Min. Weight Pos. 00 Pallet-Stacker-Counter									

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
W20XTC (24v) W25XTC (24v) W30XTC (24v) W40XTC (24v) 31.87 13.38 40.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175ry Connector 400 Min. Weight Pos. 00 Pallet-Stacker-Counter									
W20XTR (24v) W30XTR (24v) 35.40 13.50 40.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175Red Connector 400 Min. Weight Pos. B20 Walkie-Reach/Stacker									
W20XTR (12v) W30XTR (12v) 35.40 13.50 40.00	12 V	6-85-21	850	9.9	24.6	12.9	23.3	852	
W/Cover SB175Red Connector 400 Min. Weight Pos. B20 Walkie-Reach/Stacker									
W20ZA 27.80 8.10 40.00	24 V	12-85-5	170	4	24.9	7.8	23.3	576	
W/Cover SBX175Red Connector 310 Min. Weight Pos. B20 Pallet-Hand trucks									
W20ZR W30ZR 33.00 13.50 40.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175Red Connector 800 Min. Weight Pos. B20 Pallet-Stacker-Counter Trk dims									
W25ZA 27.80 9.10 40.00	24 V	12-85-7	255	6	25.4	8.7	23.3	708	
W/Cover SB175Red Connector 350 Min. Weight Pos. B20 Pallet-Hand trucks Trk dims									
W25ZC W30ZC W40ZC 33.00 13.50 40.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175Red Connector 800 Min. Weight Pos. B20 Pallet-Stacker-Counter Trk dims									
W30ZA(13") W40ZA(13") 33.00 13.50 40.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175Red Connector 800 Min. Weight Pos. B20 Pallet-Stacker-Counter P Trk dims									

HYSTER Forklift Model	V	BATTERY	CAPACITY		BATTERY	DIMENSIONS			TOTAL
Battery	O	TYPE	6 HOUR		X	Y	Z	BATTERY	
Compartment Size	L		Ah	kWh	in.	in.	in.	Weight	
	T				(L)	(W)	(H)	(Lbs.)	
W30ZA(9") W40ZA(9") 33.00 9.00 40.00	24 V	12-85-7	255	6	25.4	8.7	23.3	708	
W/Cover SB175Red Connector 525 Min. Weight Pos. B20 Pallet truck Trk dims									
W40 XT (28L"/8") 28.75 7.80 24.30	24 V	12-85-5	170	4	24.9	7.8	23.3	576	
W/Cover SB175Red Connector 200 Min. Weight Pos. B20 Pallet truck Trk dims									
W40XL(12v) W60XL(12v) W45XT 31.90 8.30 23.30	12 V	6-100-13	600	7	Call for more info (630) 851-5800				
W/Cover SB175Ylw Connector 500 Min. Weight Pos. B15 Pallet-Walkie Trk dims									
W40XL(24v) W60XL(24v) 31.90 13.60 23.30	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175Ylw Connector 900 Min. Weight Pos. B15 Pallet-Walkie Trk dims									
W40XT (25L"/6") 25.75 6.88 40.00	24 V	12-85-5	170	4	24.8	6.5	23.3	576	
W/Cover SB175Red Connector 200 Min. Weight Pos. B20 Pallet truck Trk dims									
W40XT (29L"/7") 29.50 7.80 25.40	24 V	12-85-5	170	4	24.9	7.8	23.3	576	
W/Cover SB175Red Connector 200 Min. Weight Pos. B20 Pallet truck Trk dims									
W40Z 28.50 8.10 31.00	24 V	12-85-5	170	4	24.9	7.8	23.3	576	
W/Cover SB175Red Connector 310 Min. Weight Pos. B20 Pallet-Walkie truck Trk dims									
W45Z(12v) 31.60 8.10 31.00	12 V	6-85-13	510	6	30.6	7.8	23.3	564	
W/Cover SB175Ylw Connector 436 Min. Weight Pos. B20 Pallet-Walkie truck									

HYSTER Forklift Model	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY Weight (Lbs.)
W45Z(24v) 28.50 9.10 31.00	24 V	12-85-7	255	6	25.4	8.7	23.3	708	
W/Cover SB175Red Connector 410 Min. Weight Pos. B20 Pallet-Walkie truck									
W50Z (24v) 28.00 9.10 40.00	24 V	12-85-7	255	6	25.4	8.7	23.3	708	
W/Cover SB175Red Connector 410 Min. Weight Pos. B20 Pallet-Hand trucks Trk dims									
W60XT (12/9") 32.00 9.00 31.00	12 V	6-125-13	750	8.8	30.6	7.8	31	750	
W/Cover SB175Ylw Connector 1120 Min. Weight Pos. B20 Pallet truck									
W60XT (24/13") W80XT (13") 32.00 13.40 31.00	24 V	12-125-13	750	17.6	30.6	12.9	31	1500	
W/Cover SB175Ylw Connector 1450 Min. Weight Pos. B20 Pallet truck									
W60XT (24/9") W80XT (9") 32.00 9.00 31.00	24 V	12-125-7	375	8.8	25.4	8.6	31	876	
W/Cover SB175Ylw Connector 1120 Min. Weight Pos. B20 Pallet truck									
W60Z W80Z 32.00 13.40 31.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175Red Connector 536 Min. Weight Pos. B16 Pallet truck-Walkie									
W60Z (24/9") 32.00 9.00 31.00	24 V	12-125-7	375	8.8	25.4	8.6	31	876	
W/Cover SB175Ylw Connector 1120 Min. Weight Pos. B20 Pallet truck									
W65Z 32.00 9.00 31.00	12 V	6-85-13	510	6	30.6	7.8	23.3	564	
W/Cover SB175Ylw Connector 305 Min. Weight Pos. B20 Pallet-Walk/ride									