

LINDE FORKLIFT MODEL#	V		CAPACITY	BATTERY	DIMENSIONS	TOTAL		
BATTERY	O	BATTERY	6 HOUR	X	Y	Z	BATTERY	
COMPARTMENT	L	TYPE	RATE	in.	in.	in.	WEIGHT	
SIZE (Inches)	T		Ah kWh	(Length)	(Width)	(Height)	(Lbs.)	
BFE 80(36v) 39.10 35.20 31.20	36 Volt:	18-125-27	1625 57	38.2	31.3	30.3	4860	
N/Cov. SB350Gry Connector: 3770 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
BFE 80(48v) 39.10 35.20 31.20	48 Volt:	24-125-21	1100 58.5	38.2	32.6	30.3	4824	
N/Cov. SB350Blu Connector: 3770 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
BTE/S 30 (48v) 32.67 29.29 25.82	48 Volt:	24-85-13	510	30.6	25.4	22.9	2256	
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 4 Wheel Sit down								
BTE/S 30(36v) 32.67 29.29 25.82	36 Volt:	18-100-19	900 31.6	Call For more details.. (630) 851-5800				
N/Cov. SB350Gry Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:								
BTE/S 35 (36v) 32.67 28.30 25.82	36 Volt:	18-85-17	680 23.9	31.8	26.5	22.9	2142	
N/Cov. SB350Gry Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:								
BTE/S 35 (48v) 32.67 28.30 25.82	48 Volt:	24-85-13	510	30.6	25.4	22.9	2256	
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
BTE 30 32.67 20.10 26.80	24 Volt:	24-85-19	765	Call For more details.. (630) 851-5800				
N/Cov. SB350Gry Connector: 1525 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:								
E15 33.00 20.25 26.00	24 Volt:	12-85-21	850 19.9	32.6	19.3	22.9	1704	
N/Cov. SB350Red Connector: 1525 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:								
E15C 33.00 21.00 31.00	48 Volt:	24-125-9	500 23.4	32	18.4	30.3	2136	
N/Cov. SB350Blu Connector: 2075 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:								
E15S (36v/1) 33.00 29.50 25.00	36 Volt:	18-85-19	765 26.9	31.9	29.5	23.26	2340	
N/Cov. SB350Gry Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down								
E15S (36v/2) 33.00 29.50 26.00	36 Volt:	18-100-19	900 31.6	Call For more details.. (630) 851-5800				
N/Cov. SB350Gry Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down								

LINDE FORKLIFT MODEL#	V	BATTERY	CAPACITY	BATTERY	DIMENSIONS	TOTAL	
BATTERY	O	BATTERY	6 HOUR	X	Y	Z	
COMPARTMENT	L	TYPE	RATE	in.	in.	in.	
SIZE (Inches)	T		Ah kWh	(Length)	(Width)	(Height)	
						BATTERY	
						WEIGHT	
						(Lbs.)	
E15S (36v/3) 33.00 28.00 25.00	36 Volt:	18-85-17	680 23.9	31.8	26.5	22.9	2142
N/Cov. SB350Gry Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down							
E15S (36v/4) 33.00 28.00 26.00	36 Volt:	18-85-17	680 23.9	31.8	26.5	22.9	2142
N/Cov. SB350Gry Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down							
E15S (36v/5) 31.25 26.00 25.00	36 Volt:	18-85-15	595 20.9	29.3	25.6	22.99	1926
N/Cov. SB350Gry Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E15S (36v/6) E 16 (36v/4) 31.25 26.00 26.00	36 Volt:	18-85-15	595 20.9	29.3	25.6	22.99	1926
N/Cov. SB350Gry Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E15S (48v/1) 33.00 29.50 25.00	48 Volt:	24-85-15	595 27.8	32	29.25	22.9	2568
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E15S (48v/2) 33.00 29.50 26.00	48 Volt:	24-100-13	600 28.1	Call For more details.. (630) 851-5800			
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E15S (48v/3) 33.00 28.00 25.00	48 Volt:	24-85-13	510 23.9	30.6	25.4	22.9	2256
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E15S (48v/4) 33.00 28.00 26.00	48 Volt:	24-100-13	600 28.1	Call For more details.. (630) 851-5800			
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E15S (48v/5) 31.25 26.00 25.00	48 Volt:	24-85-13	510 23.9	30.6	25.4	22.9	2256
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E15S (48v/6) 31.25 26.00 26.00	48 Volt:	24-100-13	600 28.1	Call For more details.. (630) 851-5800			
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							

LINDE FORKLIFT MODEL#	V	BATTERY	CAPACITY	BATTERY	DIMENSIONS	TOTAL	
BATTERY	O	BATTERY	6 HOUR	X	Y	Z	
COMPARTMENT	L	TYPE	RATE	in.	in.	in.	
SIZE (Inches)	T		Ah kWh	(Length)	(Width)	(Height)	BATTERY WEIGHT (Lbs.)
E 16 (36v/1) 33.00 28.50 25.00	36 Volt:	18-85-17	680 23.9	31.8	26.5	22.9	2142
N/Cov. SB350Gry Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down							
E 16 (36v/2) 33.00 28.50 26.00	36 Volt:	18-85-17	680 23.9	31.8	26.5	22.9	2142
N/Cov. SB350Gry Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down							
E 16 (36v/3) 31.25 26.00 25.00	36 Volt:	18-85-15	595 20.9	29.4	25.6	22.99	1926
N/Cov. SB350Gry Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E 16 (48v/1) 33.00 28.50 25.00	48 Volt:	24-85-13	510 23.9	30.6	25.4	22.9	2256
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E 16 (48v/2) 33.00 28.50 26.00	48 Volt:	24-100-13	600 28.1	Call For more details.. (630) 851-5800			
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E 16 (48v/3) 31.25 26.00 25.00	48 Volt:	24-85-13	510 23.9	30.6	25.4	22.9	2256
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E18C(48v/26W) E 16 (48v/4) 31.25 26.00 26.00	48 Volt:	24-100-13	600 28.1	Call For more details.. (630) 851-5800			
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E18C(48v/28W) 33.00 28.00 25.00	48 Volt:	24-85-13	510 23.9	30.6	25.4	22.9	2256
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E18C(48v/29W) 33.00 29.50 24.50	48 Volt:	24-85-15	595 27.8	32	29.5	22.9	2568
N/Cov. SB350Blu Connector: 2215 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:							
E20B (36v) 39.10 21.50 31.20	36 Volt:	18-125-17	1000 35.1	38.1	20.1	30.3	2142
N/Cov. SB350Gry Connector: 2439 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:							
E20B (48v) 39.10 21.50 31.20	48 Volt:	24-125-13	750 35.1	37.97	20.72	30.3	3000
N/Cov. SB350Blu Connector: 2439 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:							

LINDE FORKLIFT MODEL#	V	BATTERY TYPE	CAPACITY		BATTERY DIMENSIONS			TOTAL
	O		6 HOUR RATE	X	Y	Z	BATTERY WEIGHT	
	L			in.	in.	in.		(Lbs.)
BATTERY COMPARTMENT SIZE (Inches)	T	Ah	kWh	(Length)	(Width)	(Height)		
E20C/600(36v/28") E25C/600(36v/28") 38.70 27.80 23.40	36 Volt:	18-85-23	935	32.8	38.1	26.9	22.9	2736
N/Cov. SB350Gry Connector: 1942 Min. Weight: Term: A30 4 Wheel Sit down								
E20C/600(36v/30") E25C/600(36v/30") 38.70 30.30 23.40	36 Volt:	18-85-25	1020	35.8	38.1	29.1	22.9	2988
N/Cov. SB350Gry Connector: 2740 Min. Weight: Term: A30 4 Wheel Sit down								
E20C/600(48v/28") E25C/600(48v/28") 38.70 27.80 23.40	48 Volt:	24-85-17	680	31.8	38.1	26.9	22.9	2856
N/Cov. SB350Blu Connector: 1942 Min. Weight: Term: A30 4 Wheel Sit down								
E20C/600(48v/30") E25C/600(48v/30") 38.70 30.30 23.40	48 Volt:	24-85-19	765	35.8	38.1	29.5	22.9	3120
N/Cov. SB350Blu Connector: 2740 Min. Weight: Term: A30 4 Wheel Sit down								
E20P (31") 31.25 25.90 31.25	48 Volt:	24-125-13	750	35.1	30.6	25.3	30.3	3000
N/Cov. SB350Blu Connector: 2465 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E20P (33") 33.00 25.90 31.25	48 Volt:	24-125-13	750	35.1	30.6	25.3	30.3	3000
N/Cov. SB350Blu Connector: 2465 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E25B (36v) 39.10 24.80 31.20	36 Volt:	18-125-21	1250	43.9	38.2	24.6	30.3	3618
N/Cov. SB350Gry Connector: 2683 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E25B (48v) 39.10 24.80 31.20	48 Volt:	24-125-15	875	41	38.1	23.6	30.3	3384
N/Cov. SB350Blu Connector: 2683 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E25C/600(36v/34") 38.70 34.30 23.40	36 Volt:	18-85-29	1190	41.8	38.2	33.6	22.9	3492
N/Cov. SB350Gry Connector: 1942 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E25C/600(48v/34") 38.70 34.30 23.40	48 Volt:	24-85-21	850	39.8	38.1	32.6	22.9	3408
N/Cov. SB350Blu Connector: 3060 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								

LINDE FORKLIFT MODEL#	V	BATTERY	CAPACITY	BATTERY	DIMENSIONS			TOTAL
BATTERY	O	BATTERY	6 HOUR	X	Y	Z	BATTERY	
COMPARTMENT	L	TYPE	RATE	in.	in.	in.	WEIGHT	
SIZE (Inches)	T		Ah kWh	(Length)	(Width)	(Height)	(Lbs.)	
E25P E30P 40.70 33.90 26.70	80 Volt:	40-100-11	500 39	Call For more details.. (630) 851-5800				
N/Cov. SB350Ylw Connector: 3386 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E25P/600 E30P/600 Panorama E40P 40.70 33.90 33.00	80 Volt:	40-125-11	625 48.8	Call For more details.. (630) 851-5800				
N/Cov. SB350Ylw Connector: 4127 Min. Weight: Term: A30 4 Wheel Sit down								
E30B (36v) 39.10 30.30 31.20	36 Volt:	18-125-23	1375 48.3	38.2	26.9	30.3	4032	
N/Cov. 6320 SB350Gry Connector: 3350 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E30B (48v) 39.10 30.30 31.20	48 Volt:	24-125-17	1000 46.8	38.2	26.6	30.3	3792	
N/Cov. SB350Blu Connector: 3350 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E30C(36v/30") 38.70 30.30 23.40	36 Volt:	18-85-25	1020 35.8	38.1	29.1	22.9	2988	
N/Cov. SB350Gry Connector: 2740 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E30C(36v/34") 38.70 34.30 23.40	36 Volt:	18-85-29	1190 41.8	38.2	33.6	22.9	3492	
N/Cov. SB350Gry Connector: 2740 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E30C(48v/30") 38.70 30.30 23.40	48 Volt:	24-85-19	765 35.8	38.1	29.5	22.9	3120	
N/Cov. SB350Blu Connector: 2740 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E30C(48v/34") 38.70 34.30 23.40	48 Volt:	24-85-21	850 39.8	38.1	32.6	22.9	3408	
N/Cov. SB350Blu Connector: 2740 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E30C/600(36v/34") 38.70 34.30 23.40	36 Volt:	18-85-29	1190 41.8	38.2	33.6	22.9	3492	
N/Cov. SB350Gry Connector: 3060 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E30C/600(48v/34") 38.70 34.30 23.40	48 Volt:	24-85-21	850 39.8	38.1	32.6	22.9	3408	
N/Cov. SB350Blu Connector: 3060 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								

LINDE FORKLIFT MODEL#	V		CAPACITY	BATTERY	DIMENSIONS			TOTAL
BATTERY COMPARTMENT SIZE (Inches)	O	BATTERY TYPE	6 HOUR RATE	X	Y	Z	BATTERY WEIGHT	
	L		Ah kWh	in. (Length)	in. (Width)	in. (Height)	(Lbs.)	
E35 40.50 34.00 31.00	80 Volt:	40-125-11	625 48.8	Call For more details.. (630) 851-5800				
N/Cov. SB350Ylw Connector: 3902 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E40 E45 E45 600 40.50 39.50 31.00	80 Volt:	40-125-13	750 35.1	Call For more details.. (630) 851-5800				
N/Cov. SB350Ylw Connector: 4562 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E40B (36v) 39.10 33.20 31.20	36 Volt:	18-125-27	1625 57	38.2	31.4	30.3	4860	
N/Cov. SB350Gry Connector: 3770 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E40B (48v) 39.10 33.20 31.20	48 Volt:	24-125-21	1250 58.5	38.2	32.6	30.3	4824	
N/Cov. SB350Blu Connector: 3770 Min. Weight: Term: A30 4 Wheel Sit down Trk dims:								
E48P 40.70 44.90 24.70	80 Volt:							
N/Cov. SB350Ylw Connector: 4345 Min. Weight: Term: A30 4 Wheel Sit down								
ER18(48v) 32.80 29.29 24.50	48 Volt:	24-85-15	595 27.8	32	29.5	22.9	2568	
N/Cov. SB350Blu Connector: 2228 Min. Weight: Term: A30 Rider Sit down Trk dims:								
P250(28") 40.50 28.00 31.00	80 Volt:			Call For more details.. (630) 851-5800				
N/Cov. SB350Ylw Connector: 3435 Min. Weight: Term: A24 Rider Sit down								
40.50 39.30 31.00				Call For more details.. (630) 851-5800				
N/Cov. SB350Ylw Connector: 4800 Min. Weight: Term: A24 Rider Sit down								
RX50 16(24") 32.90 19.50 24.40	24 Volt:	12-85-21	850 19.9	32.6	19.3	22.9	1704	
N/Cov. SB350Blu Connector: 1490 Min. Weight: Term: A30 3 Wheel Sit down								
RX50 16(25") 32.90 19.50 25.20	24 Volt:	12-85-21	850 19.9	32.6	19.3	22.9	1704	
N/Cov. SB350Blu Connector: 1490 Min. Weight: Term: A30 3 Wheel Sit down Trk dims:								
W20(22") 40.50 22.20 18.20	80 Volt:			Call For more details.. (630) 851-5800				
N/Cov. SB350Ylw Connector: 1500 Min. Weight: Term: A24 Rider Sit down								

LINDE FORKLIFT MODEL#	V	BATTERY	CAPACITY	BATTERY	DIMENSIONS			TOTAL
BATTERY	O	BATTERY	6 HOUR	X	Y	Z	BATTERY	
COMPARTMENT	L	TYPE	RATE	in.	in.	in.	WEIGHT	
SIZE (Inches)	T		Ah kWh	(Length)	(Width)	(Height)	(Lbs.)	
W20(28") 40.50 27.90 18.20	80 Volt:						Call For more details.. (630) 851-5800	
N/Cov. SB350Ylw Connector: 1890 Min. Weight: Term: A24 Rider Sit down								
WC20 (24/13") WC30 (24/13") WC40 (24/13") 32.75 13.50 31.00	24 Volt:	12-125-13	750 17.6	30.6	12.9	31	1500	
W/Cov. SB175Gry Connector: 850 Min. Weight: Term: A21 Trk dims:								
WTT (24v) 32.75 13.50 31.00	24 Volt:	12-125-13	750 17.6	30.6	12.9	31	1500	
W/Cov. SB175Gry Connector: 850 Min. Weight: Term: A21 Trk dims:								
2 CLASS: A12 (BTMD) 44.90 24.25 32.95	48 Volt:	24-125-15	875 41	38.2	23.6	30.3	3384	
N/Cov. SB350Blu Connector: 2914 Min. Weight: Term: o 36 Order pickers Trk dims:								
A15 24.60 29.33 33.40	80 Volt:						Call For more details.. (630) 851-5800	
N/Cov. 0 Connector: 0 Min. Weight: Term: 0 0 Turret trucks								
A15Z (BTMD) 44.90 24.25 32.95	48 Volt:	24-125-15	875 41	38.2	23.6	30.3	3384	
N/Cov. SB350Blu Connector: 2914 Min. Weight: Term: o 36 Order pickers Trk dims:								
BOP 30 36.50 14.63 31.50	24 Volt:	12-125-15	875 20.5	36	14	30.3	1692	
N/Cov. SB350Gry Connector: 1600 Min. Weight: Term: B30 Order picker Trk dims:								
BOS 15 36.50 14.63 31.50	24 Volt:	12-125-15	875 20.5	36	14	30.3	1692	
N/Cov. SB350Red Connector: 1600 Min. Weight: Term: A30 Order Picker Trk dims:								
BRT 30D (21") 39.50 21.20 31.80	36 Volt:	18-125-17	1000 35.1	38.1	20.1	30.3	2844	
N/Cov. SB350Gry Connector: 2400 Min. Weight: Term: B24 Reach								
BRT35 (24v) 39.50 14.60 31.80	24 Volt:	12-125-17	1000 23.4	38	13	30.3	1896	
N/Cov. SB350Red Connector: 1425 Min. Weight: Term: B24 Reach Trk dims:								

LINDE FORKLIFT MODEL#	V	BATTERY	CAPACITY	BATTERY	DIMENSIONS	TOTAL	
BATTERY	O	BATTERY	6 HOUR	X	Y	Z	BATTERY
COMPARTMENT	L	TYPE	RATE	in.	in.	in.	WEIGHT
SIZE (Inches)	T		Ah kWh	(Length)	(Width)	(Height)	(Lbs.)
BRT45 (21") 39.50 21.10 31.80	36 Volt:	18-125-17	1000 35.1	38.1	20.1	30.3	2844
N/Cov. SB350Gry Connector: 2400 Min. Weight: Term: B24 Reach							
BRT45(16") BRT35(36v) BST40(36v) BRT 30D(16") 39.50 16.60 31.80	36 Volt:	18-125-13	750 26.3	38.1	15.4	30.3	2250
N/Cov. SB350Gry Connector: 1800 Min. Weight: Term: B24 Reach Trk dims:							
BSC 35 39.25 21.25 32.00	36 Volt:	18-125-17	1000 35.1	38.1	20.1	30.3	2844
N/Cov. SB350Gry Connector: 2400 Min. Weight: Term: A24 Rider Stand up Trk dims:							
BST40 (24v) 39.50 14.60 31.80	24 Volt:	12-125-17	1000 23.4	38	13	30.3	1896
N/Cov. SB350Red Connector: 1425 Min. Weight: Term: B24 Straddle Trk dims:							
EK 10 32.00 11.25 32.00	24 Volt:	12-125-11	625 14.6	31.8	11	30.3	1260
N/Cov. SB175Gry Connector: 0 Min. Weight: Term: A20 Trk dims:							
EK10 HL 32.00 11.25 32.00	24 Volt:	12-125-11	625 14.6	31.8	11	30.3	1260
N/Cov. SB175Gry Connector: 1110 Min. Weight: Term: A20 Trk dims:							
EK10 LL 32.00 11.25 32.00	24 Volt:	12-125-11	625 14.6	31.8	11	30.3	1260
N/Cov. SB175Gry Connector: 820 Min. Weight: Term: A20 Trk dims:							
MX 10 (BTMA) 35.80 19.80 30.50	24 Volt:	12-125-15	875 20.5	Call For more details.. (630) 851-5800			
N/Cov. SB350Red Connector: 0 Min. Weight: Term: A30 Order pickers Trk dims:							
MX 20 (BTMA) 40.50 25.10 34.00	48 Volt:	24-125-15	875 41	38.1	23.6	30.3	3384
N/Cov. SB350Blu Connector: 2930 Min. Weight: Term: 0 36 Order pickers Trk dims:							
MX 30 (BTMA) 38.10 16.00 34.00	72 Volt:	18-125-13	750 37.97	38.1	15.4	30.3	2250
No cover SB350Blu Connector: 4120 Min. Weight: Term: 0 36 Order picker							

LINDE FORKLIFT MODEL#	V		CAPACITY		BATTERY DIMENSIONS		TOTAL	
BATTERY COMPARTMENT SIZE (Inches)	O L T	BATTERY TYPE	6 HOUR RATE	Ah kWh	X in. (Length)	Y in. (Width)	Z in. (Height)	BATTERY WEIGHT (Lbs.)
MX 40 (BTMA) 42.50 40.00 30.50	72 Volt:	36-125-17	1000	70.2	Call For more details..	(630) 851-5800		
N/Cov. SB350Blu Connector: 0 Min. Weight: Term: 0 36 Order picker								
R14 (11") 48.15 11.14 30.87	48 Volt:	24-125-7	375	17.6	Call For more details..	(630) 851-5800		
N/Cov. SB350Blu Connector: 1653 Min. Weight: Term: B24 Reach Trk dims:								
R14 (14") 48.15 14.00 30.87	48 Volt:	24-125-9	500	23.4	Call For more details..	(630) 851-5800		
N/Cov. SB350Blu Connector: 2066 Min. Weight: Term: B24 Reach Trk dims:								
R16 (11") 48.15 11.14 30.87	48 Volt:	24-125-7	375	17.6	Call For more details..	(630) 851-5800		
N/Cov. SB350Blu Connector: 1653 Min. Weight: Term: B24 Reach Trk dims:								
R16 (14") 48.15 13.98 30.87	48 Volt:	24-125-9	500	23.4	Call For more details..	(630) 851-5800		
N/Cov. SB350Blu Connector: 1653 Min. Weight: Term: B24 Reach Trk dims:								
R16 (17") 48.20 16.80 30.80	48 Volt:	24-125-11	625	29.3	Call For more details..	(630) 851-5800		
N/Cov. SB350Blu Connector: 2345 Min. Weight: Term: B30 Reach								
R16HD(14") 48.20 14.00 30.80	48 Volt:	24-125-9	500	23.4	Call For more details..	(630) 851-5800		
N/Cov. SB350Blu Connector: 1970 Min. Weight: Term: 0 0 Reach Trk dims:								
R16HD(17") 48.20 16.80 30.80	48 Volt:	24-125-11	625	29.3	Call For more details..	(630) 851-5800		
N/Cov. SB350Blu Connector: 2345 Min. Weight: Term: B30 Reach Trk dims:								
R16N (14") 40.75 13.90 30.87	48 Volt:	24-125-7	375	17.6	Call For more details..	(630) 851-5800		
N/Cov. SB350Blu Connector: 1641 Min. Weight: Term: B24 Reach Trk dims:								
R16N (17") R20N (17") 40.75 17.44 30.87	48 Volt:	24-125-11	625	29.3	Call For more details..	(630) 851-5800		
N/Cov. SB350Blu Connector: 2065 Min. Weight: Term: B24 Reach Trk dims:								
R20(14") 48.20 14.00 30.80	48 Volt:	24-125-9	500	23.4	Call For more details..	(630) 851-5800		
N/Cov. SB350Blu Connector: 1970 Min. Weight: Term: 0 0 Reach Trk dims:								

LINDE FORKLIFT MODEL#	V		CAPACITY		BATTERY DIMENSIONS		TOTAL	
BATTERY COMPARTMENT SIZE (Inches)	O L T	BATTERY TYPE	6 HOUR RATE	Ah kWh	X in. (Length)	Y in. (Width)	Z in. (Height)	BATTERY WEIGHT (Lbs.)
R20(17") 48.20 16.80 30.80	48 Volt:	24-125-11	625	29.3	Call For more details.. (630) 851-5800			
N/Cov. SB350Blu Connector: 2345 Min. Weight: Term: B30 Reach Trk dims:								
R20(20") 48.20 19.50 30.80	48 Volt:	24-125-13	750	35.1	Call For more details.. (630) 851-5800			
N/Cov. SB350Blu Connector: 3000 Min. Weight: Term: 0 0 Reach Trk dims:								
R20N (21") 40.75 21.00 30.87	48 Volt:	24-125-13	750	35.1	38.1	20.9	30.3	3000
N/Cov. SB350Blu Connector: 2462 Min. Weight: Term: B24 Reach								
R20W 165(14") 48.20 14.00 30.80	48 Volt:	24-125-9	500	23.4	Call For more details.. (630) 851-5800			
N/Cov. SB350Blu Connector: 1970 Min. Weight: Term: 0 0 Reach Trk dims:								
R20W 165(17") 48.20 16.80 30.80	48 Volt:	24-125-11	625	29.3	Call For more details.. (630) 851-5800			
N/Cov. SB350Blu Connector: 2345 Min. Weight: Term: B30 Reach Trk dims:								
R20W 165(20") 48.20 19.50 30.80	48 Volt:	24-125-13	750		Call For more details.. (630) 851-5800			
N/Cov. SB350Blu Connector: 3000 Min. Weight: Term: 0 0 Reach Trk dims:								
V10 LL 32.00 11.25 32.00	24 Volt:	12-125-11	625	14.6	31.9	11	30.3	2520
N/Cov. SB175Gry Connector: 820 Min. Weight: Term: A20 Trk dims:								
V12 015(16") 32.87 16.45 30.86	48 Volt:				Call For more details.. (630) 851-5800			
N/Cov. SB350Blu Connector: 0 Min. Weight: Term: 0 0 Order picker Trk dims:								
V12 015(21") 32.87 20.71 30.86	48 Volt:	24-125-9	500	23.4	32	18.3	30.3	2136
N/Cov. SB350Blu Connector: 0 Min. Weight: Term: 0 0 Order picker Trk dims:								
3 CLASS: 3 CLASS: 3 CLASS:								
BW 60(12v) BWR 60(12v) BWR 40(12v) 31.50 8.25 40.00	12 Volt:	6-85-13	510	6	30.6	7.8	23.3	564
W/Cov. SB175Gry Connector: 450 Min. Weight: Term: B18 Pallet Walkie Trk dims:								

LINDE FORKLIFT MODEL#	V	BATTERY	CAPACITY	BATTERY	DIMENSIONS			TOTAL
BATTERY	O	BATTERY	6 HOUR	X	Y	Z	BATTERY	
COMPARTMENT	L	TYPE	RATE	in.	in.	in.	WEIGHT	
SIZE (Inches)	T		Ah kWh	(Length)	(Width)	(Height)	(Lbs.)	
BW(12v) 31.50 8.25 40.00	12 Volt:	6-85-13	510 6	30.6	7.8	23.3	564	
W/Cov. SB175Gry Connector: 450 Min. Weight: Term: B18 Pallet truck Trk dims:								
BW(24v) 31.50 13.50 40.00	24 Volt:	12-85-13	510 11.9	30.6	12.8	23.3	1128	
W/Cov. SB175Gry Connector: 975 Min. Weight: Term: B18 Pallet truck Trk dims:								
BW80 (24v) BW60(24v) 31.50 13.50 40.00	24 Volt:	12-85-13	510 11.9	30.6	12.8	23.3	1128	
W/Cov. SB175Gry Connector: 900 Min. Weight: Term: B18 Pallet Walkie Trk dims:								
BWR(12v) PPTWR(12v) GAWR(8") 31.50 8.25 40.00	12 Volt:	6-85-13	510 6	30.6	7.8	23.3	564	
W/Cov. SB175Gry Connector: 450 Min. Weight: Term: B18 Pallet truck Trk dims:								
BWR40(24v) BWR60(24v) BWR80(24v) 31.50 13.50 40.00	24 Volt:	12-85-13	510 11.9	30.6	12.8	23.3	1128	
W/Cov. SB175Gry Connector: 900 Min. Weight: Term: B18 Pallet Walkie/Rider Trk dims:								
BWS 40 (12v) 35.80 7.88 40.00	12 Volt:	6-85-15	595	35.2	7.8	23.3	642	
W/Cov. SB175Gry Connector: 690 Min. Weight: Term: B18 Pallet truck								
BWS 40 (24v) 35.80 12.00 40.00	24 Volt:	12-125-13	750 17.6	35.8	11.8	31	1500	
W/Cov. SB175Gry Connector: 1367 Min. Weight: Term: B18 Pallet truck Trk dims:								
ECR 60 ECR 80 32.75 13.50 31.00	24 Volt:	12-125-13	750 17.6	30.6	12.9	31	1500	
W/Cov. SB175Gry Connector: 850 Min. Weight: Term: A21 Trk dims:								
EGU 20 EXU 20 26.00 9.00 26.00	24 Volt:	12-85-7	255 6	25.38	8.67	23.3	708	
W/Cov. SB175Gry Connector: 450 Min. Weight: Term: A21 Pallet Trk dims:								
ETR 32.75 13.50 31.00	24 Volt:	12-85-13	510 11.9	30.6	12.8	23.3	1128	
W/Cov. SB175Gry Connector: 850 Min. Weight: Term: A21 Pallet truck Trk dims:								

LINDE FORKLIFT MODEL#	V	BATTERY	CAPACITY	BATTERY	DIMENSIONS	TOTAL		
BATTERY	O	BATTERY	6 HOUR	X	Y	Z		
COMPARTMENT	L	TYPE	RATE	in.	in.	in.		
SIZE (Inches)	T		Ah	(Length)	(Width)	(Height)		
			kWh					
						BATTERY		
						WEIGHT		
						(Lbs.)		
EW60(13")	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
EWR60(13")								
EW80(13")								
EWR80(13")								
31.50 13.50 40.00								
W/Cov. SB175Red Connector: 900 Min. Weight: Term: A21 Pallet Walkie/Rider Trk dims:								
EW60(8")	12 Volt:	6-85-13	510	6	30.6	7.8	23.3	564
EWR60(8")								
EW80(8")								
EWR80(8")								
31.50 8.25 40.00								
W/Cov. SB175Yel Connector: 450 Min. Weight: Term: A21 Pallet Walkie/Rider Trk dims:								
EWS 40 (12v)	12 Volt:	100-13			Call For more details.. (630) 851-5800			
32.50 8.25 40.00								
W/Cov. SB175Gry Connector: 625 Min. Weight: Term: B21 Pallet								
EWS 40 (24v)	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
EWX 30								
32.50 13.50 40.00								
W/Cov. SB175Gry Connector: 975 Min. Weight: Term: B21 Pallet Trk dims:								
GAW(13")	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
31.50 13.50 40.00								
W/Cov. SB175Gry Connector: 975 Min. Weight: Term: B18 Pallet truck Trk dims:								
GAW(8")	12 Volt:	6-85-13	510	6	30.6	7.8	23.3	564
31.50 8.25 40.00								
W/Cov. SB175Gry Connector: 450 Min. Weight: Term: B18 Pallet truck Trk dims:								
GAWR (13")	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
PPTWR(24v)								
BWR (24v)								
31.50 13.50 40.00								
W/Cov. SB175Gry Connector: 975 Min. Weight: Term: B18 Pallet truck Trk dims:								
MTPR	24 Volt:	12-125-11	625	14.6	31.9	11	31	1260
PALR								
33.00 12.12 31.00								
W/Cov. SB175Gry Connector: 510 Min. Weight: Term: B18 Pallet truck Trk dims:								
MTPW (24v)	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
31.50 13.50 40.00								
W/Cov. SB175Gry Connector: 975 Min. Weight: Term: B18 Pallet truck Trk dims:								
MTPW(12v)	12 Volt:	6-85-13	510	6	30.6	7.8	23.3	564
31.50 8.25 40.00								
W/Cov. SB175Gry Connector: 450 Min. Weight: Term: B18 Pallet truck Trk dims:								

LINDE FORKLIFT MODEL#	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
BATTERY COMPARTMENT SIZE (Inches)	O	BATTERY TYPE	6 HOUR RATE	kWh	X in. (Length)	Y in. (Width)	Z in. (Height)	BATTERY WEIGHT (Lbs.)
	L		Ah					
	T							
MTW (24v) MTWR (24v) 31.12 13.50 40.00	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cov. SB175Gry Connector: 975 Min. Weight: Term: B18 Pallet truck Trk dims:								
MTW(12v) MTWR (12v) 31.12 8.25 40.00	12 Volt:	6-85-13	510	6	30.6	7.8	23.3	564
W/Cov. SB175Gry Connector: 450 Min. Weight: Term: B18 Pallet truck Trk dims:								
P60Z (24V) 32.68 12.87 24.69	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
N/Cov. SB350Red Connector: 980 Min. Weight: Term: A24 Tow Tractor Trk dims:								
P60Z (48V) 32.68 16.30 24.69	48 Volt:	24-85-7	255	11.9	Call For more details.. (630) 851-5800			
N/Cov. SB350Blu Connector: 1190 Min. Weight: Term: A24 Tow Tractor Trk dims:								
PAL W (12v) PAL WR60/80(12v) 31.50 8.25 40.00	12 Volt:	6-85-13	510	6	30.6	7.8	23.3	564
W/Cov. SB175Gry Connector: 450 Min. Weight: Term: B21 Pallet truck Trk dims:								
PAL W (24v) PAL WR60/80(24v) 31.50 13.50 40.00	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cov. SB175Gry Connector: 900 Min. Weight: Term: B21 Pallet truck Trk dims:								
PALW60 (24v) PALW80 (24v) 31.50 13.50 40.00	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cov. SB175Gry Connector: 0 Min. Weight: Term: B21 Pallet Walkie/Rider Trk dims:								
PPTW(12v) 31.50 8.25 40.00	12 Volt:	6-85-13	510	6	30.6	7.8	23.3	564
W/Cov. SB175Gry Connector: 450 Min. Weight: Term: B18 Pallet truck Trk dims:								
PPTW(24v) 31.50 13.50 40.00	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cov. SB175Gry Connector: 975 Min. Weight: Term: B18 Pallet truck Trk dims:								