

RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah      kWh		BATTERY X in. (L)	DIMENSIONS Y      Z in.    in.    in. (W)    (H)			TOTAL BATTERY WEIGHT (Lbs.)
--	------------------	----------------	---	--	----------------------------	---	--	--	--------------------------------------

470-C30(36v)      36 Volt:      18-85-19      765      26.9      34.9      25.5      22.9      2340  
35.55 27.90 22.81

N/Cov. optional connector 1800 Min. Weight: Term: 00 4 Wheel-Sit down

470-C30(48v)      48 Volt:      24-85-15      595      27.8      35.2      25.4      22.9      2568  
35.55 27.90 22.81

N/Cov. optional connector 1800 Min. Weight: Term: 00 4 Wheel-Sit down

470-C40(36v)      36 Volt:      18-85-23      935      32.8      38.1      26.9      22.9      2736  
38.69 27.90 22.81

N/Cov. optional connector 2450 Min. Weight: Term: 00 4 Wheel-Sit down

470-C40(48v)      48 Volt:      24-85-17      680      31.8      38.1      26.9      22.9      2856  
38.69 27.90 22.81

N/Cov. optional connector 2450 Min. Weight: Term: 00 4 Wheel-Sit down

470-C50(36v)      36 Volt:      18-85-23      935      32.8      38.1      26.9      22.9      2736  
39.40 27.90 22.81

N/Cov. optional connector 2450 Min. Weight: Term: 00 4 Wheel-Sit down

470-C50(48v)      48 Volt:      24-85-17      680      31.8      38.1      26.9      22.9      2856  
39.40 27.90 22.81

N/Cov. optional connector 2450 Min. Weight: Term: 00 4 Wheel-Sit down

470-C50HM(36v)      36 Volt:      18-85-23      935      32.8      38.1      26.9      22.9      2736  
38.69 27.90 22.81

N/Cov. optional connector 2600 Min. Weight: Term: 00 4 Wheel-Sit down

470-C50HM(48v)      48 Volt:      24-85-17      680      31.8      38.1      26.9      22.9      2856  
38.69 27.90 22.81

N/Cov. optional connector 2600 Min. Weight: Term: 00 4 Wheel-Sit down

470-C50L(36v)      36 Volt:      18-85-27      1105      38.8      38.1      31.4      22.9      3240  
470-C60(36v)  
39.40 33.75 22.81

N/Cov. optional connector 3100 Min. Weight: Term: 00 4 Wheel-Sit down

RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah      kWh		BATTERY X in. (L)	DIMENSIONS Y      Z in.    in. (W)    (H)			TOTAL BATTERY WEIGHT (Lbs.)
--	------------------	----------------	---	--	----------------------------	--	--	--	--------------------------------------

470-C50L(48v)      48 Volt:    24-85-21      850      39.8      38.1      32.6      22.9      3408  
470-C60(48v)  
39.40 33.75 22.81

N/Cov. optional connector 3100 Min. Weight: Term: 00 4 Wheel-Sit down

DSD30r(36V)      36 Volt:    18-85-19      765      26.9      34.9      25.5      22.9      2340  
DSD35r(36V)  
35.50 27.80 23.20

N/Cov. SB350Gry Connector: 1650 Min. Weight: Term: B24 4 Wheel-Sit down

DSD30r(48V)      48 Volt:    24-85-15      595      27.8      35.2      25.4      22.9      2568  
DSD35r(48V)  
35.50 27.80 23.20

N/Cov. SB350Blu Connector: 1650 Min. Weight: Term: B24 4 Wheel-Sit down

DSD40r(36V)      36 Volt:    18-85-25      1020      35.8      38.1      29.9      22.9      2988  
39.40 30.40 23.20

N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B24 4 Wheel-Sit down

DSD40r(48V)      48 Volt:    24-85-19      765      35.8      38.1      29.5      22.9      3120  
39.40 30.40 23.20

N/Cov. SB350Blu Connector: 2200 Min. Weight: Term: B24 4 Wheel-Sit down

DSD50r(36V)      36 Volt:    18-85-25      1020      35.8      38.1      29.9      22.9      2988  
39.40 30.40 23.20

N/Cov. SB350Gry Connector: 2900 Min. Weight: Term: B24 4 Wheel-Sit down Trk dims:

DSD50r(48V)      48 Volt:    24-85-19      765      35.8      38.1      29.5      22.9      3120  
39.40 30.40 23.20

N/Cov. SB350Blu Connector: 2900 Min. Weight: Term: B24 4 Wheel-Sit down

DSD5Er(36V)      36 Volt:    18-85-29      1190      41.8      38.2      33.6      22.9      3492  
DSD60r(36V)  
39.40 34.30 23.20

N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 4 Wheel-Sit down

DSD5Er(48V)      48 Volt:    24-85-21      850      39.8      38.1      32.6      22.9      3408  
DSD60r(48V)  
39.40 34.30 23.20

N/Cov. SB350Blu Connector: 3100 Min. Weight: Term: B24 4 Wheel-Sit down

RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
--	------------------	----------------	--------------------------------------	--	----------------------------	---	--	--------------------------------------

RTW-C30TT (36V) 36 Volt: 18-85-13 510 17.9 31.6 20.4 22.9 1692  
33.07 20.86 23.50

N/Cov. SB350Gry Connector: 1410 Min. Weight: Term: A30 3 Wheel-Sit down

RTW-C30TT (48V) 48 Volt: 24-85-9 340 15.9 29.3 19.3 22.9 1680  
33.07 20.86 23.50

N/Cov. SB350Blu Connector: 1410 Min. Weight: Term: A30 3 Wheel-Sit down

RTW-C35TT (36V) 36 Volt: 18-85-15 595 20.9 31.8 23.6 22.9 1926  
33.07 25.19 23.50

N/Cov. SB350Gry Connector: 1706 Min. Weight: Term: A30 3 Wheel-Sit down

RTW-C35TT (48V) 48 Volt: 24-85-11 425 19.9 Call for more Info:(630-851-5800  
33.07 25.19 23.50

N/Cov. SB350Blu Connector: 1706 Min. Weight: Term: A30 3 Wheel-Sit down

RTW-C40TT (36V) 36 Volt: 18-85-19 765 26.9 31.9 29.6 22.9 2340  
33.07 30.39 24.68

N/Cov. SB350Gry Connector: 2016 Min. Weight: Term: A30 3 Wheel-Sit down

RTW-C40TT (48V) 48 Volt: 24-85-15 595 27.8 32 29.5 22.9 2568  
33.07 30.39 24.68

N/Cov. SB350Blu Connector: 2016 Min. Weight: Term: A30 3 Wheel-Sit down

Class 2 Type

019XD(13") 24 Volt: 12-85-13 510 11.9 30.6 12.8 23.3 1128  
31.00 13.00 24.00

W/Cover SB175Gry Connector: 965 Min. Weight: Term: B24 Pallet-Elf

019XD(9") 24 Volt: 12-85-7 255 6 25.4 8.7 23.3 708  
31.00 9.19 24.00

W/Cover SB175Gry Connector: 0 Min. Weight: Term: B24 Pallet-Elf

14 24 Volt: 12-125-15 875 20.5 36 14 31 1692  
36.50 14.50 40.00

W/Cover SB350Gry Connector: 1600 Min. Weight: Term: 00 Order Picker

150 24 Volt: 12-125-15 875 20.5 36 14 30.3 1692  
152  
36.38 14.00 30.88

N/Cov. SB350Red Connector: 1600 Min. Weight: Term: B12 Order picker

RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah      kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)      Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
--	------------------	----------------	---	--	----------------------------	--	--	--------------------------------------

160                                      36 Volt:    18-125-11                      625            21.9            38.1            13.1            30.3            1890  
162  
38.38 13.69 30.88

N/Cov. SB350Gry Connector: 1600 Min. Weight: Term: C12 Order picker

19(13")                                      24 Volt:    12-85-13                      510            11.9            30.6            12.8            23.3            1128  
31.00 13.00 24.00

W/Cover SB175Gry Connector: 965 Min. Weight: Term: B24 Pallet-Elf

19(9")                                      24 Volt:    12-85-7                      255            6            25.4            8.7            23.3            708  
31.00 9.19 24.00

W/Cover SB175Gry Connector: 0 Min. Weight: Term: B24 Pallet-Elf

20i                                      24 Volt:    12-125-15                      875            20.5            36            14            30.3            1692  
36.12 14.12 30.50

N/Cov. SB350Red Connector: 1600 Min. Weight: Term: B11 Straddle

21 (16")                                      36 Volt:    18-125-13                      750            26.3            38.1            15.4            30.3            2250  
38.38 16.50 31.38

N/Cov. SB350Red Connector: 2000 Min. Weight: Term: B14 Rider-Sit down

212-OPC22                                      24 Volt:    12-125-13                      750            17.6            30.6            12.9            30.3            1500  
218-OPC22  
32.80 13.50 32.00

N/Cov. SB175Gry Connector: 950 Min. Weight: Term: C12 Gopher

21i                                      36 Volt:    18-125-13                      750            26.3            38.1            15.4            30.3            2250  
38.12 16.12 30.50

N/Cov. SB175Gry Connector: 2000 Min. Weight: Term: B23 Straddle

233-OPC22t                                      24 Volt:    12-125-13                      750            17.6            30.6            12.9            30.3            1500  
32.80 13.50 32.00

N/Cov. SB175Gry Connector: 1150 Min. Weight: Term: C12 Gopher

24 EASi                                      24 Volt:    12-125-17                      1000            23.4            38.2            13.5            30.3            1896  
38.63 14.25 31.63

N/Cov. SB350Gry Connector: 1600 Min. Weight: Term: B23 Reach-Standup

RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah      kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)      Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
--	------------------	----------------	---	--	----------------------------	--	--	--------------------------------------

30(14")                      36 Volt:    18-125-11            625            21.9            38.1            13.1            30.3            1890  
31E(14")  
31(14")  
38.38 14.50 31.38

N/Cov.    SB350Gry Connector: 0 Min. Weight: Term: B14 Reach-Standup

31E(16")                      36 Volt:    18-125-13            750            26.3            38.1            15.4            30.3            2250  
30(16")  
31F(16")  
31(16")  
38.38 16.50 31.38

N/Cov.    SB350Gry Connector: 0 Min. Weight: Term: B14 Reach-Standup

31F (21")                      36 Volt:    18-125-13            750            26.3            31.6            20.4            30.3            2250  
31.75 21.25 31.00

N/Cov.    SB350Gry Connector: 0 Min. Weight: Term: B14 Reach-Standup

31F(14")                      36 Volt:    18-125-11            625            21.9            38.1            13.1            30.3            1890  
21(14")  
38.38 14.50 31.38

N/Cov.    SB350Gry Connector: 0 Min. Weight: Term: B14 Reach-Standup

31i EASi                      36 Volt:    18-125-13            750            26.3            38.1            15.4            30.3            2250  
38.63 16.25 31.63

N/Cov.    SB350Gry Connector: 2000 Min. Weight: Term: B14 Reach-Standup

31i R40TT                      36 Volt:    18-125-13            750            26.3            38.1            15.4            30.3            2250  
39.00 16.12 30.75

N/Cov.    SB350Gry Connector: 2000 Min. Weight: Term: B14 Reach-Standup

33                              36 Volt:    18-125-13            750            26.3            38.1            15.4            30.3            2250  
34  
35  
36  
38.12 16.12 30.75

N/Cov.    SB175Gry Connector: 2000 Min. Weight: Term: B9 Reach-Swing

38                              36 Volt:    18-125-17            1000            35.1            38.1            20.1            30.3            2844  
38.75 20.75 30.75

N/Cov.    SB350Gry Connector: 2700 Min. Weight: Term: C19 Reach-Swing

RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah      kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)      Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
--	------------------	----------------	---	--	----------------------------	--	--	--------------------------------------

40-R40TN(14")      24 Volt:    12-125-15      875      20.5      36      14      30.3      1692  
40-R40TT(14")  
36.00 14.38 34.00

W/Cover ECLkgHalf Connector: 1600 Min. Weight: Term: MT0 Reach

40-R45TN(16")      24 Volt:      125-15      Call for more Info:(630-851-5800  
40-R45TT(16")  
36.00 16.38 34.00

W/Cover ECLkgHalf Connector: 2000 Min. Weight: Term: MT0 Reach

40-R60TN(19")      24 Volt:    12-125-23      1375      32.2      35.6      19.3      31      2688  
40-R60TT(19")  
37.00 19.00 34.00

W/Cover ECLkgHalf Connector: 2200 Min. Weight: Term: MT0 Reach

40-R70TN(22")      24 Volt:    12-125-23      1375      32.2      35.6      19.3      31      2688  
40-R70TT(22")  
37.00 22.00 34.00

W/Cover ECLkgHalf Connector: 2600 Min. Weight: Term: MT0 Reach

41      24 Volt:    12-125-15      875      20.5      36      14      30.3      1692  
36.25 16.38 34.00

N/Cov. 0 Connector: 2000 Min. Weight: Term: MT11 Order picker-NA

42 (16")      24 Volt:    12-125-15      875      20.5      36      14      30.3      1692  
36.50 16.75 40.00

W/Cover ECLkgHalf Connector: 1600 Min. Weight: Term: MT0 Reach

42 (20")      24 Volt:    12-125-23      1375      32.2      35.6      19.3      31      2688  
36.50 20.00 40.00

W/Cover ECLkgHalf Connector: 2300 Min. Weight: Term: MT0 Reach

42 (22")      24 Volt:    12-125-23      1375      32.2      35.6      19.3      31      2688  
36.50 22.00 40.00

W/Cover ECLkgHalf Connector: 2300 Min. Weight: Term: MT0 Reach

44      36 Volt:    18-125-19      1125      39.5      38.2      22.3      31      3382  
39.00 22.75 34.00

W/Cover SB350Gry Connector: 3000 Min. Weight: Term: MT11 Reach

RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah      kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)      Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
--	------------------	----------------	---	--	----------------------------	--	--	--------------------------------------

4DR45TT                      36 Volt:    18-125-13            750        26.3        38.1        15.4        30.3        2250  
38.88 16.12 31.62

N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B11 Reach-EASi-4D

5200(13")                    24 Volt:    12-125-13            750        17.6        30.6        12.9        30.3        1500  
5400(13")  
31.00 13.00 30.88

N/Cov. SB350Red Connector: 950 Min. Weight: Term: C20 Order Picker

5200(14")                    24 Volt:    12-125-15            875        20.5        36            14            30.3        1692  
5400(14")  
36.38 14.12 30.88

N/Cov. SB350Red Connector: 950 Min. Weight: Term: C20 Order Picker

537 (21")                    48 Volt:    24-125-13            750        35.1        38.2        20.5        30.3        3000  
44.38 21.25 32.30

N/Cov. SB350Blu Connector: 2900 Min. Weight: Term: B20 Reach-Swing

537 (24")                    48 Volt:    24-125-15            875        41            38.2        23.6        30.3        3384  
44.38 24.00 32.30

N/Cov. SB350Blu Connector: 2900 Min. Weight: Term: B20 Reach-Swing

5600(14")                    36 Volt:    18-125-11            625        21.9        38.1        13.1        30.3        1890  
38.38 13.69 30.88

N/Cov. SB350Gry Connector: 1600 Min. Weight: Term: C12 Order Picker

5600(16")                    36 Volt:    18-125-13            750        26.3        38.1        15.4        30.3        2250  
38.38 16.12 30.88

N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: C12 Order Picker

589                            36 Volt:    18-85-7                255        9            Call for more Info:(630-851-5800  
26.00 13.00 26.00

N/Cov. optional connector 0 Min. Weight: Term: C33 0

60 (16")                    36 Volt:    18-125-13            750        26.3        38.1        15.4        30.3        2250  
38.75 16.00 31.00

N/Cov. SB350Gry Connector: 1900 Min. Weight: Term: C22 Counterbalance-Pacer





RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah      kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)      Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
--	------------------	----------------	---	--	----------------------------	--	--	--	--------------------------------------

75                                      36 Volt:    9-125-15                      875            15.4            29.3            12.5            30.3            1269  
76  
42.38 12.75 30.88

N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: CT36 Side loader-Narrow aisle

80                                      36 Volt:    18-125-17                      1000            35.1            38.1            20.1            30.3            2844  
38.75 20.75 30.75

N/Cov. SB350Gry Connector: 2500 Min. Weight: Term: B9 Reach-swing

80A                                      36 Volt:    18-125-13                      750            26.3            38.1            15.4            30.3            2250  
38.38 16.12 30.62

N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B14 Reach-swing

85                                      72 Volt:    18-125-13                      750                                      Call for more Info:(630-851-5800  
87  
88  
46.75 13.12 31.50

N/Cov. SB175Gry Connector: 4000 Min. Weight: Term: C19 Reach-swing

CSR30T/SA(21")                      48 Volt:    24-125-13                      750            35.1            44            20.6            30.3            3000  
44.38 21.00 31.00

N/Cov. SB350Blu Connector: 2900 Min. Weight: Term: B20 Reach-Swing

CSR30T/SB (24")                      48 Volt:    24-125-15                      875            41            44            23.6            30.3            3384  
44.38 24.00 31.00

N/Cov. SB350Blu Connector: 2900 Min. Weight: Term: B20 Reach-Swing

DR25TT (18")                      36 Volt:    18-125-15                      875            30.7            38.1            17.7            30.3            2538  
DR30TT (18")  
38.62 18.12 31.30

N/Cov. SB350Gry Connector: 2300 Min. Weight: Term: B11 Reach-EASi

DR25TT(24v/14")                      24 Volt:    12-125-17                      1000            23.4            38.2            13.5            30.3            1896  
38.62 14.12 31.30

N/Cov. SB350Red Connector: 1600 Min. Weight: Term: B11 Reach-EASi

RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah      kWh		BATTERY X in. (L)	DIMENSIONS Y      Z in.    in.    in. (W)    (H)			TOTAL BATTERY WEIGHT (Lbs.)
DR25TT(36v/14") 38.62 14.12 31.30	36 Volt:	18-125-11	625	21.9	38.1	13.1	30.3	1890	

N/Cov. SB350Gry Connector: 1600 Min. Weight: Term: B11 Reach-EASi

DR25TT(36v/16") DR30TT(36v/16") 38.62 16.12 31.30	36 Volt:	18-125-13	750	26.3	38.1	15.4	30.3	2250
---	----------	-----------	-----	------	------	------	------	------

N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B11 Reach-EASi

DR30TT(36v/21") DR30TT-B(36v/21") 38.62 21.12 31.30	36 Volt:	18-125-17	1000	35.1	38.1	20.1	30.3	2844
---	----------	-----------	------	------	------	------	------	------

N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B11 Reach-EASi

DSS300P DSS350P 38.88 16.25 31.62	36 Volt:	18-125-13	750	26.3	38.1	15.4	30.3	2250
---	----------	-----------	-----	------	------	------	------	------

N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: C11 Dockstocker

DSS400P DSS500P 38.50 21.25 32.30	36 Volt:	18-125-17	1000	35.1	38.1	20.1	30.3	2844
---	----------	-----------	------	------	------	------	------	------

N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: C20 Dock stocker

EASi 4000 38.63 13.44 31.62	24 Volt:	12-125-15	875	20.5	38.2	12	31	1692
--------------------------------	----------	-----------	-----	------	------	----	----	------

W/Cover SB350Red Connector: 1600 Min. Weight: Term: C11 Reach-Narrow aisle

EASi- OPC 31.00 13.00 30.88	24 Volt:	12-125-13	750	17.6	30.6	12.9	30.3	1500
--------------------------------	----------	-----------	-----	------	------	------	------	------

N/Cov. SB350Red Connector: 0 Min. Weight: Term: C20 Counterbalance

EASi4500 38.88 16.25 31.62	36 Volt:	18-125-13	750	37.97	38.1	15.4	30.3	2250
-------------------------------	----------	-----------	-----	-------	------	------	------	------

N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: C11 Reach-Narrow aisle

OPC-30TT (24v) 36.50 14.50 31.00	24 Volt:	12-125-15	875	20.5	36	14	30.3	1692
-------------------------------------	----------	-----------	-----	------	----	----	------	------

N/Cov. SB350Red Connector: 1600 Min. Weight: Term: B12 Order Picker-EASi

RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah      kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)      Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
--	------------------	----------------	---	--	----------------------------	--	--	--------------------------------------

OPC-30TT (36v)      36 Volt:    18-125-11      625      21.9      38.1      13.1      30.3      1890  
38.38 13.69 31.00

N/Cov.    SB350Gry Connector: 1600 Min. Weight: Term: C12 Order Picker-EASi

OPC-30TT (w/oHi-    24 Volt:    12-125-13      750      17.6      30.6      12.9      30.3      1500  
Pro24v)  
31.00 13.00 30.88

N/Cov.    SB350Red Connector: 920 Min. Weight: Term: C20 Order Picker-EASi Trk dims:

R30-C30              36 Volt:    18-125-15      875      30.7      38.1      17.7      30.3      2538  
R35-C35  
38.50 18.50 32.30

N/Cov.    SB350Gry Connector: 0 Min. Weight: Term: B11 Counterbal-Pacer

R30TT(24V)          24 Volt:    12-125-17      1000      23.4      38.2      13.5      30.3      1896  
R30TN(24V/14")  
R40TN(24V/14")  
38.63 14.12 31.00

N/Cov.    SB350Red Connector: 1600 Min. Weight: Term: B11 Reach-EASi

R30TT(36v/14")      36 Volt:    18-125-11      625      21.9      38.1      13.1      30.3      1890  
R30TN(36v/14")  
R35TT(36v/14")  
R40TT(36v/14")  
R40TN(36v/14")  
38.63 14.12 31.00

N/Cov.    SB350Gry Connector: 1600 Min. Weight: Term: B11 Reach-EASi

R30TT(36v/16")      36 Volt:    18-125-13      750      26.3      38.1      15.4      30.3      2250  
R35TT(36v/16")  
R40TT(36v/16")  
R40TTM(36v/16")  
38.62 16.12 31.00

N/Cov.    SB350Gry Connector: 2000 Min. Weight: Term: B11 Reach-EASi

R35TT(24V/14")      24 Volt:    12-125-17      1000      23.4      38.2      13.5      30.3      1896  
R40TT(24V/14")  
38.63 14.12 31.00

N/Cov.    SB350Red Connector: 1600 Min. Weight: Term: B11 Reach-EASi

RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah      kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)      Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
--	------------------	----------------	---	--	----------------------------	--	--	--------------------------------------

R40-C40                      36 Volt:    18-125-17      1000      35.1      38.1      20.1      30.3      2844  
38.50 21.25 32.30

N/Cov.    SB350Gry Connector: 0 Min. Weight: Term: B11 Counterbal-Pacer

R40TT (18")                      36 Volt:    18-125-15      875      30.7      38.1      17.7      30.3      2538  
R40TTM(18")  
R45TT(18")  
R45TT-M(18")  
38.63 18.12 31.38

N/Cov.    SB350Gry Connector: 2300 Min. Weight: Term: B11 Reach-EASi

R45TT (36V/16")                      36 Volt:    18-125-13      750      26.3      38.1      15.4      30.3      2250  
R45TT-M (36V/16")  
38.88 16.12 31.00

N/Cov.    SB350Gry Connector: 2000 Min. Weight: Term: B11 Reach-EASi

R45TT-MB(36/21")                      36 Volt:    18-125-17      1000      35.1      38.1      20.1      30.3      2844  
R45TT-MA(36/21")  
38.88 21.12 31.00

N/Cov.    SB350Gry Connector: 2600 Min. Weight: Term: B11 Reach-EASi

R50/C50TT                      36 Volt:    18-125-19      1125      39.5      38.2      22.4      30.3      3204  
38.50 23.50 32.30

N/Cov.    SB350Gry Connector: 2700 Min. Weight: Term: B11 Counterbal-Pacer Trk dims:

R50-C50                      36 Volt:    18-125-19      1125      39.5      38.2      22.4      30.3      3204  
38.50 23.75 32.30

N/Cov.    SB350Gry Connector: Min. Weight: Term: B11 Counterbal-Pacer Trk dims:

S30(24v/14")                      24 Volt:    12-125-15      875      20.5      36      14      30.3      1692  
S40(24v/14")  
38.62 14.12 31.30

N/Cov.    SB350Red Connector: 1600 Min. Weight: Term: B11 Straddle-EASi

S30(36v)                      36 Volt:    18-125-13      750      26.3      38.1      15.4      30.3      2250  
S40(36v)  
38.62 16.12 31.30

N/Cov.    SB350Gry Connector: 1600 Min. Weight: Term: B11 Straddle-EASi

RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
--	------------------	----------------	--------------------------------------	--	----------------------------	--	--	--------------------------------------

S30(36v/14") 36 Volt: 18-125-11 625 21.9 38.1 13.1 30.3 1890  
S40(36v/14")  
38.62 14.12 31.30

N/Cov. SB350Gry Connector: 1600 Min. Weight: Term: B11 Straddle-EASi

3 CLASS: 3 CLASS: 3 CLASS:

10 (7") 12 Volt: 6-85-5 170 2 12.5 6.5 22.9 288  
12.75 7.50 22.75

N/Cov. SB175Gry Connector: 0 Min. Weight: Term: AB6 Pallet-Walkie

10 (9") 24 Volt: 6-85-7 255 3 Call for more Info:(630-851-5800  
13.13 9.00 22.75

N/Cov. SB175Gry Connector: 0 Min. Weight: Term: CD10 Pallet-Walkie

101T-F40L (12v) 12 Volt: 6-85-11 425 5 26 7.8 23.3 486  
28.00 8.75 26.50

W/Cover SB175Gry Connector: 200 Min. Weight: Term: B12 Pallet-Walkie

101TF40L(24v) 24 Volt: 12-100-7 300 7 Call for more Info:(630-851-5800

101  
110  
28.00 8.75 26.50

W/Cover SB175Gry Connector: 200 Min. Weight: Term: B12 Pallet-Walkie

102XM(24v/8"W) 24 Volt: 12-100-5 200 4.7 Call for more Info:(630-851-5800  
26.50 7.75 32.00

W/Cover SB175Red Connector: 200 Min. Weight: Term: B18 Pallet-Walkie

102XM(24v/9"W) 24 Volt: 12-85-7 255 6 25.4 8.7 23.3 708  
26.50 9.00 32.00

W/Cover SB175Red Connector: 200 Min. Weight: Term: B18 Pallet-Walkie

11 24 Volt: 6-85-11 425 5 18.9 8.9 22.9 354  
12  
19.38 9.38 22.50

N/Cov. SB175Gry Connector: 0 Min. Weight: Term: CD5 Pallet-Walkie

RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah      kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)      Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
--	------------------	----------------	---	--	----------------------------	--	--	--------------------------------------

110 TOW                      24 Volt:    12-85-13            510            11.9            30.6            12.8            23.3            1128  
32.00 13.38 23.50

W/Cover SB175Gry Connector: 200 Min. Weight: Term: B12 Pallet-Walkie

110F-F40L                      12 Volt:    6-100-13            600            7            Call for more Info:(630-851-5800  
110F-F60L  
32.00 8.13 23.50

W/Cover SB175Gry Connector: 200 Min. Weight: Term: B12 Pallet-Walkie

110FRC40L                      24 Volt:    12-85-13            510            11.9            30.6            12.8            23.3            1128  
110FRE40L  
110FRC60L  
110FRE60L  
32.00 13.38 23.50

W/Cover SB175Gry Connector: 200 Min. Weight: Term: B12 Pallet-Walkie

111 (12v)                      12 Volt:    6-100-13            600            7            Call for more Info:(630-851-5800  
32.00 8.13 23.50

W/Cover SB175Gry Connector: 200 Min. Weight: Term: B12 Pallet-Walkie

111(24v)                      24 Volt:    12-85-13            510            11.9            30.6            12.8            23.3            1128  
112  
113  
114  
31.50 13.00 40.00

W/Cover SB175Gry Connector: 965 Min. Weight: Term: B12 Pallet-Walkie

111(24v/9"W)                      24 Volt:    12-85-7            255            6            25.4            8.7            23.3            708  
31.00 9.19 31.00

W/Cover SB175Gry Connector: 490 Min. Weight: Term: B12 Pallet-Walkie

111XD (12v)                      12 Volt:    6-100-13            600            7  
32.00 8.13 23.50

W/Cover SB175Gry Connector: 200 Min. Weight: Term: B12 Pallet-Walkie

111XD(24v)                      24 Volt:    12-85-13            510            11.9            30.6            12.8            23.3            1128  
112XD  
113XD  
114XD  
31.50 13.00 40.00

W/Cover SB175Gry Connector: 965 Min. Weight: Term: B12 Pallet-Walkie

RAYMOND Forklift Model Battery Compartment Size	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
--	------------------	----------------	--------------------------------------	--	----------------------------	--	--	--	--------------------------------------

111XD(24v/9"W) 24 Volt: 12-85-7 255 6 25.4 8.7 23.3 708  
31.00 9.19 31.00

W/Cover SB175Gry Connector: 490 Min. Weight: Term: B12 Pallet-Walkie

8300 24 Volt: 12-85-13 510 11.9 30.6 12.8 23.3 1128  
8400  
8500  
8600  
31.00 13.38 31.00

W/Cover SB175Gry Connector: 965 Min. Weight: Term: B18 Pallet-Walkie

8300(6"W) 24 Volt: 12-85-7 255 6 33.6 6.5 23.3 708  
34.44 6.69 31.00

W/Cover SB175Gry Connector: 490 Min. Weight: Term: B18 Pallet-Walkie

8300(9"W) 24 Volt: 12-85-7 255 6 25.4 8.7 23.3 708  
31.00 9.19 31.00

W/Cover SB175Gry Connector: 490 Min. Weight: Term: B18 Pallet-Walkie

RAS20 24 Volt: 12-100-7 300 7 Call for more Info:(630-851-5800  
RAS25  
27.30 8.75 40.00

W/Cover SB175Red Connector: 290 Min. Weight: Term: B15 Pallet-Straddle

RCS20 24 Volt: 12-85-13 510 11.9 30.6 12.8 23.3 1128  
RCS30  
RCS40  
32.30 13.30 40.00

W/Cover SB175Red Connector: 950 Min. Weight: Term: B20 Pallet-Counterbalance

RSS22 24 Volt: 12-85-7 255 6 25.4 8.7 23.3 708  
32.30 9.00 40.00

W/Cover SB175Red Connector: 300 Min. Weight: Term: B20 Pallet-Straddle

RSS30 24 Volt: 12-85-13 510 11.9 30.6 12.8 23.3 1128  
RSS40  
32.30 13.30 40.00

W/Cover SB175Red Connector: 950 Min. Weight: Term: B20 Pallet-Straddle