

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
Class 1 Trucks								
ERC025AC (48v) ERC030AC (48v) 35.00 26.50 23.00	48 V	24-85-13	510	23.9	30.6	25.4	22.9	2256
N/Cov. SB350Blu Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down								
ERC025AC(36V) ERC030AC(36V) ERC040AC(36v) 35.00 26.50 23.00	36 V	18-85-17	680	23.9	33.1	25.6	22.9	2142
N/Cov. SB350Gry Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down								
ERC030AF(36/34"L") ERC040AF(36/34"L") ERC040AG(36/34L") ERC030AG(36/34L") 34.57 27.36 24.29	36 V	18-85-17	680	23.9	33.1	25.6	22.9	2142
N/Cov. SB350Gry Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down								
ERC030AF(36/35L") ERC040AF(36/35L") ERC040AG(36/35L") ERC030AG(36/35L") 35.79 27.36 24.29	36 V	18-85-19	765	26.9	34.9	25.5	22.9	2340
N/Cov. SB350Gry Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down								
ERC030AF(48/34L") ERC040AF(48/34L") ERC030AG(48/34L") ERC040AG(48/34L") 34.57 27.36 24.29	48 V	24-85-13	510	23.9	30.6	25.4	22.9	2256
N/Cov. SB350Blu Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down								
ERC030AF(48/35L") ERC040AF(48/35L") ERC030AG(48/35L") ERC040AG(48/35L") 35.79 27.36 24.29	48 V	24-85-15	595	27.8	35.2	25.6	22.9	2568
N/Cov. SB350Blu Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down								
ERC030AH(36/35L") ERC040AH(36/35L") 35.79 27.36 24.29	36 V	18-85-19	765	26.9	34.9	25.5	22.9	2340
N/Cov. SB350Gry Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down								

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			TOTAL BATTERY WEIGHT (Lbs.)
			Ah	kWh	X in. (L)	Y in. (W)	Z in. (H)	
ERC030AH(48/34L") ERC040AH(48/34L") 34.57 27.36 24.29 N/Cov. SB350Blu Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-13	510	23.9	30.6	25.4	22.9	2256
ERC030AH(48/35L") ERC040AH(48/35L") 35.79 27.36 24.29 N/Cov. SB350Blu Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-15	595	27.8	35.2	25.6	22.9	2568
ERC030B (36v) ERC035B (36v) ERC040B (36v) ERC030BC(36v) ERC040BC(36v) 39.25 27.70 23.00 N/Cov. SB350Gry Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-21	850	29.8	39	25.6	22.9	2556
ERC030B(48v) ERC035B(48v) 39.25 27.70 23.00 N/Cov. SB350Blu Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
ERC030BG(36/34"L") ERC040BG(36/34"L") 34.57 27.36 24.29 N/Cov. SB350Gry Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-17	680	23.9	33.1	25.6	22.9	2142
ERC030BG(36/35L") ERC040BG(36/35L") 35.79 27.36 24.29 N/Cov. SB350Gry Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-19	765	26.9	34.9	25.5	22.9	2340
ERC030BG(48/34L") ERC040BG(48/34L") 34.57 27.36 24.29 N/Cov. SB350Blu Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-13	510	23.9	30.6	25.4	22.9	2256
ERC040BG(48/35L") 35.79 27.36 24.29 N/Cov. SB350Blu Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down								
ERC040(36/27") ERC040RG(36/27") ERC050(36/27") ERC050RG(36/27") 38.86 27.36 24.41 N/Cov. SB350Gry Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-23	935	32.8	38.1	26.9	22.9	2736

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			TOTAL BATTERY WEIGHT (Lbs.)
			Ah	kWh	X in. (L)	Y in. (W)	Z in. (H)	
ERC040(36/30") ERC050(36/30") 38.86 30.75 24.41 N/Cov. SB350Gry Connector: 2500 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-25	1020	35.8	38.1	29.9	22.9	2988
ERC040(48/27") ERC050(48/27") ERC040ZF(48/27") ERC050ZF(48/27") 38.86 27.36 24.41 N/Cov. SB350Blu Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
ERC040(48/30") ERC050(48/30") 38.86 30.75 24.41 N/Cov. SB350Blu Connector: 2500 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120
ERC040AH(36/34L") ERC030AH(36/34L") 34.57 27.36 24.29 N/Cov. SB350Gry Connector: 1850 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-17	680	23.9	33.1	25.6	22.9	2142
ERC040B(48v) ERC030BC(48v) ERC040BC(48v) 39.25 27.70 23.00 N/Cov. SB350Blu Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
ERC040GH(36/27") ERC050GH(36/27") 38.86 27.36 24.41 N/Cov. SB350Gry Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-23	935	32.8	38.1	26.8	22.9	2736
ERC040GH(36/30") ERC050GH(36/30") 38.86 30.75 24.41 N/Cov. SB350Gry Connector: 2500 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-25	1020	35.8	38.1	29.9	22.9	2988
ERC040GH(36/33") ERC050GH(36/33") ERC060GH(36/33") 38.86 33.15 24.41 N/Cov. SB350Gry Connector: 2900 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-27	1105	38.8	38.1	31.4	22.9	3240
ERC040GH(48/27") ERC050GH(48/27") 38.86 27.36 24.41 N/Cov. SB350Blu Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			TOTAL BATTERY WEIGHT (Lbs.)
			Ah	kWh	X in. (L)	Y in. (W)	Z in. (H)	
ERC040GH(48/30") ERC050GH(48/30") 38.86 30.75 24.41 N/Cov. SB350Blu Connector: 2500 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120
ERC040GH(48/33") ERC050GH(48v/33") ERC060GH(48v/33") 38.86 33.15 24.41 N/Cov. SB350Blu Connector: 2900 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
ERC040RA(36/30") ERC040RG(36/30") ERC040RF(36/30") ERC040ZF(36/30") 38.86 30.75 24.41 N/Cov. SB350Gry Connector: 2500 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-25	1020	35.8	38.1	29.9	22.9	2988
ERC040RA(48/27") ERC040RF(48/27") ERC040RG(48/27") 38.86 27.36 24.41 N/Cov. SB350Blu Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
ERC040RA(48/30") ERC040RG(48/30") ERC040RF(48/30") ERC040ZF(48/30") 38.86 30.75 24.41 N/Cov. SB350Blu Connector: 2500 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120
ERC040RF(36/27") ERC050RA(36/27") 38.86 27.36 24.41 N/Cov. SB350Gry Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-23	935	32.8	38.1	26.9	22.9	2736
ERC040RF(36/33") ERC050RF(36/33") ERC040RG(36/33") ERC050RG(36/33") 38.86 33.15 24.41 N/Cov. SB350Gry Connector: 2900 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-27	1105	38.8	38.1	31.4	22.9	3240
ERC040RF(48/33") ERC040RG(48/33") 38.86 33.15 24.41 N/Cov. SB350Blu Connector: 2900 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408

YALE FORKLIFT MODEL	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
BATTERY	O	MODEL #	6 HOUR		X	Y	Z	BATTERY
COMPARTMENT	L		RATE		in.	in.	in.	WEIGHT
SIZE (Inches)	T		Ah	kWh	(L)	(W)	(H)	(Lbs.)
ERC040ZF(36/27") ERC050ZF(36/27") 38.86 27.36 24.41 N/Cov. SB350Gry Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-23	935	32.8	38.1	26.9	22.9	2736
ERC040ZF(36/33") ERC050ZF(36/33") 38.86 33.15 24.41 N/Cov. SB350Gry Connector: 2900 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-27	1105	38.8	38.1	31.4	22.9	3240
ERC040ZF(48/33") ERC050ZF(48v/33") ERC050ZG(48v/33") 38.86 33.15 24.41 N/Cov. SB350Blu Connector: 2900 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
ERC040ZG(36/27") ERC050ZG(36/27") 38.86 27.36 24.41 N/Cov. SB350Gry Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-23	935	32.8	38.1	26.9	22.9	2736
ERC040ZG(36/30") ERC050ZG(36/30") 38.86 30.75 24.41 N/Cov. SB350Gry Connector: 2500 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-25	1020	35.8	38.1	29.9	22.9	2988
ERC040ZG(36/33") ERC050ZG(36/33") ERC060ZG(36/33") 38.86 33.15 24.41 N/Cov. SB350Gry Connector: 2900 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-27	1105	38.8	38.1	31.4	22.9	3240
ERC040ZG(48/27") ERC050ZG(48/27") 38.86 27.36 24.41 N/Cov. SB350Blu Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
ERC040ZG(48/30") ERC050ZG(48/30") 38.86 30.75 24.41 N/Cov. SB350Blu Connector: 2500 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120
ERC040ZG(48/33") ERC050ZG(48v/33") ERC060ZG(48v/33") 38.86 33.15 24.41 N/Cov. SB350Blu Connector: 2900 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
ERC050RA (36/30") ERC050RF (36/30") ERC050RG (36/30") 38.86 30.75 24.41 N/Cov. SB350Gry Connector: 2500 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-25	1020	35.8	38.1	29.9	22.9	2988
ERC050RA (48/30") ERC050RF (48/30") ERC050RG (48/30") 38.86 30.75 24.41 N/Cov. SB350Blu Connector: 2500 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120
ERC050RA(48/27") ERC050RF(48/27") ERC050RG(48/27") 38.86 27.36 24.41 N/Cov. SB350Blu Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
ERC050RF(48/33") ERC060RA(48v) ERC060RF(48v) ERC050RG(48/33") 38.86 33.15 24.41 N/Cov. SB350Blu Connector: 2900 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
ERC050ZF (36/30") 38.86 30.75 24.41 N/Cov. SB350Gry Connector: 2500 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-25	1020	35.8	38.1	29.9	22.9	2988
ERC050ZF (48/30") 38.86 30.75 24.41 N/Cov. SB350Blu Connector: 2500 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120
ERC060HC (36v) ERC070HC (36v) 39.10 33.60 26.00 N/Cov. SB350Gry Connector: 3300 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-100-27	1300	Call for more information (630) 851-5800				
ERC060HC (48v) ERC070HC (48v) 39.10 33.60 26.00 N/Cov. SB350Blu Connector: 3300 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-100-21	1000	Call for more information (630) 851-5800				
ERC060RA(36v) ERC060RF(36v) ERC060RG(36v) 38.86 33.15 24.41 N/Cov. SB350Gry Connector: 2900 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-27	1105	38.8	38.1	31.4	22.9	3240

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
			Ah	kWh				
ERC060RG(48v) 38.86 33.15 24.41 N/Cov. SB350Blu Connector: 2900 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
ERC060ZF(36v) ERC060ZG(36v) 38.86 33.15 24.41 N/Cov. SB350Gry Connector: 2900 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-27	1105	38.8	38.1	31.4	22.9	3240
ERC060ZF(48v) ERC060ZG(48v) 38.86 33.15 24.41 N/Cov. SB350Blu Connector: 2900 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408
ERC065GH(36/36") 38.86 36.54 24.41 N/Cov. SB350Gry Connector: 0 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-31	1275	44.8	38.2	36.2	22.9	3780
ERC065GH(48v/36") 38.86 36.54 24.41 N/Cov. SB350Blu Connector: 0 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-23	935	43.8	38.2	35.6	22.9	3648
ERC065RF (36v) 38.86 36.54 23.15 N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	3492
ERC065RF (48v) 38.86 36.54 23.15 N/Cov. SB350Blu Connector: 3100 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-23	935	43.8	38.2	35.6	22.9	3648
ERC065RG (36v) 38.86 36.54 24.41 N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-31	1275	44.8	38.2	36.2	22.9	3780
ERC065RG (48v) 38.86 36.54 24.41 N/Cov. SB350Blu Connector: 3100 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-23	935	43.8	38.2	35.6	22.9	3648
ERC065ZF (36v) 38.86 36.54 23.15 N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	3492
ERC065ZF(48v) 38.86 36.54 23.15 N/Cov. SB350Blu Connector: 3100 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-23	935	43.8	38.2	35.6	22.9	3648

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
ERC065ZG (36v) 38.86 36.54 24.41 N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-31	1275	44.8	38.2	36.2	22.9	3780
ERC065ZG (48v) 38.86 36.54 24.41 N/Cov. SB350Blu Connector: 3100 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-23	935	43.8	38.2	35.6	22.9	3648
ERC070HD (36v) ERC080HD (36v) ERC100HD(36/39") ERC070HG (36/39") ERC080HG (36/39") 44.10 39.20 23.15 N/Cov. SB350Gry Connector: 3400 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-33	1360	47.7	38.4	38.2	22.9	4032
ERC070HD (48v) ERC080HD (48v) ERC070HG(48v) ERC080HG (48v) ERC100HD (48/39") 44.10 39.20 23.15 N/Cov. SB350Blu Connector: 3400 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-27	1105	51.7	42	38.5	22.9	4320
ERC070HH (36v) ERC080HH (36v) ERC100HH (36/39") 44.10 39.20 23.15 N/Cov. SB350Gry Connector: 3400 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-33	1360	47.7	38.4	38.2	22.9	4032
ERC070HH (48v) ERC080HH (48v) ERC100HH (48/39") 44.10 39.20 23.15 N/Cov. SB350Blu Connector: 3400 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-27	1105	51.7	42	38.5	22.9	4320
ERC100HD (36/45") ERC100HG (36/45") ERC120HG (36/45") 44.10 45.70 23.15 N/Cov. SB350Gry Connector: 4230 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	6-85-21	1700	Call for more information (630) 851-5800				
ERC100HD (48/45") ERC120HD (48v) ERC100HG(48/45") ERC120HG (48v) 44.10 45.70 23.15 N/Cov. SB350Blu Connector: 4230 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-31	1275	Call for more information (630) 851-5800				

YALE FORKLIFT MODEL	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
BATTERY	O	BATTERY	6 HOUR		X	Y	Z	BATTERY
COMPARTMENT	L	MODEL #	RATE		in.	in.	in.	WEIGHT
SIZE (Inches)	T		Ah	kWh	(L)	(W)	(H)	(Lbs.)
ERC100HG (36/39") 44.10 39.20 23.15 N/Cov. SB350Gry Connector: 3600 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-33	1360	47.7	38.4	38.2	22.9	4032
ERC100HG (48/39") 44.10 39.20 23.15 N/Cov. SB350Blu Connector: 3600 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-27	1105	51.7	42	38.5	22.9	4320
ERC100HH (36/45") ERC120HH (36/45") 44.10 45.70 23.15 N/Cov. SB350Gry Connector: 4230 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	6-85-21	1700	Call for more information (630) 851-5800				
ERC100HH (48/45") ERC120HH (48/45") 44.10 45.70 23.15 N/Cov. SB350Blu Connector: 4230 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-31	1275	Call for more information (630) 851-5800				
ERC120HD (36v) 44.10 45.70 23.15 N/Cov. SB350Gry Connector: 4230 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	6-85-21	1700	Call for more information (630) 851-5800				
ERP030B(36v) ERP035B(36v) ERP040B(36v) 39.25 27.70 23.00 N/Cov. SB350Gry Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	36 V	18-85-23	935	32.8	38.1	26.9	22.9	2736
ERP030B(48v) ERP035B(48v) 39.25 27.70 23.00 N/Cov. SB350Blu Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
ERP030TF(36v) ERP030TG(36v) 39.00 21.50 26.12 N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B30 3 Wheel-Sit down	36 V	18-85-17	680	23.9	38.1	20.1	22.9	2142
ERP030TF(48v) ERP030TG(48v) 39.00 21.50 26.12 N/Cov. SB350Blu Connector: 1700 Min. Weight: Term: B30 3 Wheel-Sit down	48 V	24-85-13	510	23.9	38.1	20.6	22.9	2256
ERP030TH(36v) 39.00 21.50 23.10 N/Cov. SB350Gry Connector: 1900 Min. Weight: Term: A20 4 Wheel-Sit down	36 V	18-85-17	680	23.9	38.1	20.1	22.9	2142
ERP030TH(48v) 39.00 21.50 23.10 N/Cov. SB350Blu Connector: 1900 Min. Weight: Term: A20 3 Wheel-Sit down	48 V	24-85-13	510	23.9	38.1	20.6	22.9	2256

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
ERP035TF(36v) ERP040TF(36v) ERP035TG(36v) ERP040TG(36v) 39.00 25.20 26.12 N/Cov. SB350Gry Connector: 2100 Min. Weight: Term: B30 3 Wheel-Sit down	36 V	18-85-21	850	29.8	38.1	24.6	22.9	2556
ERP035TF(48v) ERP035TG(48v) ERP040TF(48v) ERP040TG(48v) 39.00 25.20 26.12 N/Cov. SB350Blu Connector: 2100 Min. Weight: Term: B30 3 Wheel-Sit down	48 V	24-85-15	595	27.8	38.1	23.6	22.9	2568
ERP035TH(36v) ERP040TH(36v) 39.00 25.20 23.10 N/Cov. SB350Gry Connector: 2100 Min. Weight: Term: A20 3 Wheel-Sit down	36 V	18-85-21	850	29.8	38.1	24.6	22.9	2556
ERP035TH(48v) ERP040TH(48v) 39.00 25.20 23.10 N/Cov. SB350Blu Connector: 2100 Min. Weight: Term: A20 3 Wheel-Sit down	48 V	24-85-15	595	27.8	38.1	23.6	22.9	2568
ERP040B(48v) 39.25 27.70 23.00 N/Cov. SB350Blu Connector: 2300 Min. Weight: Term: B30 4 Wheel-Sit down	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856
ERP040DH(80v) ERP050DH(80v/28") 40.60 28.30 30.90 N/Cov. SBE320Bk Connector: 3720 Min. Weight: Term: A12 4 Wheel-Sit down	80 V	40-125-9	500	Call for more information (630) 851-5800				
ERP050DH(80v/34") ERP060DH(80v) 40.60 33.90 30.90 N/Cov. SBE320Bk Connector: 4456 Min. Weight: Term: A12 4 Wheel-Sit down	80 V	40-125-11	625	Call for more information (630) 851-5800				
ERPS030TF (36v) 39.00 16.70 26.12 N/Cov. SB350Gry Connector: 1250 Min. Weight: Term: B30 3 Wheel-Sit down	36 V	18-85-13	510	17.9	38.1	15.4	22.9	1692
ERPS030TF (48v) 39.00 16.70 26.12 N/Cov. SB350Blu Connector: 1150 Min. Weight: Term: B30 3 Wheel-Sit down	48 V	24-85-9	340	15.9	38.1	14.5	22.9	1680

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
Class 2 Trucks								
ESC020A(24v) ESC025A(24v) ESC030A(24v) 36.50 13.60 31.30 W/Cover -SB350Gry Connector: 1100 Min. Weight: Term: B20 Rider-Stand up	24 V	12-125-15	875	20.5	35.1	12.9	30.3	1692
ESC020AB(24v) ESC025AB(24v) ESC030AB(24v) 36.50 13.60 31.30 W/Cover -SB350Gry Connector: 1100 Min. Weight: Term: B20 Rider-Stand up	24 V	12-125-15	875	20.5	35.1	12.9	30.3	1692
ESC020AB(36v) ESC025AB(36v) ESC030AB(36v) 36.50 13.60 31.30 W/Cover -SB350Gry Connector: 1100 Min. Weight: Term: B20 Rider-Stand up	36 V	18-125-9	500	Call for more information (630) 851-5800				
ESC030EA (16") 38.75 16.12 31.50 W/Cover -SB350Gry Connector: 1925 Min. Weight: Term: D9 Rider-Stand up	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
ESC030FA(16") 38.60 16.30 31.10 Cover optional, Connector: 1885 Min. Weight: Term: D9 Rider-Stand up	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
ESC030FA(18") ESC035FA(18") 38.60 18.30 31.10 N/Cov 0 Connector: 2315 Min. Weight: Term: D9 Rider-Stand up	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
ESC030HC 39.00 16.00 31.00 W/Cover -SB350Gry Connector: 1400 Min. Weight: Term: B24 Rider-Stand up	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
ESC030ZA (16") ESC035ZA (16") 38.75 16.12 31.50 N/Cov. SB350Gry Connector: 1925 Min. Weight: Term: D9 Rider-Stand up	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
ESC030ZA (18") ESC035ZA (18") 38.81 18.12 31.50 N/Cov. SB350Gry Connector: 1925 Min. Weight: Term: D9 Rider-Stand up	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE		BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
			Ah	kWh				
ESC035FA(21") ESC040FA(21") 38.60 20.80 31.10 No cover req'd Connector: 2540 Min. Weight: Term: D9 Rider-Stand up	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
ESC040HC 39.00 20.80 31.00 N/Cov. SB350Gry Connector: 1600 Min. Weight: Term: B30 Rider-Stand up	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
ESC040ZA 38.88 20.75 31.50 N/Cov. SB350Gry Connector: 2700 Min. Weight: Term: D9 Rider-Stand up	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
NDR030AD (36/14") 39.00 14.60 31.50 N/Cov. SB350Gry Connector: 1550 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
NDR030AD(24/14") 39.00 14.60 31.50 N/Cov. SB350Gry Connector: 1550 Min. Weight: Term: B16 Reach-Narrow aisle	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896
NDR030AD(24/16") 39.00 16.50 31.50 N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B16 Reach-Narrow aisle	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136
NDR030AD(36/16") 39.00 16.50 31.50 N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
NDR030AE(24/14") 39.00 14.50 31.50 N/Cov. SB350Red Connector: 1550 Min. Weight: Term: B16 Reach-Narrow aisle	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896
NDR030AE(24/16") 39.00 16.50 31.50 N/Cov. SB350Red Connector: 1700 Min. Weight: Term: B16 Reach-Narrow aisle	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136
NDR030AE(36/14") 39.00 14.50 31.50 N/Cov. SB350Gry Connector: 1550 Min. Weight: Term: B16 Straddle-Narrow aisle	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
NDR030AE(36/16") 39.00 16.50 31.50 N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250

YALE FORKLIFT MODEL	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
BATTERY	O	MODEL #	6 HOUR		X	Y	Z	BATTERY
COMPARTMENT	L		RATE		in.	in.	in.	WEIGHT
SIZE (Inches)	T		Ah	kWh	(L)	(W)	(H)	(Lbs.)
NDR030BC(18") NDR030CA(18") NDR030GA(18") 39.00 18.80 31.50 N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
NDR030BC(21") 39.00 21.00 31.50 N/Cov. SB350Gry Connector: 2500 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
NDR030CB (21") 38.69 20.75 30.80 N/Cov. SB350Gry Connector: 2500 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
NDR030CB(18") NDR030GB(18") 38.69 18.50 30.80 N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
NDR030GB (21") 38.69 20.75 30.80 N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
NR035AC(24/14") NR035AD(24/14") NR040AD(24/14") NR040AC(24/14") 39.00 14.60 31.50 N/Cov. SB350Gry Connector: 1550 Min. Weight: Term: B16 Reach-Narrow aisle	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896
NR035AC(24/16") NR040AC(24/16") NR035AD(24/16") NR040AD(24/16") 39.00 16.50 31.50 N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B16 Reach-Narrow aisle	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136
NR035AC(36/16") NR040AC(36/16") NR035AD(36/16") NR040AD(36/16") 39.00 16.50 31.50 N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
NR035AD(24/12") NR035AC(24/12") NR040AD (24/12") 39.00 12.50 31.50 N/Cov. SB350Gry Connector: 1400 Min. Weight: Term: B16 Straddle-Narrow aisle	24 V	12-125-15	875	20.5	38	12	30.3	1692

YALE FORKLIFT MODEL	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
BATTERY	O	BATTERY	6 HOUR		X	Y	Z	BATTERY
COMPARTMENT	L	MODEL #	RATE		in.	in.	in.	WEIGHT
SIZE (Inches)	T		Ah	kWh	(L)	(W)	(H)	(Lbs.)
NR035AD(36/14") NR035AC(36/14") 39.00 14.60 31.50 N/Cov. SB350Gry Connector: 1550 Min. Weight: Term: B16 Straddle-Narrow aisle	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
NR035AE(24/12") NR040AE(24/12") 39.00 12.50 31.50 N/Cov. SB350Red Connector: 1400 Min. Weight: Term: B16 Straddle-Narrow aisle	24 V	12-125-15	875	20.5	38	12	30.3	1692
NR035AE(24/14") NR040AE(24/14") 39.00 14.50 31.50 N/Cov. SB350Red Connector: 1550 Min. Weight: Term: B16 Reach-Narrow aisle	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896
NR035AE(24/16") NR040AE(24/16") 39.00 16.50 31.50 N/Cov. SB350Red Connector: 1700 Min. Weight: Term: B16 Reach-Narrow aisle	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136
NR035AE(36/14") NR040AE(36/14") NR045AE(36/14") 39.00 14.50 31.50 N/Cov. SB350Gry Connector: 1550 Min. Weight: Term: B16 Straddle-Narrow aisle	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
NR035AE(36/16") NR040AE(36/16") NR045AE(36/16") 39.00 16.50 31.50 N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
NR035B(16") NDR030B(16") NR045B(16") 42.00 16.20 31.50 N/Cov. SB350Gry Connector: 2024 Min. Weight: Term: B30 Reach-Narrow aisle	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
NR035B(18") NDR030B(18") NR045B(18") 42.00 18.80 31.50 N/Cov. SB350Gry Connector: 2331 Min. Weight: Term: B30 Reach-Narrow aisle	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
NR035B(21") NDR030B(21") NR045B(21") 42.00 21.10 31.50 N/Cov. SB350Gry Connector: 2704 Min. Weight: Term: B30 Reach-Narrow aisle	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE		BATTERY DIMENSIONS			TOTAL BATTERY WEIGHT (Lbs.)
			Ah	kWh	X in. (L)	Y in. (W)	Z in. (H)	
NR035BC (18") NR045BC (18") 39.00 18.50 31.00 N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
NR035BC (20") NR045BC (20") 39.00 20.88 31.00 N/Cov. SB350Gry Connector: 2500 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
NR035EA(14") NR040EA(14") NDR030EA(14") 39.00 14.50 31.50 N/Cov. SB350Gry Connector: 1500 Min. Weight: Term: B16 Reach	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
NR035EA(16") NR040EA(16") NDR030EA(16") NR045EA(16") NDR035EA(16") 39.00 16.50 31.50 N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B16 Reach	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
NR040AC(36/14") NR045AC(14") NR045AD(14") NR040AD(36/14") 39.00 14.60 31.50 N/Cov. SB350Gry Connector: 1550 Min. Weight: Term: B16 Straddle-Narrow aisle	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
NR045AD(16") NR045AC(16") 39.00 16.50 31.50 N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
NR045CA(18") NR045GA(18") 39.00 18.80 31.50 N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
NR045CA(21") NR045GA(21") 39.00 21.00 31.50 N/Cov. SB350Gry Connector: 2500 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
NR045CB (21") 38.88 21.00 31.50 N/Cov. SB350Gry Connector: 2500 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844

YALE FORKLIFT MODEL	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
BATTERY	O	MODEL #	6 HOUR		X	Y	Z	BATTERY
COMPARTMENT	L		RATE		in.	in.	in.	WEIGHT
SIZE (Inches)	T		Ah	kWh	(L)	(W)	(H)	(Lbs.)
NR045CB(18") NR045GB(18") 38.88 18.80 31.50 N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
NR045EA(18") NDR035EA(18") 39.00 18.50 31.50 N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B16 Reach	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
NR045EA(21") NDR035EA(21") 39.00 21.50 31.50 N/Cov. SB350Gry Connector: 2500 Min. Weight: Term: B16 Reach	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
NR045GB (21") 38.88 21.00 31.50 N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844
NS040AD (24/12") 38.88 12.50 31.50 N/Cov. SB350Gry Connector: 1400 Min. Weight: Term: B30 Straddle	24 V	12-125-15	875	20.5	38	12	30.3	1692
NS040AD(24/12") 39.00 12.50 31.50 N/Cov. SB350Gry Connector: 1400 Min. Weight: Term: B16 Straddle-Narrow aisle	24 V	12-125-15	875	20.5	38	12	30.3	1692
NS040AD(24/14") 39.00 14.60 31.50 N/Cov. SB350Gry Connector: 1550 Min. Weight: Term: B16 Reach-Narrow aisle	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896
NS040AD(24/16") 39.00 16.50 31.50 N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B16 Reach-Narrow aisle	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136
NS040AD(36/14") NS050AD(36/14") 39.00 14.60 31.50 N/Cov. SB350Gry Connector: 1550 Min. Weight: Term: B16 Straddle-Narrow aisle	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
NS040AE (24/12") 38.88 12.50 31.50 N/Cov. SB350Gry Connector: 1400 Min. Weight: Term: B30 Straddle	24 V	12-125-15	875	20.5	38	12	30.3	1692
NS040AE (24/14") 38.88 14.60 31.50 N/Cov. SB350Gry Connector: 1550 Min. Weight: Term: B30 Straddle	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896

YALE FORKLIFT MODEL	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
BATTERY	O	BATTERY	6 HOUR		X	Y	Z	BATTERY
COMPARTMENT	L	MODEL #	RATE		in.	in.	in.	WEIGHT
SIZE (Inches)	T		Ah	kWh	(L)	(W)	(H)	(Lbs.)
NS040AE (24/16") 38.88 16.60 31.50 N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B30 Straddle	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136
NS040AE (36/16") NS050AE (16") 38.88 16.60 31.50 N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B30 Straddle	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
NS040AF(24/12") 38.80 12.50 31.50 N/Cov. SB350Red Connector: 1400 Min. Weight: Term: B16 Straddle-Narrow aisle	24 V	12-125-15	875	20.5	38	12	30.3	1692
NS040AF(24/14") 38.80 14.50 31.50 N/Cov. SB350Red Connector: 1550 Min. Weight: Term: B16 Reach-Narrow aisle	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896
NS040AF(24/16") 38.80 16.50 31.50 N/Cov. SB350Red Connector: 1700 Min. Weight: Term: B16 Reach-Narrow aisle	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136
NS040AF(36/14") NS050AF(36/14") 39.00 14.50 31.50 N/Cov. SB350Gry Connector: 1550 Min. Weight: Term: B16 Straddle-Narrow aisle	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
NS040AF(36/16") NS050AF(36/16") 39.00 16.35 31.50 N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B16 Reach-Narrow aisle	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250
NS050AE (14') NS040AE (36/14") 38.88 14.60 31.50 N/Cov. SB350Gry Connector: 1550 Min. Weight: Term: B30 Straddle	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890
NTA030SA 44.37 21.26 32.28 N/Cov. SB350Blu Connector: 2640 Min. Weight: Term: B30 Turret	48 V	24-125-13	750	35.1	44	20.6	30.3	3000
NTA030SB(LWB,23.6") 38.70 23.60 31.00 N/Cov. SB350Blu Connector: 3087 Min. Weight: Term: B30 Turret truck	48 V	24-125-15	875	41	38.2	23.6	30.3	3384
NTA030SB(LWB,26.8") 38.40 26.80 31.00 N/Cov. SB350Blu Connector: 3087 Min. Weight: Term: B30 Turret truck	48 V	24-125-17	1000	46.8	38.1	26.6	30.3	3792

YALE FORKLIFT MODEL	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL
BATTERY	O	BATTERY	6 HOUR		X	Y	Z	BATTERY
COMPARTMENT	L	MODEL #	RATE		in.	in.	in.	WEIGHT
SIZE (Inches)	T		Ah	kWh	(L)	(W)	(H)	(Lbs.)
NTA030SB(LWB,27") 38.70 27.00 31.00	48 V	24-125-17	1000	46.8	38.1	26.6	30.3	3792
N/Cov. SB350Blu Connector: 3087 Min. Weight: Term: B30 Turret truck								
NTA030SB(MWB,20.8") 44.20 20.80 31.00	48 V	24-125-13	750	35.1	44	20.6	30.3	3000
N/Cov. SB350Blu Connector: 2976 Min. Weight: Term: B30 Turret truck								
NTA030SB(MWB,23.8") 38.70 23.80 31.00	48 V	24-125-15	875	41	38.2	23.6	30.3	3384
N/Cov. SB350Blu Connector: 2976 Min. Weight: Term: B30 Turret truck								
NTA035SB(LWB,17.9") 38.30 17.90 31.00	72 V	18-125-15	875	Call for more information (630) 851-5800				
N/Cov. SB350Grn Connector: 4189 Min. Weight: Term: B30 Turret truck								
NTA035SB(LWB,20.1") 38.30 20.10 31.00	72 V	18-125-17	1000	Call for more information (630) 851-5800				
N/Cov. SB350Grn Connector: 4189 Min. Weight: Term: B30 Turret truck								
NTA035SB(LWB,20.4") 38.70 20.40 31.00	72 V	18-125-17	1000	Call for more information (630) 851-5800				
N/Cov. SB350Grn Connector: 4189 Min. Weight: Term: B30 Turret truck								
NTA035SB(MWB,15.5") 37.90 15.50 31.00	72 V	18-125-13	750	Call for more information (630) 851-5800				
N/Cov. SB350Grn Connector: 4079 Min. Weight: Term: B30 Turret truck								
NTA035SB(MWB,15.8") 38.10 15.80 31.00	72 V	18-125-13	750	26.3	Call for more information (630) 851-5800			
N/Cov. SB350Grn Connector: 4079 Min. Weight: Term: B30 Turret truck								
NTA035SB(SWB,13.5") 38.30 13.50 31.00	72 V	18-125-11	625	Call for more information (630) 851-5800				
N/Cov. SB350Grn Connector: 3307 Min. Weight: Term: B30 Turret truck								
NTA035SB(SWB,14") 37.90 14.00 31.00	72 V	18-125-11	625	Call for more information (630) 851-5800				
N/Cov. SB350Grn Connector: 3307 Min. Weight: Term: B30 Turret truck								
NTA035SB(SWB,26.7") 38.30 26.70 31.00	72 V	125-11	Call for more information (630) 851-5800					
N/Cov. SB350Grn Connector: 3307 Min. Weight: Term: B30 Turret truck								
NTA040DA 46.15 37.60 33.25	72 V	6-125-13	750	Call for more information (630) 851-5800				
N/Cov. SB350Gry Connector: 4200 Min. Weight: Term: B12 Turret								

YALE FORKLIFT MODEL	V	BATTERY	CAPACITY		BATTERY DIMENSIONS			TOTAL	
BATTERY	O	BATTERY	6 HOUR		X	Y	Z	BATTERY	
COMPARTMENT	L	MODEL #	RATE		in.	in.	in.	WEIGHT	
SIZE (Inches)	T		Ah	kWh	(L)	(W)	(H)	(Lbs.)	
NTA040SA 40.43 27.87 34.40	72 V	6-125-11	625	Call for more information (630) 851-5800					
N/Cov. SB350Gry Connector: 3300 Min. Weight: Term: B12 Turret									
OS030BC 39.00 14.60 31.50	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896	
N/Cov. SB350Red Connector: 1550 Min. Weight: Term: B16 Order Picker									
OS030BD(36V) OS030BE(36V) 39.00 14.60 31.50	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350Red Connector: 1500 Min. Weight: Term: B16 Order Picker									
OS030BE (24V) 39.00 14.60 31.50	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896	
N/Cov. SB350Red Connector: 1600 Min. Weight: Term: B16 Order Picker									
OS030EA OS030EB OS030EC 36.00 13.50 25.00	24 V	12-85-15	595	13.9	35.1	12.9	30.3	1284	
N/Cov. SB175Gry Connector: 945 Min. Weight: Term: B16 Order Picker									
SS030B 36.50 15.30 40.00	24 V	12-125-15	875	20.5	36	14	30.3	1692	
Battery cover option 320-SB350Gry Connector: 1480 Min. Weight: Term: A30 Order picker									
SS030BC 39.00 14.60 31.50	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896	
N/Cov. SB350Gry Connector: 1550 Min. Weight: Term: B16 Order Picker									
SS030BD(36V) SS030BE(36V) 39.00 14.60 31.50	36 V	18-125-11	625	21.9	38.1	13.1	30.3	1890	
N/Cov. SB350Gry Connector: 1500 Min. Weight: Term: B16 Order Picker									
SS030BE (24V) 39.00 14.60 31.50	24 V	12-125-17	1000	23.4	38	13.5	30.3	1896	
N/Cov. SB175Gry Connector: 1500 Min. Weight: Term: B16 Reach-Narrow aisle									
CLASS 3 TRUCKS									
MCW020(12v) MCW025(12v) MCW030(12v) 31.87 13.36 40.00	12 V	6-85-21	850	Call for more information (630) 851-581					852
W/Cover SB175Gry Connector: 400 Min. Weight: Term: B20 Pallet-Hand trucks									

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
MCW020(24v) MCW025(24v) MCW030(24v) MCW040 31.87 13.36 40.00 W/Cover SB175Gry Connector: 500 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
MCW025-E (13") MCW030-E (13") MCW040-E (13") 33.00 13.50 40.00 W/Cover SB175Red Connector: 600 Min. Weight: Term: B20 Pallet-Stacker-Counter	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
MLW040 (12/13") MLW060 (12/13") 32.00 13.50 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	12 V	6-85-19	765	Call for more information (630) 851-5800				
MLW040 (12/8") MLW060 (12/8") 32.00 8.10 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	12 V	6-85-13	510	6	30.6	7.8	23.3	564
MLW040 (24/13") MLW060 (24/13") 32.00 13.50 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
MLW040 (24/8") MLW060 (24/8") 32.00 8.10 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-5	170	4	24.8	7.8	23.3	576
MP040A MP030A 29.50 7.60 25.40 W/Cover SB175Gry Connector: 0 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-5	170	4	24.9	6.5	23.3	576
MP040AC(24.3"H) 28.97 7.69 24.30 N/Cov. SB175Gry Connector: 0 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-5	170	4	24.8	7.8	23.3	576
MP040AC(Open) 25.75 6.88 40.00 N/Cov. SB175Gry Connector: 0 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-5	170	4	24.9	6.5	23.3	576
MPB030A MPB040A 29.50 7.60 25.40 W/Cover SB175Gry Connector: 0 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-5	170	4	24.9	6.5	23.3	576

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
MPB040AC(24.3"H) 28.97 7.69 24.30 N/Cov. SB175Gry Connector: 0 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-5	170	4	24.9	6.5	23.3	576
MPB040AC(Open) 25.75 6.88 40.00 N/Cov. SB175Gry Connector: 0 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-5	170	4	24.9	6.5	23.3	576
MPB040-E 28.97 8.50 28.00 W/Cover SB175Red Connector: 0 Min. Weight: Term: B16 Pallet-Hand trucks	24 V	12-85-5	170	4	24.8	7.8	23.3	576
MPC060 MPC060AD MPC060LD MPC060-E 32.00 13.40 40.00 W/Cover SB175Gry Connector: 0 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
MPC080 MPC080AD MPC080LD MPC080-E 32.00 13.40 40.00 W/Cover SB175Red Connector: 0 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
MPE060(12/13") 32.00 13.40 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	12 V	6-85-19	765	Call for more information (630) 851-5800				
MPE060(12/9") 32.00 9.00 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	12 V	6-85-13	510	6	30.6	7.8	23.3	564
MPE060(24/13") MPE80(24/13") 32.00 13.40 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
MPE060(24/9") MPE80(24/9") 32.00 9.00 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-7	255	6	25.3	8.7	23.3	708
MPE060-E(24/13") MPE80-E(24/13") 32.00 13.40 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
MPE060-E(24/9") MPE80-E(24/9") 32.00 9.00 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-7	255	6	25.3	8.7	23.3	708

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
MPE060-LE(13") MPE080-E(13") 32.00 13.40 40.00 W/Cover SB175Red Connector: 300 Min. Weight: Term: B16 Pallet-Hand trucks	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
MPW045DA 31.75 8.10 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	12 V	6-85-13	510	6	30.6	7.8	23.3	564
MPW045-E(12v) 31.75 8.10 40.00 W/Cover SB175Red Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	12 V	6-85-13	510	6	30.6	7.8	23.3	564
MPW045-E(24v) 28.50 9.10 40.00 W/Cover SB175Red Connector: 410 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-7	255	6	25.3	8.7	23.3	708
MPW050-E(24v) 28.00 9.10 40.00 W/Cover SB175Red Connector: 410 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-7	255	6	25.3	8.7	23.3	708
MPW060(12/13") MPW065-E(13") 32.00 13.40 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	12 V	6-85-19	765	Call for more information (630) 851-5800				
MPW060(12/9") MPW065-E(9") 32.00 9.00 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	12 V	6-85-13	510	6	30.6	7.8	23.3	564
MPW060(24/13") MPW80(24/13") 32.00 13.40 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-13	510		30.6	12.8	23.3	1128
MPW060(24/9") MPW80(24/9") 32.00 9.00 40.00 W/Cover SB175Gry Connector: 300 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-7	255	6	25.3	8.7	23.3	708
MPW060-E(13") 32.00 13.40 40.00 W/Cover SB175Red Connector: 300 Min. Weight: Term: B16 Pallet-Hand trucks	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
MPW060-E(9") 32.00 9.00 40.00 W/Cover SB175Red Connector: 300 Min. Weight: Term: B16 Pallet-Hand trucks	24 V	12-85-7	255	6	25.3	8.7	23.3	708
MPW060-LE(13") MPW080-E(13") 32.00 13.40 40.00 W/Cover SB175Red Connector: 300 Min. Weight: Term: B16 Pallet-Hand trucks	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
MPW080-E(9") 32.00 9.00 40.00 W/Cover SB175Red Connector: 300 Min. Weight: Term: B16 Pallet-Hand trucks	24 V	12-85-7	255	6	25.3	8.7	23.3	708
MRW020 (12/13") MRW030 (12/13") 35.40 13.50 40.00 W/Cover SB175Gry Connector: 400 Min. Weight: Term: B20 Pallet-Hand trucks	12 V	6-85-25	1020	11.9	29.2	12.9	23.3	996
MRW020 (12/8") MRW030 (12/8") 35.40 8.12 40.00 W/Cover SB175Gry Connector: 400 Min. Weight: Term: B20 Pallet-Hand trucks	12 V	6-85-13	510	Call for more information (630) 851-5800				
MRW020 (24/13") MRW030 (24/13") 35.40 13.50 40.00 W/Cover SB175Gry Connector: 400 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
MRW020/30 (24/8") 35.40 8.12 40.00 W/Cover SB175Gry Connector: 400 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-7	255	6	33.6	6.5	23.3	708
MRW020-E (13") MRW030-E (13") 33.00 13.50 40.00 W/Cover SB175Red Connector: 600 Min. Weight: Term: B20 Pallet-Reach/Stacker	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
MSW020 (12/8") MSW030 (12/8") 35.40 8.12 40.00 W/Cover SB175Gry Connector: 400 Min. Weight: Term: B20 Pallet-Hand trucks	12 V	6-85-13	510	Call for more information (630) 851-5800				
MSW020 (24/13") MSW030 (24/13") MSW040 (13") 35.40 13.50 40.00 W/Cover SB175Gry Connector: 400 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128

YALE FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY MODEL #	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
MSW020 (24/8") MSW030 (24/8") MSW040 (8") 35.40 8.12 40.00 W/Cover SB175Gry Connector: 400 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-7	255	6	33.6	6.5	23.3	708
MSW020-E(9") 27.80 8.10 40.00 W/Cover SBX175Rd Connector: 310 Min. Weight: Term: B20 Pallet-Straddle	24 V	12-100-5	Call for more information (630) 851-5800					
MSW025-E(9") 27.80 9.00 40.00 W/Cover SB175Red Connector: 350 Min. Weight: Term: B20 Pallet-Straddle	24 V	12-85-7	255	6	25.4	8.7	23.3	708
MSW030 (12/13") MSW020 (12/13") 35.40 13.50 40.00 W/Cover SB175Gry Connector: 400 Min. Weight: Term: B20 Pallet-Hand trucks	12 V	6-85-25	1020	11.9	29.2	12.9	23.3	996
MSW030-E (13") MSW040-E (13") 33.00 13.50 40.00 W/Cover SB175Red Connector: 600 Min. Weight: Term: B20 Pallet-Straddle	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
MSW030-E (9") MSW040-E (9") 33.00 9.00 40.00 W/Cover SB175Red Connector: 600 Min. Weight: Term: B20 Pallet-Straddle	24 V	12-85-7	255	6	25.4	8.7	23.3	708
MTR 31.50 13.40 40.00 W/Cover SB175Gry Connector: 800 Min. Weight: Term: B20 Pallet-Hand trucks	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128
MTR005-E MTR007-E 31.30 13.40 40.00 W/Cover SB175Red Connector: 880 Min. Weight: Term: B16 Tow tractor	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128